Gateway Documentation - Bills and Collections Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.87.1.0

[August] [2014]

Table Of Contents

1. BACKGROUND **1**

2. FCUBSBCService **2**

2.1. QueryPayment **2**

2.1.1. BC-Payment-Query-Req-Msg.xsd *2*

2.1.2. BC-Payment-Query-Res-Full-Msg.xsd *9*

2.2. NewPayment **75**

2.2.1. BC-Payment-Req-Full-MSG.xsd *75*

2.2.2. BC-Payment-Req-MSG.xsd *140*

2.2.3. BC-Payment-Res-Full-MSG.xsd *205*

2.2.4. BC-Payment-Res-MSG.xsd *272*

2.3. ReversePayment **340**

2.3.1. BC-Payment-Rev-Req-Full-MSG.xsd *340*

2.3.2. BC-Payment-Rev-Req-IO-MSG.xsd *405*

2.3.3. BC-Payment-Rev-Res-Full-MSG.xsd *412*

2.3.4. BC-Payment-Rev-Res-IO-MSG.xsd *479*

2.4. QueryAmendConfirm **488**

2.4.1. BC-QueryAmendConfirm-Req-IO-MSG.xsd *488*

2.4.2. BC-QueryAmendConfirm-Res-Full-MSG.xsd *494*

2.5. QueryBCGoods **580**

2.5.1. BC-QueryBCGoods-Req-IO-MSG.xsd *580*

2.5.2. BC-QueryBCGoods-Res-Full-MSG.xsd *587*

2.6. QueryBCPayment **599**

2.6.1. BC-QueryBCPayment-Req-IO-MSG.xsd *599*

2.6.2. BC-QueryBCPayment-Res-Full-MSG.xsd *605*

2.7. QueryBrnPrm **680**

2.7.1. BC-QueryBrnPrm-Req-IO-MSG.xsd *680*

2.7.2. BC-QueryBrnPrm-Res-Full-MSG.xsd *686*

2.8. QueryCollectRegistration **698**

2.8.1. BC-QueryCollectRegistration-Req-IO-MSG.xsd *698*

2.8.2. BC-QueryCollectRegistration-Res-Full-MSG.xsd *704*

2.9. QueryContract **723**

2.9.1. BC-QueryContract-Req-IO-MSG.xsd *723*

2.9.2. BC-QueryContract-Res-Full-MSG.xsd *730*

2.10. QueryDocArrival **960**

2.10.1. BC-QueryDocArrival-Req-IO-MSG.xsd *960*

2.10.2. BC-QueryDocArrival-Res-Full-MSG.xsd *966*

2.11. QueryProduct **988**

2.11.1. BC-QueryProduct-Req-IO-MSG.xsd *988*

2.11.2. BC-QueryProduct-Res-Full-MSG.xsd *994*

2.12. ReverseBCPayment **1083**

2.12.1. BC-ReverseBCPayment-Req-Full-MSG.xsd *1083*

2.12.2. BC-ReverseBCPayment-Req-IO-MSG.xsd *1156*

2.12.3. BC-ReverseBCPayment-Res-Full-MSG.xsd *1162*

2.12.4. BC-ReverseBCPayment-Res-PK-MSG.xsd *1237*

2.13. ReverseContract **1246**

2.13.1. BC-ReverseContract-Req-Full-MSG.xsd *1246*

2.13.2. BC-ReverseContract-Req-IO-MSG.xsd *1474*

2.13.3. BC-ReverseContract-Res-Full-MSG.xsd *1480*

2.13.4. BC-ReverseContract-Res-PK-MSG.xsd *1709*

2.14. RolloverContract **1718**

2.14.1. BC-RolloverContract-Req-Full-MSG.xsd *1718*

2.14.2. BC-RolloverContract-Req-IO-MSG.xsd *1946*

2.14.3. BC-RolloverContract-Res-Full-MSG.xsd *1966*

2.14.4. BC-RolloverContract-Res-PK-MSG.xsd *2195*

2.15. AuthBCAmndBillAmt **2217**
2.15.1. BCBill-Amt-Amnd-Auth-Req-MSG.xsd *2217*
2.15.2. BCBill-Amt-Amnd-Auth-Res-MSG.xsd *2225*
2.16. CreateBCAmendBillAmt **2235**
2.16.1. BCBill-Amt-Amnd-Create-Req-Full-MSG.xsd *2235*
2.16.2. BCBill-Amt-Amnd-Create-Req-MSG.xsd *2252*
2.16.3. BCBill-Amt-Amnd-Create-Res-Full-MSG.xsd *2260*
2.16.4. BCBill-Amt-Amnd-Create-Res-MSG.xsd *2278*
2.17. DeleteBCAmendBillAmt **2290**
2.17.1. BCBill-Amt-Amnd-Delete-Req-Full-MSG.xsd *2290*
2.17.2. BCBill-Amt-Amnd-Delete-Req-MSG.xsd *2307*
2.17.3. BCBill-Amt-Amnd-Delete-Res-Full-MSG.xsd *2315*
2.17.4. BCBill-Amt-Amnd-Delete-Res-MSG.xsd *2333*
2.18. QueryBCAmendBillAmt **2345**
2.18.1. BCBill-Amt-Amnd-Query-Req-MSG.xsd *2345*
2.18.2. BCBill-Amt-Amnd-Query-Res-Full-MSG.xsd *2352*
2.19. DeleteProduct **2370**
2.19.1. BC-DeleteProduct-Req-Full-MSG.xsd *2370*
2.19.2. BC-DeleteProduct-Req-IO-MSG.xsd *2456*
2.19.3. BC-DeleteProduct-Res-Full-MSG.xsd *2462*
2.19.4. BC-DeleteProduct-Res-PK-MSG.xsd *2550*
2.20. ExecuteQueryDocs **2558**
2.20.1. BC-ExecuteQueryDocs-Req-IO-MSG.xsd *2558*
2.20.2. BC-ExecuteQueryDocs-Res-Full-MSG.xsd *2565*
2.21. ExecuteQueryFfts **2580**
2.21.1. BC-ExecuteQueryFfts-Req-IO-MSG.xsd *2580*
2.21.2. BC-ExecuteQueryFfts-Res-Full-MSG.xsd *2587*
2.22. LiquidateContract **2600**
2.22.1. BC-LiquidateContract-Req-Full-MSG.xsd *2600*
2.22.2. BC-LiquidateContract-Req-IO-MSG.xsd *2828*
2.22.3. BC-LiquidateContract-Res-Full-MSG.xsd *2875*
2.22.4. BC-LiquidateContract-Res-PK-MSG.xsd *3104*
2.23. ModifyAmendConfirm **3153**
2.23.1. BC-ModifyAmendConfirm-Req-Full-MSG.xsd *3153*
2.23.2. BC-ModifyAmendConfirm-Req-IO-MSG.xsd *3237*
2.23.3. BC-ModifyAmendConfirm-Res-Full-MSG.xsd *3274*
2.23.4. BC-ModifyAmendConfirm-Res-PK-MSG.xsd *3360*
2.24. ModifyBCDisc **3399**
2.24.1. BC-ModifyBCDisc-Req-Full-MSG.xsd *3399*
2.24.2. BC-ModifyBCDisc-Req-IO-MSG.xsd *3409*
2.24.3. BC-ModifyBCDisc-Res-Full-MSG.xsd *3418*
2.24.4. BC-ModifyBCDisc-Res-PK-MSG.xsd *3430*
2.25. ModifyBCGoods **3446**
2.25.1. BC-ModifyBCGoods-Req-Full-MSG.xsd *3446*
2.25.2. BC-ModifyBCGoods-Req-IO-MSG.xsd *3457*
2.25.3. BC-ModifyBCGoods-Res-Full-MSG.xsd *3466*
2.25.4. BC-ModifyBCGoods-Res-PK-MSG.xsd *3478*
2.26. ModifyBCPayment **3494**
2.26.1. BC-ModifyBCPayment-Req-Full-MSG.xsd *3494*
2.26.2. BC-ModifyBCPayment-Req-IO-MSG.xsd *3567*
2.26.3. BC-ModifyBCPayment-Res-Full-MSG.xsd *3606*
2.26.4. BC-ModifyBCPayment-Res-PK-MSG.xsd *3681*
2.27. ModifyCollectRegistration **3723**
2.27.1. BC-ModifyCollectRegistration-Req-Full-MSG.xsd *3723*
2.27.2. BC-ModifyCollectRegistration-Req-IO-MSG.xsd *3740*
2.27.3. BC-ModifyCollectRegistration-Res-Full-MSG.xsd *3748*
2.27.4. BC-ModifyCollectRegistration-Res-PK-MSG.xsd *3766*

2.28. ModifyContract **3776**
2.28.1. BC-ModifyContract-Req-Full-MSG.xsd *3776*
2.28.2. BC-ModifyContract-Req-IO-MSG.xsd *4004*
2.28.3. BC-ModifyContract-Res-Full-MSG.xsd *4139*
2.28.4. BC-ModifyContract-Res-PK-MSG.xsd *4368*
2.29. ModifyDocArrival **4505**
2.29.1. BC-ModifyDocArrival-Req-Full-MSG.xsd *4505*
2.29.2. BC-ModifyDocArrival-Req-IO-MSG.xsd *4525*
2.29.3. BC-ModifyDocArrival-Res-Full-MSG.xsd *4539*
2.29.4. BC-ModifyDocArrival-Res-PK-MSG.xsd *4560*
2.30. ModifyDocs **4577**
2.30.1. BC-ModifyDocs-Req-Full-MSG.xsd *4577*
2.30.2. BC-ModifyDocs-Req-IO-MSG.xsd *4589*
2.30.3. BC-ModifyDocs-Res-Full-MSG.xsd *4599*
2.30.4. BC-ModifyDocs-Res-PK-MSG.xsd *4613*
2.31. ModifyFfts **4632**
2.31.1. BC-ModifyFfts-Req-Full-MSG.xsd *4632*
2.31.2. BC-ModifyFfts-Req-IO-MSG.xsd *4643*
2.31.3. BC-ModifyFfts-Res-Full-MSG.xsd *4652*
2.31.4. BC-ModifyFfts-Res-PK-MSG.xsd *4664*
2.32. ModifyProduct **4680**
2.32.1. BC-ModifyProduct-Req-Full-MSG.xsd *4680*
2.32.2. BC-ModifyProduct-Req-IO-MSG.xsd *4766*
2.32.3. BC-ModifyProduct-Res-Full-MSG.xsd *4838*
2.32.4. BC-ModifyProduct-Res-PK-MSG.xsd *4926*
2.33. NewFfts **5000**
2.33.1. BC-NewFfts-Req-Full-MSG.xsd *5000*
2.33.2. BC-NewFfts-Req-IO-MSG.xsd *5011*
2.33.3. BC-NewFfts-Res-Full-MSG.xsd *5021*
2.33.4. BC-NewFfts-Res-PK-MSG.xsd *5033*
2.34. AuthPayment **5051**
2.34.1. BC-Payment-Auth-Req-Full-MSG.xsd *5051*
2.34.2. BC-Payment-Auth-Req-IO-MSG.xsd *5061*
2.34.3. BC-Payment-Auth-Res-Full-MSG.xsd *5068*
2.34.4. BC-Payment-Auth-Res-IO-MSG.xsd *5079*
2.35. DeletePayment **5092**
2.35.1. BC-Payment-Del-Req-Full-MSG.xsd *5092*
2.35.2. BC-Payment-Del-Req-IO-MSG.xsd *5157*
2.35.3. BC-Payment-Del-Res-Full-MSG.xsd *5164*
2.35.4. BC-Payment-Del-Res-IO-MSG.xsd *5231*
2.36. CreateBCGoods **5299**
2.36.1. BC-CreateBCGoods-Req-Full-MSG.xsd *5299*
2.36.2. BC-CreateBCGoods-Req-IO-MSG.xsd *5310*
2.36.3. BC-CreateBCGoods-Res-Full-MSG.xsd *5321*
2.36.4. BC-CreateBCGoods-Res-PK-MSG.xsd *5338*
2.37. CreateBCPayment **5356**
2.37.1. BC-CreateBCPayment-Req-Full-MSG.xsd *5356*
2.37.2. BC-CreateBCPayment-Req-IO-MSG.xsd *5429*
2.37.3. BC-CreateBCPayment-Res-Full-MSG.xsd *5487*
2.37.4. BC-CreateBCPayment-Res-PK-MSG.xsd *5562*
2.38. CreateCollectRegistration **5622**
2.38.1. BC-CreateCollectRegistration-Req-Full-MSG.xsd *5622*
2.38.2. BC-CreateCollectRegistration-Req-IO-MSG.xsd *5639*
2.38.3. BC-CreateCollectRegistration-Res-Full-MSG.xsd *5655*
2.38.4. BC-CreateCollectRegistration-Res-PK-MSG.xsd *5673*
2.39. CreateContract **5691**
2.39.1. BC-CreateContract-Req-Full-MSG.xsd *5691*
2.39.2. BC-CreateContract-Req-IO-MSG.xsd *5919*

2.39.3. BC-CreateContract-Res-Full-MSG.xsd *6086*
2.39.4. BC-CreateContract-Res-PK-MSG.xsd *6315*
2.40. CreateDocArrival **6484**
2.40.1. BC-CreateDocArrival-Req-Full-MSG.xsd *6484*
2.40.2. BC-CreateDocArrival-Req-IO-MSG.xsd *6504*
2.40.3. BC-CreateDocArrival-Res-Full-MSG.xsd *6522*
2.40.4. BC-CreateDocArrival-Res-PK-MSG.xsd *6543*
2.41. CreateDocs **6563**
2.41.1. BC-CreateDocs-Req-Full-MSG.xsd *6563*
2.41.2. BC-CreateDocs-Req-IO-MSG.xsd *6575*
2.41.3. BC-CreateDocs-Res-Full-MSG.xsd *6587*
2.41.4. BC-CreateDocs-Res-PK-MSG.xsd *6601*
2.42. CreateProduct **6622**
2.42.1. BC-CreateProduct-Req-Full-MSG.xsd *6622*
2.42.2. BC-CreateProduct-Req-IO-MSG.xsd *6708*
2.42.3. BC-CreateProduct-Res-Full-MSG.xsd *6782*
2.42.4. BC-CreateProduct-Res-PK-MSG.xsd *6870*
2.43. DeleteAmendConfirm **6947**
2.43.1. BC-DeleteAmendConfirm-Req-Full-MSG.xsd *6947*
2.43.2. BC-DeleteAmendConfirm-Req-IO-MSG.xsd *7031*
2.43.3. BC-DeleteAmendConfirm-Res-Full-MSG.xsd *7037*
2.43.4. BC-DeleteAmendConfirm-Res-PK-MSG.xsd *7123*
2.44. DeleteBCDisc **7132**
2.44.1. BC-DeleteBCDisc-Req-Full-MSG.xsd *7132*
2.44.2. BC-DeleteBCDisc-Req-IO-MSG.xsd *7142*
2.44.3. BC-DeleteBCDisc-Res-Full-MSG.xsd *7149*
2.44.4. BC-DeleteBCDisc-Res-PK-MSG.xsd *7161*
2.45. DeleteBCGoods **7175**
2.45.1. BC-DeleteBCGoods-Req-Full-MSG.xsd *7175*
2.45.2. BC-DeleteBCGoods-Req-IO-MSG.xsd *7186*
2.45.3. BC-DeleteBCGoods-Res-Full-MSG.xsd *7193*
2.45.4. BC-DeleteBCGoods-Res-PK-MSG.xsd *7205*
2.46. DeleteBCPayment **7219**
2.46.1. BC-DeleteBCPayment-Req-Full-MSG.xsd *7219*
2.46.2. BC-DeleteBCPayment-Req-IO-MSG.xsd *7292*
2.46.3. BC-DeleteBCPayment-Res-Full-MSG.xsd *7298*
2.46.4. BC-DeleteBCPayment-Res-PK-MSG.xsd *7373*
2.47. DeleteCollectRegistration **7382**
2.47.1. BC-DeleteCollectRegistration-Req-Full-MSG.xsd *7382*
2.47.2. BC-DeleteCollectRegistration-Req-IO-MSG.xsd *7399*
2.47.3. BC-DeleteCollectRegistration-Res-Full-MSG.xsd *7405*
2.47.4. BC-DeleteCollectRegistration-Res-PK-MSG.xsd *7423*
2.48. DeleteContract **7432**
2.48.1. BC-DeleteContract-Req-Full-MSG.xsd *7432*
2.48.2. BC-DeleteContract-Req-IO-MSG.xsd *7660*
2.48.3. BC-DeleteContract-Res-Full-MSG.xsd *7666*
2.48.4. BC-DeleteContract-Res-PK-MSG.xsd *7895*
2.49. DeleteDocArrival **7904**
2.49.1. BC-DeleteDocArrival-Req-Full-MSG.xsd *7904*
2.49.2. BC-DeleteDocArrival-Req-IO-MSG.xsd *7924*
2.49.3. BC-DeleteDocArrival-Res-Full-MSG.xsd *7930*
2.49.4. BC-DeleteDocArrival-Res-PK-MSG.xsd *7951*
2.50. DeleteDocs **7960**
2.50.1. BC-DeleteDocs-Req-Full-MSG.xsd *7960*
2.50.2. BC-DeleteDocs-Req-IO-MSG.xsd *7972*
2.50.3. BC-DeleteDocs-Res-Full-MSG.xsd *7979*
2.50.4. BC-DeleteDocs-Res-PK-MSG.xsd *7993*
2.51. DeleteFfts **8008**

2.51.1. BC-DeleteFfts-Req-Full-MSG.xsd *8008*
2.51.2. BC-DeleteFfts-Req-IO-MSG.xsd *8019*
2.51.3. BC-DeleteFfts-Res-Full-MSG.xsd *8026*
2.51.4. BC-DeleteFfts-Res-PK-MSG.xsd *8038*
2.52. AuthBCDisc **8052**
2.52.1. BC-AuthBCDisc-Req-Full-MSG.xsd *8052*
2.52.2. BC-AuthBCDisc-Req-IO-MSG.xsd *8062*
2.52.3. BC-AuthBCDisc-Res-Full-MSG.xsd *8069*
2.52.4. BC-AuthBCDisc-Res-PK-MSG.xsd *8082*
2.53. AuthBCGoods **8096**
2.53.1. BC-AuthBCGoods-Req-Full-MSG.xsd *8096*
2.53.2. BC-AuthBCGoods-Req-IO-MSG.xsd *8107*
2.53.3. BC-AuthBCGoods-Res-Full-MSG.xsd *8114*
2.53.4. BC-AuthBCGoods-Res-PK-MSG.xsd *8127*
2.54. AuthDocs **8141**
2.54.1. BC-AuthDocs-Req-Full-MSG.xsd *8141*
2.54.2. BC-AuthDocs-Req-IO-MSG.xsd *8153*
2.54.3. BC-AuthDocs-Res-Full-MSG.xsd *8160*
2.54.4. BC-AuthDocs-Res-PK-MSG.xsd *8175*
2.55. AuthFfts **8191**
2.55.1. BC-AuthFfts-Req-Full-MSG.xsd *8191*
2.55.2. BC-AuthFfts-Req-IO-MSG.xsd *8202*
2.55.3. BC-AuthFfts-Res-Full-MSG.xsd *8209*
2.55.4. BC-AuthFfts-Res-PK-MSG.xsd *8222*
2.56. AuthorizeAmendConfirm **8236**
2.56.1. BC-AuthorizeAmendConfirm-Req-Full-MSG.xsd *8236*
2.56.2. BC-AuthorizeAmendConfirm-Req-IO-MSG.xsd *8320*
2.56.3. BC-AuthorizeAmendConfirm-Res-Full-MSG.xsd *8326*
2.56.4. BC-AuthorizeAmendConfirm-Res-PK-MSG.xsd *8412*
2.57. AuthorizeBCPayment **8421**
2.57.1. BC-AuthorizeBCPayment-Req-Full-MSG.xsd *8421*
2.57.2. BC-AuthorizeBCPayment-Req-IO-MSG.xsd *8494*
2.57.3. BC-AuthorizeBCPayment-Res-Full-MSG.xsd *8500*
2.57.4. BC-AuthorizeBCPayment-Res-PK-MSG.xsd *8575*
2.58. AuthorizeBrnPrm **8584**
2.58.1. BC-AuthorizeBrnPrm-Req-Full-MSG.xsd *8584*
2.58.2. BC-AuthorizeBrnPrm-Req-IO-MSG.xsd *8594*
2.58.3. BC-AuthorizeBrnPrm-Res-Full-MSG.xsd *8600*
2.58.4. BC-AuthorizeBrnPrm-Res-PK-MSG.xsd *8612*
2.59. AuthorizeCollectRegistration **8620**
2.59.1. BC-AuthorizeCollectRegistration-Req-Full-MSG.xsd *8620*
2.59.2. BC-AuthorizeCollectRegistration-Req-IO-MSG.xsd *8637*
2.59.3. BC-AuthorizeCollectRegistration-Res-Full-MSG.xsd *8643*
2.59.4. BC-AuthorizeCollectRegistration-Res-PK-MSG.xsd *8661*
2.60. AuthorizeContract **8670**
2.60.1. BC-AuthorizeContract-Req-Full-MSG.xsd *8670*
2.60.2. BC-AuthorizeContract-Req-IO-MSG.xsd *8898*
2.60.3. BC-AuthorizeContract-Res-Full-MSG.xsd *8904*
2.60.4. BC-AuthorizeContract-Res-PK-MSG.xsd *9133*
2.61. AuthorizeDocArrival **9142**
2.61.1. BC-AuthorizeDocArrival-Req-Full-MSG.xsd *9142*
2.61.2. BC-AuthorizeDocArrival-Req-IO-MSG.xsd *9162*
2.61.3. BC-AuthorizeDocArrival-Res-Full-MSG.xsd *9168*
2.61.4. BC-AuthorizeDocArrival-Res-PK-MSG.xsd *9189*
2.62. AuthorizeProduct **9198**
2.62.1. BC-AuthorizeProduct-Req-Full-MSG.xsd *9198*
2.62.2. BC-AuthorizeProduct-Req-IO-MSG.xsd *9284*
2.62.3. BC-AuthorizeProduct-Res-Full-MSG.xsd *9290*

2.62.4. BC-AuthorizeProduct-Res-PK-MSG.xsd *9378*
2.63. CloseAmendConfirm **9386**
2.63.1. BC-CloseAmendConfirm-Req-Full-MSG.xsd *9386*
2.63.2. BC-CloseAmendConfirm-Req-IO-MSG.xsd *9470*
2.63.3. BC-CloseAmendConfirm-Res-Full-MSG.xsd *9479*
2.63.4. BC-CloseAmendConfirm-Res-PK-MSG.xsd *9565*
2.64. CloseContract **9576**
2.64.1. BC-CloseContract-Req-Full-MSG.xsd *9576*
2.64.2. BC-CloseContract-Req-IO-MSG.xsd *9804*
2.64.3. BC-CloseContract-Res-Full-MSG.xsd *9821*
2.64.4. BC-CloseContract-Res-PK-MSG.xsd *10050*
2.65. CloseDocArrival **10069**
2.65.1. BC-CloseDocArrival-Req-Full-MSG.xsd *10069*
2.65.2. BC-CloseDocArrival-Req-IO-MSG.xsd *10089*
2.65.3. BC-CloseDocArrival-Res-Full-MSG.xsd *10096*
2.65.4. BC-CloseDocArrival-Res-PK-MSG.xsd *10117*
2.66. CreateAmendConfirm **10126**
2.66.1. BC-CreateAmendConfirm-Req-Full-MSG.xsd *10126*
2.66.2. BC-CreateAmendConfirm-Req-IO-MSG.xsd *10210*
2.66.3. BC-CreateAmendConfirm-Res-Full-MSG.xsd *10271*
2.66.4. BC-CreateAmendConfirm-Res-PK-MSG.xsd *10357*
2.67. CreateBCDisc **10420**
2.67.1. BC-CreateBCDisc-Req-Full-MSG.xsd *10420*
2.67.2. BC-CreateBCDisc-Req-IO-MSG.xsd *10430*
2.67.3. BC-CreateBCDisc-Res-Full-MSG.xsd *10440*
2.67.4. BC-CreateBCDisc-Res-PK-MSG.xsd *10456*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSBCService of BC-Module

2.FCUBSBCService

Bills and Collections ServiceBills and Collections Service

2.1.QueryPayment

Query of Bills and Collections Payment

2.1.1.BC-Payment-Query-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *FCCREF*
    - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract interest payment query

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections Contract Payment Query Input Only type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	

Restrictions	Description
maxLength	16

TOP

XREF

Attribute	Description

Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.1.2.BC-Payment-Query-Res-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*

- *AMTDUE*
- *COMPCCY*
- *PREPAYINT*

STTLMENT

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest has been paid

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections Contract Payment Query details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	Description	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description	
Name	INT_REIM_INST1	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST2

Attribute	Description	
Name	INT_REIM_INST2	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	Description	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

2.2.NewPayment

Input of Bills and Collections Payment

2.2.1.BC-Payment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*

FCCREF
ESN
COMP
AMTDUE
COMPCCY
PREPAYINT

STTLMENT

ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract that has been paid interest

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections Payment Request Full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

2.2.2.BC-Payment-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*

- *AMTDUE*
- *COMPCCY*
- *PREPAYINT*

STTLMENT

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract that has been paid interest

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections Contract Payment Request Input Only type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

AMTDUE

Attribute	**Description**	
Name	AMTDUE	
Datatype	Number	
Description	Indicates Amount Due	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

COMPCCY

Attribute	**Description**	
Name	COMPCCY	
Datatype	String	
Description	Indicates Currency	
Restrictions	**Restrictions**	**Description**
	pattern	[A-Z]{3}

TOP

PREPAYINT

Attribute	**Description**	
Name	PREPAYINT	
Datatype	Number	
Description	Indicates Amount Prepaid	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

STTLMENT

Attribute	**Description**
Name	STTLMENT
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	**Description**	
Name	ACC_INST3	
Datatype	String	
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST4

Attribute	**Description**
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	Description	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	Description	
Name	ORDER_INST5	
Datatype	String	
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST6

Attribute	Description	
Name	ORDER_INST6	
Datatype	String	
Description	Country to which the ordering institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

2.2.3.BC-Payment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*

AMTDUE
COMPCCY
PREPAYINT
STTLMENT
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest has been paid

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections Payment Response Full type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BDUEAMT

Attribute	**Description**	
Name	BDUEAMT	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFNO

Attribute	**Description**	
Name	REFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MIS

Attribute	**Description**	
Name	MIS	
Datatype	Date	
Description	Indicates MIS Class	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDT

Attribute	**Description**	
Name	TXNDT	
Datatype	String	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

OLDMIS

Attribute	**Description**	
Name	OLDMIS	
Datatype	String	
Description	Indicates Old MIS	
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.BC-Payment-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *FCCREF*
      - *XREF*
    - *Contract-Details-IO*
      - *FCCREF*
      - *XREF*
      - *ESN*
      - *SUBSYSTEMSTAT*
      - *BDUEAMT*
      - *CONTCCY*
      - *CUSTNAME*
      - *Contract-Liq-Summary*
        - *FCCREF*
        - *CESN*
        - *TESN*
        - *VALDATE*
        - *TOTPAID*
        - *PMTREMARKS*

- *Contract-Liq*
  - *FCCREF*
  - *ESN*
  - *COMP*
  - *AMTDUE*
  - *COMPCCY*
  - *PREPAYINT*

STTLMENT

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*

INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1

ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest has been paid

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	Includes Bills and Collections Contract Payment Request Primary Key type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections Contract Payment Request Input Only type details

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME

Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description	
Name	INT_REIM_INST1	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST2

Attribute	Description	
Name	INT_REIM_INST2	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.ReversePayment

Reversal of Bills and Collections Payment

2.3.1.BC-Payment-Rev-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*

FCCREF
ESN
COMP
AMTDUE
COMPCCY
PREPAYINT

STTLMENT

ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest paid is reversed

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections Contract Payment details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

2.3.2.BC-Payment-Rev-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Details-IO*
  - *FCCREF*
  - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest paid is reversed

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections Contract Payment Input Only type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.3.3.BC-Payment-Rev-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*

AMTDUE
COMPCCY
PREPAYINT
STTLMENT
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest paid is reversed

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections Contract Payment details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BDUEAMT

Attribute	Description	
Name	BDUEAMT	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	Description	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.4.BC-Payment-Rev-Res-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *FCCREF*
      - *XREF*
    - *Contract-Details-IO*
      - *FCCREF*
      - *XREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest paid is reversed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	Includes Bills and Collections Contract Payment Primary Key type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections Contract Payment Input Only type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.QueryAmendConfirm

Query of BC Amendment Confirmation

2.4.1.BC-QueryAmendConfirm-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Amendmaster-IO*
  - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.4.2.BC-QueryAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-IO*
      - *CONREFNO*
    - *Amendmaster-Full*
      - *CONREFNO*
      - *BILLDUEAMT*
      - *BILLAMT*
      - *CUSTID*
      - *BILLCCY*
      - *CR_VALUE_DATE*
      - *DRVALDT*
      - *VALDT*
      - *MATDT*
      - *BCREFNO*
      - *CONTREFNO*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BILLCCY

Attribute	Description	
Name	BILLCCY	
Datatype	String	
Description	Indicates Bill Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CR_VALUE_DATE

Attribute	Description	
Name	CR_VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRVALDT

Attribute	Description	
Name	DRVALDT	
Datatype	Date	
Description	Indicates Debit Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MATDT

Attribute	**Description**	
Name	MATDT	
Datatype	Date	
Description	Indicates Maturity Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCREFNO

Attribute	**Description**	
Name	BCREFNO	
Datatype	String	
Description	Indicates BC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Letters Of Credit Contract reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	User id of the user who saved the contract	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	**Description**	
Name	Amendadv	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTY

Attribute	**Description**	
Name	PRTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACQRCCY

Attribute	**Description**	
Name	ACQRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTYP

Attribute	**Description**	
Name	RTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENATYTYP

Attribute	**Description**	
Name	PENATYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWNINMASTER

Attribute	**Description**	
Name	SHOWNINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARG

Attribute	**Description**	
Name	CUSTMARG	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLG

Attribute	**Description**	
Name	BULKAMTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,D,M,Y</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Intrest-View

Attribute	Description	
Name	Intrest-View	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	Description

Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,Y,D</td></tr></table>

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.QueryBCGoods

Query of Bills and Collections Commodity Code

2.5.1.BC-QueryBCGoods-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-IO*
    - *GOODSCODE*
    - *LANGUAGECODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections Commodity Codes Query Request Input Only type details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE

Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.5.2.BC-QueryBCGoods-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Codes Query Master Response Full type details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.QueryBCPayment

Query of BC Payment

2.6.1.BC-QueryBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.6.2.BC-QueryBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-IO*
      - *CONREFNO*
    - *Payment-Details-Full*
      - *CONREFNO*
      - *VALDT*
      - *CONTCCY*
      - *REKYTTLPAID*
      - *PAYMENT_REMARKS*
      - *BILLDUEAMT*
      - *CNAME*
      - *TOTPAYMNT*
      - *CURRPAYMNT*
      - *TOTAMTDUE*
      - *Auth-Details*
        - *MAKER*
        - *MAKERSTAMP*
        - *CHECKER*
        - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMENT_REMARKS

Attribute	**Description**	
Name	PAYMENT_REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BILLDUEAMT

Attribute	**Description**	
Name	BILLDUEAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CNAME

Attribute	**Description**	
Name	CNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TOTPAYMNT

Attribute	**Description**	
Name	TOTPAYMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRPAYMNT

Attribute	**Description**
Name	CURRPAYMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Payment-Breakup

Attribute	**Description**	
Name	Payment-Breakup	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT_DUE

Attribute	**Description**	
Name	AMT_DUE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT_PREPAID

Attribute	**Description**	
Name	AMOUNT_PREPAID	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**

Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	**Description**	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	**Description**	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.QueryBrnPrm

Query of Bills and Collections Branch Parameters

2.7.1.BC-QueryBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bcbranch-Parameters-IO*
    - *BRANCH*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bcbranch-Parameters-IO

Attribute	Description
Name	Bcbranch-Parameters-IO
Datatype	
Description	Includes the Bills and Collections Branch Parameters IO details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

2.7.2.BC-QueryBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bcbranch-Parameters-IO*
      - *BRANCH*
    - *Bcbranch-Parameters-Full*
      - *BRANCH*
      - *PRCSSTILLNWDFLG*
      - *USEUSERREFINMSGS*
      - *USEULTIPARENTREF*
      - *BTN_UDF*
      - *BRNNAME*
      - *ACQRLVL*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *ONCEAUTH*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bcbranch-Parameters-IO

Attribute	Description
Name	Bcbranch-Parameters-IO
Datatype	
Description	Includes the Bills and Collections branch parameters IO details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

Bcbranch-Parameters-Full

Attribute	Description
Name	Bcbranch-Parameters-Full
Datatype	
Description	Includes the Bills and Collections branch parameters Full details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

PRCSSTILLNWDFLG

Attribute	Description
Name	PRCSSTILLNWDFLG
Datatype	String
Description	Indicates the Process Till Next Working Day. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USEUSERREFINMSGS

Attribute	Description
Name	USEUSERREFINMSGS
Datatype	String
Description	Indicates the Use User Reference No In Messages. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USEULTIPARENTREF

Attribute	Description
Name	USEULTIPARENTREF
Datatype	String
Description	Indicates the User Ultimate Parent User Refernce For Child Contracts. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates the User Defined Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String

Description	Indicates the Branch Name.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQRLVL

Attribute	Description
Name	ACQRLVL
Datatype	String
Description	Indicates the Accrual Level. P - Product, C - Contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	Indicates the Checker date stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction status. O-Open, C-Closed.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation status. A- Authorised, U - Unauthorised.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Once Auth or not.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 150 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.QueryCollectRegistration

Query of Collection Registration

2.8.1.BC-QueryCollectRegistration-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Details-IO*
  - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.8.2.BC-QueryCollectRegistration-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNO*
    - *Contract-Details-Full*
      - *CONREFNO*
      - *PRDCD*
      - *OPERATION*
      - *USEREFNO*
      - *COLLREF*
      - *THEIRLCREF*
      - *CUSTID*
      - *CUSTPRTYTYPE*
      - *ORGDOCRECV*
      - *DUPDOCRECV*
      - *COVLETDATE*
      - *STAGE*
      - *BILLCCY*
      - *BILLAMT*
      - *TXNDATE*

TENOR
VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
BCREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	**Description**	
Name	USEREFNO	
Datatype	String	
Description	Indicates the User Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLREF

Attribute	**Description**	
Name	COLLREF	
Datatype	String	
Description	Indicates Collection Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIRLCREF

Attribute	**Description**	
Name	THEIRLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTPRTYTYPE

Attribute	Description	
Name	CUSTPRTYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ORGDOCRECV

Attribute	Description	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	Description	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	Description	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	**Description**	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.QueryContract

Query of BC Contract

2.9.1.BC-QueryContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.9.2.BC-QueryContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *EXTREFNO*
      - *USEREFNO*
    - *Contract-Details-Full*
      - *CONREFNO*
      - *EXTREFNO*
      - *USEREFNO*
      - *PRODCD*
      - *CHAR*
      - *CURRENCY*
      - *PRDDESC*
      - *OPERATION*
      - *STAG*
      - *LCISSUEDATE*
      - *LC_CUST*
      - *LCREFNO*
      - *THEIR_LCREF*

COLLREF
THECHGCCY
THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT

PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT

AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*

- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*

- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*

- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref

- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*
- *EVNTCOD*
- *STLAMT*

Pack-Credit-Dtls

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*
- *EVNTCOD*

Deferred-Chg-Comp-Details

- *LCREFNO*
- *COMPONENT*
- *AMT_TRANSFERRED*
- *COMP_CCY*
- *AMT_PAID*

Bctbs-Int-Chg-Calc

- *CONTREFNOA*
- *COMPONENTA*
- *STDTA*
- *COMPCCYA*
- *INTRATEA*
- *INTBASISA*
- *WAIVEA*
- *INTAMOUNTA*
- *COMPONENTB*
- *COMPCCYB*
- *INTRATEB*
- *INTBASISB*
- *WAIVEB*
- *INTAMOUNTB*
- *COMPONENTC*
- *COMPCCYC*
- *INTRATEC*
- *INTBASISC*
- *WAIVEC*
- *INTAMOUNTC*
- *CONTREFNOD*
- *COMPONENTD*
- *INTCHGCOMPD*
- *STDTD*

COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT

- EXCRATE
- DISCOUNTDAMT
- LIQDTNAMT
- LIQDTDAMT
- FRMCALCDATE
- TOCALCDATE
- USRDFNDSTS
- STSAFDATE
- UNDERPROTEST
- PROTESTDATE

Taxes

- Tax
  - CONREFNO
  - SCHEME
  - WAIVER
  - Tax-Details
    - RULE
    - BASISAMNTAG
    - COMPUEVNT
    - WAIVER
    - Rule-Details
      - VALUEDT
      - COMPUTATIONDT
      - CCY
      - AMT
      - ESN

TXNUDFDETAILS

- FLDNAME
- FLDVAL

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT

- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*

POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN

- *TRANMIS1*
- *TRANMIS2*
- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Adice

- ADV_CODE
- SUPRESS
- PRIORITY
- PRTY
- MEDIUM
- PRTYID
- PRTYNAME
- Fft
  - FFT_CODE
  - FFTTXT
- Ins
  - INSCD
  - INSTXT

Split-Master

- CONREFNO
- Split-Master
  - BASISAMTTAG
  - BASISAMTCCY
  - BASISAMT
  - Split-Detail
    - SPTSEQNO
    - SPTAMTTAG
    - SPTAMT
    - SPTACBRN
    - SPTACCCY
    - SPRACNO
    - SPTEXCHRT
    - SPTPRTYID
    - SPTPERCENTAGE
    - LOANACC
    - NEGORATE
    - NEGO_REF_NO

Bcpref

- CONREFNO
- LATEVNSEQNO
- BCREFNO

- *ESN*
- *CNTRPARTY*
- *PRD*
- *CCY*
- *TENOR*
- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

CONREFNO

Intrest-Details

- *INTBASIS*
- *RATE*
- *RATECD*
- *SPREAD*
- *STATUS*
- *ACRDAMT*
- *WAIVER*
- *ACRREQRD*
- *ACQRCCY*
- *RTYP*
- *PENATYTYP*
- *SHOWNINMASTER*
- *MAXRT*
- *MINRT*
- *RESTTENOR*
- *BORROWLENDID*
- *RTCALCTYP*
- *CUSTMARG*
- *LEVELNO*
- *BULKAMTFLG*
- *DEPOSITRTCD*
- *NOUNIT*
- *NOUNITS*
- *RATCDUSGE*
- *DISCACCAPP*
- *DENOMITORBASIS*
- *BASIS366*
- *NOINTPRE*
- *MINSPRD*
- *MAXSPRD*
- *MARGIN*
- *COMPONENT*
- *AMT*
- *CHANGEDURAMND*
- *CCY*
- *EVNT*
- *EVNTDESC*
- *COMPDESC*

Intrest-View

- *INTBASIS*
- *RATE*
- *RATECD*

SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE

- *AMOUNT*
  - *Bcfx-Details*
    - *FXREFNO*
    - *TFAMT*
    - *TFRATE*
    - *CCY*
- *Loanacc*
  - *CONREFNO*
  - *Loanaccdet*
    - *ACCNO*
    - *AMTFIN*
    - *CCY*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*
    - *GOODSCD*
    - *QTYUTIL*
    - *AMTUTIL*
    - *QTYREIN*
    - *AMTREIN*
    - *REMARKS*

UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description

Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description	
Name	PRODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	Description	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>INI,FIN,REG</td></tr></table>

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description	
Name	LIQAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	Description	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	Description	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOCAL_CURRR

Attribute	Description	
Name	LOCAL_CURRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	Description	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_LIAB_AMOUNT

Attribute	Description
Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,I</td></tr></table>

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PRTYTYP

Attribute	**Description**	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LMTMONFLG

Attribute	**Description**	
Name	LMTMONFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REDISFLG

Attribute	**Description**	
Name	REDISFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATCNFLG

Attribute	**Description**	
Name	STATCNFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHG_REFUSED

Attribute	Description
Name	CHG_REFUSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description
Name	PASS_INT_TO_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATASDT

Attribute	Description
Name	STATASDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOAN_CONTREF

Attribute	Description
Name	LOAN_CONTREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

USRDEFSTATS

Attribute	**Description**	
Name	USRDEFSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SOURCE

Attribute	**Description**	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	**Description**	
Name	CHGCLAIM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDCOLLAT

Attribute	**Description**	
Name	LIQDCOLLAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	Description	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	Description	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	Description	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description	
Name	LINKEDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECMAILCOP

Attribute	**Description**	
Name	SECMAILCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Doc-Clause

Attribute	**Description**	
Name	Doc-Clause	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Pay-Fate

Attribute	**Description**	
Name	Pay-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	**Description**	
Name	ADVFTREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

ADVFTMED

Attribute	**Description**	
Name	ADVFTMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRVADVFTDT

Attribute	**Description**	
Name	PRVADVFTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVTRACDT

Attribute	**Description**	
Name	PREVTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTTRACDT

Attribute	**Description**	
Name	NEXTTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NUMTRSENT

Attribute	**Description**	
Name	NUMTRSENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NONACCPAYMSGDT

Attribute	**Description**	
Name	NONACCPAYMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTFLG

Attribute	**Description**	
Name	PROTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DISCDESC

Attribute	**Description**	
Name	DISCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3500

TOP

DISCRESLFLG

Attribute	**Description**	
Name	DISCRESLFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,N

TOP

DISCRESDT

Attribute	**Description**	
Name	DISCRESDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCRECDT

Attribute	**Description**	
Name	DISCRECDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,I

TOP

FRMCALCDT

Attribute	**Description**	
Name	FRMCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**

Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNOA

Attribute	**Description**	
Name	CONTREFNOA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENTA

Attribute	**Description**	
Name	COMPONENTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STDTA

Attribute	**Description**	
Name	STDTA	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPCCYA

Attribute	**Description**	
Name	COMPCCYA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISA

Attribute	Description
Name	INTBASISA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>3,6,0,1,2,4,5,7,8,9,-1,-2</td></tr></table>

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISE

Attribute	**Description**	
Name	INTBASISE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEE

Attribute	**Description**	
Name	WAIVEE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTE

Attribute	**Description**	
Name	CHGAMTE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSE

Attribute	**Description**	
Name	STATUSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGPERF

Attribute	**Description**	
Name	CHGPERF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	Description
Name	STATUSF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description	
Name	BASDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDATE_CODE

Attribute	Description	
Name	BASEDATE_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

VALUDATE

Attribute	Description	
Name	VALUDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TNOR

Attribute	Description	
Name	TNOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSTDAYS

Attribute	Description	
Name	TRANSTDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDAT

Attribute	Description	
Name	MATDAT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPLITPCT

Attribute	Description	
Name	SPLITPCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLAMNT

Attribute	Description	
Name	BILLAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNTAMT

Attribute	Description	
Name	DISCOUNTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REBATAMT

Attribute	Description	
Name	REBATAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINKEDTOREF

Attribute	**Description**	
Name	LINKEDTOREF	
Datatype	String	
Description	Indicates Linked To Reference Number/Account	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINKAGETYP

Attribute	**Description**	
Name	LINKAGETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,C,P

TOP

Ui-Fields

Attribute	**Description**	
Name	Ui-Fields	
Datatype		
Description	Includes UI Fields details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOUNT

Attribute	**Description**	
Name	ACCOUNT	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	**Description**	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	**Description**
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	**Description**
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	**Description**
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	**Description**
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRTY

Attribute	**Description**	
Name	PRTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MEDIUM

Attribute	**Description**	
Name	MEDIUM	
Datatype	String	
Description	Indicates Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRTYID

Attribute	**Description**	
Name	PRTYID	
Datatype	String	
Description	Indicates Party Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

Fft

Attribute	Description	
Name	Fft	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FFT_CODE

Attribute	Description	
Name	FFT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTXT

Attribute	Description	
Name	FFTTXT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Ins

Attribute	Description

Name	Ins
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCREFNO

Attribute	**Description**	
Name	BCREFNO	
Datatype	String	
Description	Indicates BC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CNTRPARTY

Attribute	**Description**	
Name	CNTRPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

RTCD

Attribute	**Description**	
Name	RTCD	
Datatype	String	
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EXCHRT

Attribute	**Description**	
Name	EXCHRT	
Datatype	Number	
Description	Indicates Exchange Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

MATACC

Attribute	**Description**
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	**Description**	
Name	BRIDGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CYSTALTYP

Attribute	**Description**	
Name	CYSTALTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COLLLIQDAMT

Attribute	**Description**	
Name	COLLLIQDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDLCCHGCOMM

Attribute	**Description**	
Name	LIQDLCCHGCOMM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGEXCHRATE

Attribute	Description
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TFAMT

Attribute	Description	
Name	TFAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TFRATE

Attribute	Description	
Name	TFRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Loanacc

Attribute	Description	
Name	Loanacc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Extsys-Ws-Master

Attribute	Description	
Name	Extsys-Ws-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Extsys-Ws-Details

Attribute	Description	
Name	Extsys-Ws-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EXTWSRESP

Attribute	Description	
Name	EXTWSRESP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

USERREMARKS

Attribute	Description	
Name	USERREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description

Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.QueryDocArrival

Query of BC Document Arrival

2.10.1.BC-QueryDocArrival-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.10.2.BC-QueryDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNO*
    - *Contract-Details-Full*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *BRNCD*
      - *Doc-Details*
        - *DOCODE*
        - *DOCDESC*
        - *DOCSLNO*
        - *FRSTMAILCOP*
        - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,A</td></tr></table>

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description

Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	Description	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description	
Name	PARTIALSHPMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description	
Name	FFT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTXT

Attribute	Description	
Name	FFTTXT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Ins

Attribute	Description	
Name	Ins	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INSCD

Attribute	Description	
Name	INSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.QueryProduct

Query of Bills and Collections Product

2.11.1.BC-QueryProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections-Product Query-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.11.2.BC-QueryProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-IO*
      - *PRDCD*
    - *Product-Details-Full*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *PRDTYPDESC*
      - *OP*
      - *PRDGRPDESC*
      - *PRDTYP*
      - *RC*
      - *ATA*
      - *ATD*
      - *CTP*

DTC
PTC
DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N

BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N

- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*

- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
- Role-To-Head-Mapping
  - CLASCD
  - CLASDESC
  - Mapping-Details
    - ACCTRL
    - ROLDESC
    - ACCTHD
    - GLDESC
- Product-Events
  - CLASCD
  - CLASDESC
  - Event-Details
    - EVNTCD
    - EVENTDESC
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
      - RATE_TYPE_INDICATOR
    - Advices
      - MSGTYP
      - DESC
      - GENTIME
      - SUPRS
      - PRIOR
      - CHGREQD
- Branch-Ccy-Restrictions
  - CCYLST

- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*

AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY

STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections-Product Query-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections-Product Query details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String

Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATA

Attribute	**Description**	
Name	ATA	
Datatype	String	
Description	Indicates Acceptance to Advance is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATD

Attribute	**Description**	
Name	ATD	
Datatype	String	
Description	Indicates whether Acceptance to Discount is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CTP

Attribute	**Description**	
Name	CTP	
Datatype	String	
Description	Indicates whether Collection to Purchase is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTC

Attribute	**Description**	
Name	DTC	
Datatype	String	
Description	Indicates whether Discount to Collection is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF
Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N
Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	Description	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	Description	
Name	REKYVALDATE_N	
Datatype	String	
Description	Indicates whether Value Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVANCEBYLOAN_N

Attribute	**Description**	
Name	ADVANCEBYLOAN_N	
Datatype	String	
Description	Indicates whether Advance by Loan is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRIDGEGL_N

Attribute	**Description**	
Name	BRIDGEGL_N	
Datatype	String	
Description	Indicates Settlement Bridge GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD_N

Attribute	**Description**	
Name	LOANPRD_N	
Datatype	String	
Description	Indicates Loan Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DISCNTMETHOD

Attribute	**Description**
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,T,

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

FREECOLLFLAG_N

Attribute	**Description**	
Name	FREECOLLFLAG_N	
Datatype	String	
Description	Indicates whether the Product is used for Free Collection	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BILLNOTICEDAYS_N

Attribute	**Description**	
Name	BILLNOTICEDAYS_N	
Datatype	Number	
Description	Indicates Billing Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLNOTICEREQDFLAG_N

Attribute	**Description**	
Name	BILLNOTICEREQDFLAG_N	
Datatype	String	
Description	Indicates whether Billing Notice is Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE
Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,R</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK

Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	Indicates Transfer Collateral from LC Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A - Authorized U - Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Their-Details

Attribute	**Description**	
Name	Charge-Their-Details	
Datatype		
Description	Includes Charge their details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description

Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I

Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details

Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details

Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N

Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Scheme

Attribute	**Description**	
Name	Tax-Scheme	
Datatype		
Description	Indicates Tax Scheme details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SCHME

Attribute	**Description**	
Name	SCHME	
Datatype	String	
Description	Specifies the Scheme ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

SCHEMEDESC

Attribute	**Description**	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Indicates Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates the Tax Component of Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String

Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGREQD

Attribute	**Description**	
Name	CHGREQD	
Datatype	String	
Description	Indicates charges required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Branch-Ccy-Restrictions

Attribute	**Description**	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Branch Currency Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	**Description**	
Name	CCYLST	
Datatype	String	
Description	Indicates Currency Restrictions .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String

Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Cust Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Customer Category Desription	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	**Description**	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	**Description**	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	**Description**	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	**Description**	
Name	Ccy-Preferences	
Datatype		
Description	Includes Currency Preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String

Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	Description	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	Description	
Name	BRWLENDIND	
Datatype	String	
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M

TOP

LVLNO

Attribute	Description	
Name	LVLNO	
Datatype	Number	
Description	Indicates Level No.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPMTMETD

Attribute	Description	
Name	PREPMTMETD	
Datatype	String	
Description	Indicates Pre Payment Method Flexcube : F Custom : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP

Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Y

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	Number	
Description	Indicates Grace Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNT

Attribute	**Description**	
Name	EVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates Component	
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences

Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPRD

Attribute	**Description**	
Name	MINSPRD	
Datatype	Number	
Description	Indicates Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPRD

Attribute	**Description**	
Name	MAXSPRD	
Datatype	Number	
Description	Indicates Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	Description	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	Description	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	Description	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.ReverseBCPayment

ReverseBC Payment

2.12.1.BC-ReverseBCPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	Description

Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.12.2.BC-ReverseBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.12.3.BC-ReverseBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*

Payment-Breakup
- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*

SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.12.4.BC-ReverseBCPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.13.ReverseContract

Reversal of BC Contract

2.13.1.BC-ReverseContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

PRD
CCY
TENOR
UNITS
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
BRIDGL
CYSTALTYP
COLLLIQDAMT
LIQDLCCHGCOMM
MATDT
LOANAMT
BILLOS
CONTRACT_CURRENCY
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
ORGEXCHRATE
Bcprefdet
UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Effective-Int-Rate
CONREFNO
Effective-Intrate-Det
EFFECTDT
IRR
Intrest
CONREFNO
Intrest-Details

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	**Description**	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_LIAB_AMOUNT

Attribute	Description
Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHG_REFUSED

Attribute	Description
Name	CHG_REFUSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description
Name	PASS_INT_TO_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATASDT

Attribute	Description
Name	STATASDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOAN_CONTREF

Attribute	Description
Name	LOAN_CONTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TFR_COLL_AMT

Attribute	**Description**	
Name	TFR_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUT_COLL_AMT

Attribute	**Description**	
Name	OUT_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTID

Attribute	**Description**	
Name	PARTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED, CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	**Description**
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	Description	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	Description	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.13.2.BC-ReverseContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.13.3.BC-ReverseContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY
PRD
CCY
TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

- *ACCRUALCCY*
- *RTTYP*
- *PENALTYTYP*
- *SHOWINMASTER*
- *MAXRT*
- *MINRT*
- *RESETTENOR*
- *BORROW_LEND_IND*
- *RATECALCTYP*
- *CUSTMARGIN*
- *LEVELNO*
- *BULKAMTFLAG*
- *DEPOSITASRTCD*
- *UNIT*
- *NOUNITS*
- *RATCD*
- *DISACCRAPP*
- *DENOMINATORBASIS*
- *BASIS366*
- *NOINTPERIOD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *COMPONENT*
- *CONREFNO*
- *VALDT*
- *TRDT*
- *AMT*
- *CHNGDRNGAMD*
- *CCY*
- *EVENT*
- *ESN*
- *PESN*
- *AMTCALC*

Bcfx

- *BILLREFNO*
- *ESN*
- *Uicolumns*
  - *RATE*
  - *AMOUNT*
- *Bcfx-Details*
  - *FXREFNO*
  - *TFAMT*
  - *TFRATE*

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBRK

Attribute	Description
Name	ALLWBRK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BROKPAIDBYUS

Attribute	Description
Name	BROKPAIDBYUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DTOFPROT

Attribute	**Description**	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCMSGDT

Attribute	**Description**	
Name	ACCMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Fate

Attribute	**Description**	
Name	Acc-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTCOD

Attribute	Description
Name	BASEDTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

UDEID

Attribute	**Description**	
Name	UDEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

RTCD

Attribute	**Description**	
Name	RTCD	
Datatype	String	
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

USAGE

Attribute	**Description**	
Name	USAGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTBASIS

Attribute	**Description**
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.4.BC-ReverseContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.14.RolloverContract

Rolloverof BC Contract

2.14.1.BC-RolloverContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

PRD
CCY
TENOR
UNITS
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
BRIDGL
CYSTALTYP
COLLLIQDAMT
LIQDLCCHGCOMM
MATDT
LOANAMT
BILLOS
CONTRACT_CURRENCY
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
ORGEXCHRATE
Bcprefdet
UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Effective-Int-Rate
CONREFNO
Effective-Intrate-Det
EFFECTDT
IRR
Intrest
CONREFNO
Intrest-Details

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	**Description**	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	**Description**	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOCAL_CURRR

Attribute	**Description**	
Name	LOCAL_CURRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_LIAB_AMOUNT

Attribute	**Description**	
Name	LC_LIAB_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description	
Name	MATDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR_DAYS

Attribute	Description	
Name	TENOR_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	Description	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDT

Attribute	Description	
Name	BASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description	
Name	CONTRACT_DERIVED_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR_FIELD1

Attribute	Description	
Name	CHAR_FIELD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CNFRMD

Attribute	Description	
Name	CNFRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

CONF_AMT

Attribute	Description	
Name	CONF_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TFR_COLL_AMT

Attribute	**Description**	
Name	TFR_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUT_COLL_AMT

Attribute	**Description**	
Name	OUT_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DTOFPROT

Attribute	**Description**	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCMSGDT

Attribute	**Description**	
Name	ACCMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Fate

Attribute	**Description**	
Name	Acc-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INTAMOUNTC

Attribute	Description	
Name	INTAMOUNTC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNOD

Attribute	Description	
Name	CONTREFNOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENTD

Attribute	Description	
Name	COMPONENTD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTCHGCOMPD

Attribute	Description	
Name	INTCHGCOMPD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASISAMTTAG

Attribute	**Description**	
Name	BASISAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMTCCY

Attribute	**Description**	
Name	BASISAMTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BASISAMT

Attribute	**Description**	
Name	BASISAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Split-Detail

Attribute	**Description**	
Name	Split-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	**Description**	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

GOODSCD

Attribute	**Description**	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

QTYUTIL

Attribute	**Description**	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTUTIL

Attribute	**Description**	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYREIN

Attribute	**Description**

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.14.2.BC-RolloverContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *Roll-Pref*
      - *ESN*
      - *BASEDT*
      - *BASEDTDESC*
      - *TNRDAYS*
      - *TRNSDAYS*
      - *MATDAYS*
      - *INTLIQDMOD*
      - *FRMCALCDT*
      - *TOCALCDT*
      - *BASEDTCOD*
    - *Taxes*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*

Charges
LATEVNSEQNO
CONREFNO
Collateral-details
CONREFNO
LATEVNSEQNO
Linkages
CONREFNO
LATEVNSEQNO
Misdetails
CONREFNO
Settlements
CONREFNO
LATEVNSEQNO
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Bcpref
CONREFNO
LATEVNSEQNO
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest
CONREFNO
LATEVNSEQNO
Bcfx
BILLREFNO
ESN
Loanacc
CONREFNO
LATEVNSEQNO
Extsys-Ws-Master
KEYID
Brok-Master
CONREFNO
LATEVNSEQNO
Lic-Master
CONREFNO
LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,D

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTCOD

Attribute	Description
Name	BASEDTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Settlements

Attribute	**Description**
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Lic-Master

Attribute	**Description**	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.14.3.BC-RolloverContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY
PRD
CCY
TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

- *ACCRUALCCY*
- *RTTYP*
- *PENALTYTYP*
- *SHOWINMASTER*
- *MAXRT*
- *MINRT*
- *RESETTENOR*
- *BORROW_LEND_IND*
- *RATECALCTYP*
- *CUSTMARGIN*
- *LEVELNO*
- *BULKAMTFLAG*
- *DEPOSITASRTCD*
- *UNIT*
- *NOUNITS*
- *RATCD*
- *DISACCRAPP*
- *DENOMINATORBASIS*
- *BASIS366*
- *NOINTPERIOD*
- *MINSPREAD*
- *MAXSPREAD*
- *MARGIN*
- *COMPONENT*
- *CONREFNO*
- *VALDT*
- *TRDT*
- *AMT*
- *CHNGDRNGAMD*
- *CCY*
- *EVENT*
- *ESN*
- *PESN*
- *AMTCALC*

Bcfx

- *BILLREFNO*
- *ESN*
- *Uicolumns*
  - *RATE*
  - *AMOUNT*
- *Bcfx-Details*
  - *FXREFNO*
  - *TFAMT*
  - *TFRATE*

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	**Description**
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	**Description**
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	**Description**
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	**Description**
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	Description	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	Description	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRREQRD

Attribute	**Description**	
Name	ACRREQRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACQRCCY

Attribute	**Description**	
Name	ACQRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTYP

Attribute	**Description**	
Name	RTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENATYTYP

Attribute	**Description**	
Name	PENATYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TFRATE

Attribute	**Description**	
Name	TFRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Loanacc

Attribute	**Description**	
Name	Loanacc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Loanaccdet

Attribute	**Description**
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.4.BC-RolloverContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *Roll-Pref*
        - *ESN*
        - *BASEDT*
        - *BASEDTDESC*
        - *TNRDAYS*
        - *TRNSDAYS*
        - *MATDAYS*
        - *INTLIQDMOD*
        - *FRMCALCDT*
        - *TOCALCDT*
        - *BASEDTCOD*
      - *Taxes*
        - *CONREFNO*
        - *LATEVNSEQNO*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *LATEVNSEQNO*
- *CONREFNO*

Collateral-details

- *CONREFNO*
- *LATEVNSEQNO*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*

Misdetails

- *CONREFNO*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*

Adice

Split-Master

- *CONREFNO*
- *LATEVNSEQNO*

Bcpref

- *CONREFNO*
- *LATEVNSEQNO*

Effective-Int-Rate

- *CONREFNO*
- *LATEVNSEQNO*

Intrest

- *CONREFNO*
- *LATEVNSEQNO*

Bcfx

- *BILLREFNO*
- *ESN*

Loanacc

- *CONREFNO*
- *LATEVNSEQNO*

Extsys-Ws-Master

- *KEYID*

Brok-Master

- *CONREFNO*
- *LATEVNSEQNO*

Lic-Master

- *CONREFNO*
- *LATEVNSEQNO*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Roll-Pref

Attribute	Description

Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRNSDAYS

Attribute	Description

Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,D

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTCOD

Attribute	Description

Name	BASEDTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.AuthBCAmndBillAmt

Authorization of Bills and Collections Amount Amenment

2.15.1.BCBill-Amt-Amnd-Auth-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Auth-Details-IO*
  - *XREF*
  - *FCCREF*
- *REKEY_DETAILS*
  - *VALDT*
  - *MATDT*
  - *CUSTID*
  - *BLCCY*
  - *BLAMT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the format Primary request which has Input only fields

TOP

Auth-Details-IO

Attribute	Description
Name	Auth-Details-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Authorization-IO details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

REKEY_DETAILS

Attribute	Description
Name	REKEY_DETAILS
Datatype	
Description	Includes Rekey details

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BLCCY

Attribute	Description
Name	BLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BLAMT

Attribute	Description
Name	BLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.15.2.BCBill-Amt-Amnd-Auth-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Auth-Details-PK*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *Auth_Details-IO*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the primary information relating the Contract.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Auth-Details-PK

Attribute	Description
Name	Auth-Details-PK
Datatype	
Description	Includes Bills and Collections-Amount Amendment Authorization-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date

Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

Auth_Details-IO

Attribute	Description
Name	Auth_Details-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Authorization-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.CreateBCAmendBillAmt

Input of Bills and Collections Amount Amendment

2.16.1.BCBill-Amt-Amnd-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd*
    - *FCCREF*
    - *XREF*
    - *CONTRACT_MASTER_AMND*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *CONTRACT_AMND_ADVICE*
      - *FCCREF*

EVESEQNO
MSGTYPE
MEDIUM
PARTYTYPE
PARTYID
PARTYNAME
PRIORITY
SUPRESS
CONTRACT_AMND_INS
BCREFNO
ADVCODE
INSCODE
INS_TEXT
CONTRACT_AMND_FFT
BCREFNO
ADVCODE
FFTCODE
FFT_TEXT
CONTRACT_AMND_EVENT_LOG
FCCREF
MAKERID
EVESEQ
MAKERSTAMP
CHECKERSTAMP
CHECKERID
EVEDT
EVECD
CONTSTAT
AUTHSTAT
EVENTDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the format for primary request for creation of Contract.

TOP

Contract-Master-Amnd

Attribute	Description
Name	Contract-Master-Amnd
Datatype	
Description	Includes Bills and Collections-Amount Amendment Input details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTRACT_MASTER_AMND

Attribute	Description
Name	CONTRACT_MASTER_AMND
Datatype	
Description	Includes Contract Master Amend details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT

Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CONTRACT_AMND_ADVICE

Attribute	Description
Name	CONTRACT_AMND_ADVICE
Datatype	
Description	Includes Contract Amend Amend details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVESEQNO

Attribute	Description
Name	EVESEQNO
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String

Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	Indicates Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 1

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{1}

TOP

CONTRACT_AMND_INS

Attribute	Description
Name	CONTRACT_AMND_INS
Datatype	
Description	Includes Contract Amend Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	**Description**	
Name	ADVCODE	
Datatype	String	
Description	Indicates Advice Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INSCODE

Attribute	**Description**	
Name	INSCODE	
Datatype	String	
Description	Indicates Instructions Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

INS_TEXT

Attribute	**Description**	
Name	INS_TEXT	
Datatype	String	
Description	Indicates Instructions Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

CONTRACT_AMND_FFT

Attribute	**Description**
Name	CONTRACT_AMND_FFT
Datatype	
Description	Includes Contract Amend FFT details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCREFNO

Attribute	**Description**	
Name	BCREFNO	
Datatype	String	
Description	Indicates BC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	**Description**	
Name	ADVCODE	
Datatype	String	
Description	Indicates Advice Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

FFTCODE

Attribute	**Description**	
Name	FFTCODE	
Datatype	String	
Description	Indicates FFT Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

FFT_TEXT

Attribute	**Description**	
Name	FFT_TEXT	
Datatype	String	
Description	Indicates Free Format Text	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

CONTRACT_AMND_EVENT_LOG

Attribute	Description
Name	CONTRACT_AMND_EVENT_LOG
Datatype	
Description	Includes Contract Amend Event Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

EVESEQ

Attribute	Description
Name	EVESEQ
Datatype	Number
Description	Indicates Serial Number
Restrictions	**Restrictions** / **Description** fractionDigits: 0 totalDigits: 4

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates the inputting time of the record

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

EVEDT

Attribute	Description
Name	EVEDT
Datatype	Date
Description	Indicates Event Date

TOP

EVECD

Attribute	Description
Name	EVECD
Datatype	String
Description	Indicates Event Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{4}</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String

Description	Indicates Contract Status. Active : A Hold : H Liquidated : L Closed : S Reversed : V Yet to be Initiated : Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description

TOP

2.16.2.BCBill-Amt-Amnd-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd-IO*
    - *FCCREF*
    - *XREF*
    - *CUSTID*
    - *BILLCCY*
    - *BILLAMT*
    - *BILLDUEAMT*
    - *VALUEDT*
    - *DRVALDT*
    - *CRVALDT*
    - *MATDT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the format for primary request for creation of Contract.

TOP

Contract-Master-Amnd-IO

Attribute	Description
Name	Contract-Master-Amnd-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Input-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

BILLCCY

Attribute	**Description**	
Name	BILLCCY	
Datatype	String	
Description	Indicates Bill Currency	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BILLAMT

Attribute	**Description**	
Name	BILLAMT	
Datatype	Number	
Description	Indicates Bill Amount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

2.16.3.BCBill-Amt-Amnd-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd*
    - *FCCREF*
    - *XREF*
    - *CONTRACT_MASTER_AMND*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *CONTRACT_AMND_ADVICE*
      - *FCCREF*
      - *EVESEQNO*
      - *MSGTYPE*
      - *MEDIUM*

PARTYTYPE
PARTYID
PARTYNAME
PRIORITY
SUPRESS
CONTRACT_AMND_INS
BCREFNO
ADVCODE
INSCODE
INS_TEXT
CONTRACT_AMND_FFT
BCREFNO
ADVCODE
FFTCODE
FFT_TEXT
CONTRACT_AMND_EVENT_LOG
FCCREF
MAKERID
EVESEQ
MAKERSTAMP
CHECKERSTAMP
CHECKERID
EVEDT
EVECD
CONTSTAT
AUTHSTAT
EVENTDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the Contract that has been successfully Created

TOP

Contract-Master-Amnd

Attribute	Description
Name	Contract-Master-Amnd
Datatype	
Description	Includes Bills and Collections-Amount Amendment Input details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTRACT_MASTER_AMND

Attribute	Description
Name	CONTRACT_MASTER_AMND
Datatype	
Description	Includes Contract Master Amend details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CONTRACT_AMND_ADVICE

Attribute	Description
Name	CONTRACT_AMND_ADVICE
Datatype	
Description	Includes Contract Amend Amend details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

EVESEQNO

Attribute	Description
Name	EVESEQNO
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	Indicates Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party ID

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 1

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{1}

TOP

CONTRACT_AMND_INS

Attribute	Description
Name	CONTRACT_AMND_INS
Datatype	

Description	Includes Contract Amend Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INSCODE

Attribute	Description
Name	INSCODE
Datatype	String
Description	Indicates Instructions Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

INS_TEXT

Attribute	Description
Name	INS_TEXT
Datatype	String
Description	Indicates Instructions Text
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

CONTRACT_AMND_FFT

Attribute	Description
Name	CONTRACT_AMND_FFT
Datatype	
Description	Includes Contract Amend FFT details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates FFT Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

FFT_TEXT

Attribute	Description
Name	FFT_TEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

CONTRACT_AMND_EVENT_LOG

Attribute	Description
Name	CONTRACT_AMND_EVENT_LOG
Datatype	
Description	Includes Contract Amend Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

EVESEQ

Attribute	Description

Name	EVESEQ
Datatype	Number
Description	Indicates Serial Number
Restrictions	

Restrictions	Description
fractionDigits	0
totalDigits	4

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates the inputting time of the record

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	

Restrictions	Description
maxLength	12
minLength	1

TOP

EVEDT

Attribute	Description
Name	EVEDT
Datatype	Date
Description	Indicates Event Date

TOP

EVECD

Attribute	Description
Name	EVECD
Datatype	String
Description	Indicates Event Code
Restrictions	

Restrictions	Description
pattern	[A-Z]{4}

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Hold : H Liquidated : L Closed : S Reversed : V Yet to be Initiated : Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.4.BCBill-Amt-Amnd-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Amnd-PK*
      - *XREF*
      - *FCCREF*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
    - *Contract-Master-Amnd-IO*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*

CRVALDT
MATDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This.xsd gives the message format for detailing the primary information relating the Contract that has been successfully Created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Amnd-PK

Attribute	Description
Name	Contract-Master-Amnd-PK
Datatype	
Description	Includes Bills and Collections-Amount Amendment Input-Primary key details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

Contract-Master-Amnd-IO

Attribute	Description
Name	Contract-Master-Amnd-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Input-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.DeleteBCAmendBillAmt

Input of Bills and Collections Amount Amendment

2.17.1.BCBill-Amt-Amnd-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd*
    - *FCCREF*
    - *XREF*
    - *CONTRACT_MASTER_AMND*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *CONTRACT_AMND_ADVICE*
      - *FCCREF*

EVESEQNO
MSGTYPE
MEDIUM
PARTYTYPE
PARTYID
PARTYNAME
PRIORITY
SUPRESS
CONTRACT_AMND_INS
BCREFNO
ADVCODE
INSCODE
INS_TEXT
CONTRACT_AMND_FFT
BCREFNO
ADVCODE
FFTCODE
FFT_TEXT
CONTRACT_AMND_EVENT_LOG
FCCREF
MAKERID
EVESEQ
MAKERSTAMP
CHECKERSTAMP
CHECKERID
EVEDT
EVECD
CONTSTAT
AUTHSTAT
EVENTDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full request information relating the Contract that has to be Deleted

TOP

Contract-Master-Amnd

Attribute	Description
Name	Contract-Master-Amnd
Datatype	
Description	Includes Bills and Collections-Amount Amendment Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTRACT_MASTER_AMND

Attribute	Description
Name	CONTRACT_MASTER_AMND
Datatype	
Description	Includes Contract Master Amend details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT

Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CONTRACT_AMND_ADVICE

Attribute	Description
Name	CONTRACT_AMND_ADVICE
Datatype	
Description	Includes Contract Amend Amend details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVESEQNO

Attribute	Description
Name	EVESEQNO
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String

Description	Indicates Advice Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	Indicates Party Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String

Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 1

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{1}

TOP

CONTRACT_AMND_INS

Attribute	Description
Name	CONTRACT_AMND_INS
Datatype	
Description	Includes Contract Amend Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	**Description**	
Name	ADVCODE	
Datatype	String	
Description	Indicates Advice Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INSCODE

Attribute	**Description**	
Name	INSCODE	
Datatype	String	
Description	Indicates Instructions Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

INS_TEXT

Attribute	**Description**	
Name	INS_TEXT	
Datatype	String	
Description	Indicates Instructions Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

CONTRACT_AMND_FFT

Attribute	**Description**
Name	CONTRACT_AMND_FFT
Datatype	
Description	Includes Contract Amend FFT details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 1

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates FFT Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

FFT_TEXT

Attribute	Description
Name	FFT_TEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

CONTRACT_AMND_EVENT_LOG

Attribute	Description
Name	CONTRACT_AMND_EVENT_LOG
Datatype	
Description	Includes Contract Amend Event Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

EVESEQ

Attribute	Description
Name	EVESEQ
Datatype	Number
Description	Indicates Serial Number
Restrictions	**Restrictions** / **Description** fractionDigits: 0 totalDigits: 4

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates the inputting time of the record

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

EVEDT

Attribute	Description
Name	EVEDT
Datatype	Date
Description	Indicates Event Date

TOP

EVECD

Attribute	Description
Name	EVECD
Datatype	String
Description	Indicates Event Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{4}</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String

Description	Indicates Contract Status. Active : A Hold : H Liquidated : L Closed : S Reversed : V Yet to be Initiated : Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description

TOP

2.17.2.BCBill-Amt-Amnd-Delete-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Master-Amnd-IO*
  - *FCCREF*
  - *XREF*
  - *CUSTID*
  - *BILLCCY*
  - *BILLAMT*
  - *BILLDUEAMT*
  - *VALUEDT*
  - *DRVALDT*
  - *CRVALDT*
  - *MATDT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the format for the primary request for Deletion of the contract.

TOP

Contract-Master-Amnd-IO

Attribute	Description
Name	Contract-Master-Amnd-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Deletion-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

BILLCCY

Attribute	**Description**	
Name	BILLCCY	
Datatype	String	
Description	Indicates Bill Currency	
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BILLAMT

Attribute	**Description**	
Name	BILLAMT	
Datatype	Number	
Description	Indicates Bill Amount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

2.17.3.BCBill-Amt-Amnd-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd*
    - *FCCREF*
    - *XREF*
    - *CONTRACT_MASTER_AMND*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *CONTRACT_AMND_ADVICE*
      - *FCCREF*
      - *EVESEQNO*
      - *MSGTYPE*
      - *MEDIUM*

PARTYTYPE
PARTYID
PARTYNAME
PRIORITY
SUPRESS
CONTRACT_AMND_INS
BCREFNO
ADVCODE
INSCODE
INS_TEXT
CONTRACT_AMND_FFT
BCREFNO
ADVCODE
FFTCODE
FFT_TEXT
CONTRACT_AMND_EVENT_LOG
FCCREF
MAKERID
EVESEQ
MAKERSTAMP
CHECKERSTAMP
CHECKERID
EVEDT
EVECD
CONTSTAT
AUTHSTAT
EVENTDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the Contract that has been successfully Deleted

TOP

Contract-Master-Amnd

Attribute	Description
Name	Contract-Master-Amnd
Datatype	
Description	Includes Bills and Collections-Amount Amendment Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CONTRACT_MASTER_AMND

Attribute	Description
Name	CONTRACT_MASTER_AMND
Datatype	
Description	Includes Contract Master Amend details

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID

Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date

Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CONTRACT_AMND_ADVICE

Attribute	Description
Name	CONTRACT_AMND_ADVICE
Datatype	
Description	Includes Contract Amend Amend details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

EVESEQNO

Attribute	Description
Name	EVESEQNO
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	Indicates Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 1

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{1}

TOP

CONTRACT_AMND_INS

Attribute	Description
Name	CONTRACT_AMND_INS
Datatype	
Description	Includes Contract Amend Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INSCODE

Attribute	Description
Name	INSCODE
Datatype	String
Description	Indicates Instructions Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

INS_TEXT

Attribute	Description
Name	INS_TEXT
Datatype	String
Description	Indicates Instructions Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

CONTRACT_AMND_FFT

Attribute	Description
Name	CONTRACT_AMND_FFT
Datatype	
Description	Includes Contract Amend FFT details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates FFT Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

FFT_TEXT

Attribute	Description
Name	FFT_TEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

CONTRACT_AMND_EVENT_LOG

Attribute	Description
Name	CONTRACT_AMND_EVENT_LOG
Datatype	
Description	Includes Contract Amend Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

EVESEQ

Attribute	Description
Name	EVESEQ
Datatype	Number

Description	Indicates Serial Number
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates the inputting time of the record

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

EVEDT

Attribute	Description
Name	EVEDT
Datatype	Date
Description	Indicates Event Date

TOP

EVECD

Attribute	Description
Name	EVECD
Datatype	String
Description	Indicates Event Code
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{4}

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Hold : H Liquidated : L Closed : S Reversed : V Yet to be Initiated : Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.4.BCBill-Amt-Amnd-Delete-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Master-Amnd-PK*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *Contract-Master-Amnd-IO*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*

VALUEDT
DRVALDT
CRVALDT
MATDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the primary information relating the Contract that has been successfully Deleted

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Master-Amnd-PK

Attribute	Description
Name	Contract-Master-Amnd-PK
Datatype	
Description	Includes Bills and Collections-Amount Amendment Deletion-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID

Datatype	String
Description	Indicates Customer
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date

Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

Contract-Master-Amnd-IO

Attribute	Description
Name	Contract-Master-Amnd-IO
Datatype	
Description	Includes Bills and Collections-Amount Amendment Deletion-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.QueryBCAmendBillAmt

Query of Bills and Collections Amount Amendment

2.18.1.BCBill-Amt-Amnd-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd-IO*
    - *XREF*
    - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the format in which the external system has to send a Query request for BC Contract.This is the normal request which has Input fields only

TOP

Contract-Master-Amnd-IO

Attribute	Description
Name	Contract-Master-Amnd-IO
Datatype	
Description	Includes Bills and Collections Bill Amount Amendment Query Master Input Only type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

2.18.2.BCBill-Amt-Amnd-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Master-Amnd*
    - *FCCREF*
    - *XREF*
    - *CONTRACT_MASTER_AMND*
      - *FCCREF*
      - *XREF*
      - *CUSTID*
      - *BILLCCY*
      - *BILLAMT*
      - *BILLDUEAMT*
      - *VALUEDT*
      - *DRVALDT*
      - *CRVALDT*
      - *MATDT*
    - *CONTRACT_AMND_ADVICE*
      - *FCCREF*
      - *EVESEQNO*
      - *MSGTYPE*
      - *MEDIUM*

PARTYTYPE
PARTYID
PARTYNAME
PRIORITY
SUPRESS
CONTRACT_AMND_INS
BCREFNO
ADVCODE
INSCODE
INS_TEXT
CONTRACT_AMND_FFT
BCREFNO
ADVCODE
FFTCODE
FFT_TEXT
CONTRACT_AMND_EVENT_LOG
FCCREF
MAKERID
EVESEQ
MAKERSTAMP
CHECKERSTAMP
CHECKERID
EVEDT
EVECD
CONTSTAT
AUTHSTAT
EVENTDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for providing Full information of the FX Internal Swap details that are successfully Query in FLEXCUBE UBS

TOP

Contract-Master-Amnd

Attribute	Description
Name	Contract-Master-Amnd
Datatype	
Description	Includes Bills and Collections Bill Amount Amendment Query Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CONTRACT_MASTER_AMND

Attribute	Description
Name	CONTRACT_MASTER_AMND
Datatype	
Description	Includes Contract Master Amend details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date

TOP

CRVALDT

Attribute	Description
Name	CRVALDT
Datatype	Date
Description	Indicates Credit Value Date

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

CONTRACT_AMND_ADVICE

Attribute	Description
Name	CONTRACT_AMND_ADVICE
Datatype	
Description	Includes Contract Amend Amend details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

EVESEQNO

Attribute	Description
Name	EVESEQNO
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 4

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	Indicates Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	1

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description	Indicates Supress Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[A-Z]{1}

TOP

CONTRACT_AMND_INS

Attribute	**Description**
Name	CONTRACT_AMND_INS
Datatype	

Description	Includes Contract Amend Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description
Name	ADVCODE
Datatype	String
Description	Indicates Advice Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INSCODE

Attribute	Description
Name	INSCODE
Datatype	String
Description	Indicates Instructions Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

INS_TEXT

Attribute	Description
Name	INS_TEXT
Datatype	String
Description	Indicates Instructions Text
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

CONTRACT_AMND_FFT

Attribute	Description	
Name	CONTRACT_AMND_FFT	
Datatype		
Description	Includes Contract Amend FFT details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCREFNO

Attribute	Description	
Name	BCREFNO	
Datatype	String	
Description	Indicates BC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ADVCODE

Attribute	Description	
Name	ADVCODE	
Datatype	String	
Description	Indicates Advice Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

FFTCODE

Attribute	Description	
Name	FFTCODE	
Datatype	String	
Description	Indicates FFT Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

FFT_TEXT

Attribute	Description
Name	FFT_TEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

CONTRACT_AMND_EVENT_LOG

Attribute	Description
Name	CONTRACT_AMND_EVENT_LOG
Datatype	
Description	Includes Contract Amend Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

EVESEQ

Attribute	Description

Name	EVESEQ
Datatype	Number
Description	Indicates Serial Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>0</td></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	Indicates the inputting time of the record

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

EVEDT

Attribute	Description
Name	EVEDT
Datatype	Date
Description	Indicates Event Date

TOP

EVECD

Attribute	Description
Name	EVECD
Datatype	String
Description	Indicates Event Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{4}</td></tr></table>

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Hold : H Liquidated : L Closed : S Reversed : V Yet to be Initiated : Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.DeleteProduct

Deletion of Bills and Collections Product

2.19.1.BC-DeleteProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*

DTC
PTC
DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N

BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N

- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*

- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*
  - *AMNTTAG*
  - *BASISAMNTTAG*
  - *COMPTATIONEVNT*
  - *TYP*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Product-Events*
  - *CLASCD*
  - *CLASDESC*
  - *Event-Details*
    - *EVNTCD*
    - *EVENTDESC*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*
      - *REVALRTCD*
      - *REVALTXNCD*
      - *HOLTREAT*
      - *REVALREQD*
      - *RATE_TYPE_INDICATOR*
    - *Advices*
      - *MSGTYP*
      - *DESC*
      - *GENTIME*
      - *SUPRS*
      - *PRIOR*
      - *CHGREQD*
- *Branch-Ccy-Restrictions*
  - *CCYLST*

- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*

AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY

STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Deletion details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT

Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP

Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TC

Attribute	**Description**	
Name	TC	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,U

TOP

ATF

Attribute	**Description**	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	**Description**	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	**Description**	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N

Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N

Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	**Description**	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description

Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description

Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRANSITDAYS_N

Attribute	**Description**	
Name	TRANSITDAYS_N	
Datatype	Number	
Description	Indicates Transit Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INCOTERM_N

Attribute	**Description**	
Name	INCOTERM_N	
Datatype	String	
Description	Indicates INCO Term	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

LTL

Attribute	**Description**	
Name	LTL	
Datatype	String	
Description	Indicates whether Export Bill should be Linked to a Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPCOLTYPE

Attribute	**Description**	
Name	ACPCOLTYPE	
Datatype	String	
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	Indicates Transfer Collateral from LC Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description

Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String

Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String

Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	

Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description	
Name	UPWARDTRANSFERTOGL_N	
Datatype	String	
Description	Indicates Upward Transfer To GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description	
Name	UPWARDTRANSFERTOGLDESC_N	
Datatype	String	
Description	Indicates Upward Transfer To GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description	
Name	DWNWRDTRANSFERFRMGL_N	
Datatype	String	
Description	Indicates Downward Transfer From GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description	
Name	DWNWRDTRANSFERFRMGLDESC_N	
Datatype	String	
Description	Indicates Downward Transfer From GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Indicates Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AMNTTAG

Attribute	**Description**	
Name	AMNTTAG	
Datatype	String	
Description	Indicates the Tax Component of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description

Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description

Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Cust Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Customer Category Desription	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String

Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	Description	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences

Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	Description	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	Description	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	Description	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	Description	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.19.2.BC-DeleteProduct-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Product-Details-IO
PRDCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Deletion-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.19.3.BC-DeleteProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *DOC*

ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N

TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N
  ACCEXCTRACERFLAG_I
  ACCEXCNUMTRACERS_N
  PAYEXTARCERFLAG_T

- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*

- AMNTTAG
- BASISAMNTTAG
- COMPTATIONEVNT
- TYP

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Branch-Ccy-Restrictions

- CCYLST
- BRNLST
- CLASCD
- CLASDESC

- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND

LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Deletion details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indciates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OP

Attribute	**Description**	
Name	OP	
Datatype	String	
Description	Indicates Operation Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF
Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REKEYREQFLAG_N

Attribute	**Description**	
Name	REKEYREQFLAG_N	
Datatype	String	
Description	Indicates whether Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYAMNTFLAG_N

Attribute	**Description**	
Name	REKEYAMNTFLAG_N	
Datatype	String	
Description	Indicates Amount Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	**Description**	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	**Description**	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description
Name	REKYMATURTYDATE_N
Datatype	String
Description	Indicates whether Maturity Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N

Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD_N

Attribute	Description	
Name	LOANPRD_N	
Datatype	String	
Description	Indicates Loan Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DISCNTMETHOD

Attribute	Description	
Name	DISCNTMETHOD	
Datatype	String	
Description	Indicates Discounting Method Discounted : D True Discounted : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,T,

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

FREECOLLFLAG_N

Attribute	Description	
Name	FREECOLLFLAG_N	
Datatype	String	
Description	Indicates whether the Product is used for Free Collection	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE

Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	**Description**	
Name	TRANSFERCOLLATFROMLC	
Datatype	String	
Description	Indicates Transfer Collateral from LC Flag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description

Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM

Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description

Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String

Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates the Tax Component of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	**Description**	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates the Event of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	**Description**	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Role To Head Mapping	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String

Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Cust Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	**Description**	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String

Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description

Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String

Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	**Description**	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	**Description**	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.4.BC-DeleteProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Includes Bills and Collections- Product Deletion-Primary key details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Deletion-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.ExecuteQueryDocs

Query of Bills and Collections Document Code

2.20.1.BC-ExecuteQueryDocs-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-IO*
    - *DOCCODE*
    - *LANGCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE

Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.20.2.BC-ExecuteQueryDocs-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-Full*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *DOCTYPE*
      - *VALIDATESHIPGUA*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

Docs-Clauses
CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	**Description**	
Name	VALIDATESHIPGUA	
Datatype	String	
Description	Indicates the Validate Ship Guarantee.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String

Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.ExecuteQueryFfts

Query of Bills and Collections Free Format Code

2.21.1.BC-ExecuteQueryFfts-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-IO*
    - *FFTCODE*
    - *LANGCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Query-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE

Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.21.2.BC-ExecuteQueryFfts-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-Full*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Query-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Query details

TOP

FFTCODE

Attribute	Description	
Name	FFTCODE	
Datatype	String	
Description	Indicates Text Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FREEFORMATTEXT

Attribute	Description	
Name	FREEFORMATTEXT	
Datatype	String	
Description	Indicates Free Format Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User Identification who inputted the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.LiquidateContract

Liquidate BC Contract

2.22.1.BC-LiquidateContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

- *PRD*
- *CCY*
- *TENOR*
- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- *FXREFNO*
- *TFAMT*
- *TFRATE*
- *CCY*

Loanacc

- *CONREFNO*
- *Loanaccdet*
  - *ACCNO*
  - *AMTFIN*
  - *CCY*

Extsys-Ws-Master

- *Extsys-Ws-Details*
  - *EXTWSRESP*
  - *USERREMARKS*

Brok-Master

- *CONREFNO*
- *CONTRACTCCY*
- *BROKPERCENT*
- *BROKAMT*
- *Brok-Detail*
  - *BROKNAME*
  - *BROKER*
  - *BRKACC*
  - *BRKACCCCY*
  - *BRKPERCENT*
  - *BRKAMTACCCCY*
  - *EXRATE*
  - *ORGEXRATE*
  - *NEGRATE*
  - *NEGREFNO*
  - *REMARKS*
  - *BRKAMTCONCCY*
  - *LIQSTATUS*

Lic-Master

- *License-Utils-Detail*
  - *IMPLICNO*
  - *GOODSCD*
  - *QTYUTIL*
  - *AMTUTIL*
  - *QTYREIN*
  - *AMTREIN*
  - *REMARKS*
  - *UNIT_OF_MEASUREMENT*
  - *LICENSE_AMOUNT*

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_LIAB_AMOUNT

Attribute	Description
Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TFR_COLL_AMT

Attribute	**Description**	
Name	TFR_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUT_COLL_AMT

Attribute	**Description**	
Name	OUT_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTID

Attribute	**Description**	
Name	PARTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDT

Attribute	Description	
Name	SHIPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ARRVDT

Attribute	Description	
Name	ARRVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	Description	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Pay-Excep

Attribute	Description	
Name	Pay-Excep	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DTOFPROT

Attribute	**Description**	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCMSGDT

Attribute	**Description**	
Name	ACCMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Fate

Attribute	**Description**	
Name	Acc-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	**Description**
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	**Description**
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	**Description**
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENOMITORBASIS

Attribute	Description	
Name	DENOMITORBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPRE

Attribute	Description	
Name	NOINTPRE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPRD

Attribute	Description	
Name	MINSPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.22.2.BC-LiquidateContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *OUTSTAMT*
    - *VDATECR*
    - *DRVALDT*
    - *INTLIQDMOD*
    - *OURCHGREF*
    - *CHG_REFUSED*
    - *CHKNUM*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *SUBSYSSTAT*
    - *LIQDCOLLAT*
    - *SETTLEAMT*
    - *ALLWBRK*
    - *OUT_COLL_AMT*

Pay-Excep

MANGENFLG

Pay-Fate

MANGENFLG

Acc-Excep

MANGENFLG

Pack-Credit

BCREFNO

CLACCNO

SEQNO

LNKCCY

OUTSTAMT

EVNTCOD

STLAMT

Pack-Credit-Dtls

BCREFNO

CLACCNO

SEQNO

LNKCCY

OUTSTAMT

EVNTCOD

Deferred-Chg-Comp-Details

AMT_PAID

STATUS

Bctbs-Int-Chg-Calc

COMPCCYA

INTBASISA

WAIVEA

COMPCCYB

INTBASISB

WAIVEB

COMPCCYC

INTBASISC

WAIVEC

COMPCCYD

INTBASISD

WAIVEDD

COMPCCYE

INTBASISE

WAIVEE

COMPCCYF

INTBASISF

WAIVEF

Contract-Multitnr

LIQDTNAMT
LIQDTDAMT
Taxes
CONREFNO
LATEVNSEQNO
TXNUDFDETAILS
FLDNAME
FLDVAL
Charges
LATEVNSEQNO
CONREFNO
Collateral-details
CONREFNO
LATEVNSEQNO
Linkages
CONREFNO
LATEVNSEQNO
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Settlements
CONREFNO
LATEVNSEQNO
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Bcpref
CONREFNO
LATEVNSEQNO
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest
CONREFNO
LATEVNSEQNO
Bcfx

BILLREFNO
ESN
Loanacc
CONREFNO
LATEVNSEQNO
Extsys-Ws-Master
KEYID
Brok-Master
CONREFNO
LATEVNSEQNO
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
AMTQ_UT
AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,I

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHG_REFUSED

Attribute	Description
Name	CHG_REFUSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>200</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWBRK

Attribute	Description
Name	ALLWBRK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLACCNO

Attribute	**Description**	
Name	CLACCNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SEQNO

Attribute	**Description**	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNKCCY

Attribute	**Description**	
Name	LNKCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SEQNO

Attribute	**Description**	
Name	SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LNKCCY

Attribute	**Description**	
Name	LNKCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTBASISA

Attribute	Description	
Name	INTBASISA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description	
Name	WAIVEA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

COMPCCYB

Attribute	Description	
Name	COMPCCYB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTBASISB

Attribute	Description	
Name	INTBASISB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTBASISF

Attribute	Description
Name	INTBASISF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEF

Attribute	Description
Name	WAIVEF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

Contract-Multitnr

Attribute	**Description**	
Name	Contract-Multitnr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LIQDTNAMT

Attribute	**Description**	
Name	LIQDTNAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDTDAMT

Attribute	**Description**	
Name	LIQDTDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Taxes

Attribute	**Description**	
Name	Taxes	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String

Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	

Attribute	Description
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO

Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>200</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.22.3.BC-LiquidateContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- TOCALCDATE
- USRDFNDSTS
- STSAFDATE
- UNDERPROTEST
- PROTESTDATE

Taxes

- Tax
  - CONREFNO
  - SCHEME
  - WAIVER
  - Tax-Details
    - RULE
    - BASISAMNTAG
    - COMPUEVNT
    - WAIVER
    - Rule-Details
      - VALUEDT
      - COMPUTATIONDT
      - CCY
      - AMT
      - ESN

TXNUDFDETAILS

- FLDNAME
- FLDVAL

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- TRANMIS6
- TRANMIS7
- TRANMIS8
- TRANMIS9
- TRANMIS10
- COMMIS1
- COMMIS2
- COMMIS3
- COMMIS4
- COMMIS5
- COMMIS6
- COMMIS7
- COMMIS8
- COMMIS9
- COMMIS10
- FUNMIS1
- FUNMIS2
- FUNMIS3
- FUNMIS4
- FUNMIS5
- FUNMIS6
- FUNMIS7
- FUNMIS8
- FUNMIS9
- FUNMIS10
- Txnmisdetails
- Compmisdetails
- Fundmisdetails

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY
  - ERIAMT
  - GENMSG

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY
PRD
CCY
TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description	
Name	THEIR_LCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COLLREF

Attribute	Description	
Name	COLLREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THECHGCCY

Attribute	Description	
Name	THECHGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

THECHGAMT

Attribute	Description	
Name	THECHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBRK

Attribute	Description
Name	ALLWBRK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BROKPAIDBYUS

Attribute	Description
Name	BROKPAIDBYUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

JVPARENT

Attribute	**Description**	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	**Description**	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	**Description**	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	**Description**	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	Description	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	Description	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.4.BC-LiquidateContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *THECHGCCY*
      - *THECHGAMT*
      - *LIQAMT*
      - *OUTSTAMT*
      - *VDATECR*
      - *DRVALDT*
      - *INTLIQDMOD*
      - *OURCHGREF*
      - *CHG_REFUSED*
      - *CHKNUM*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *SUBSYSSTAT*
      - *LIQDCOLLAT*

SETTLEAMT
ALLWBRK
OUT_COLL_AMT
Pay-Excep
  MANGENFLG
Pay-Fate
  MANGENFLG
Acc-Excep
  MANGENFLG
Pack-Credit
  BCREFNO
  CLACCNO
  SEQNO
  LNKCCY
  OUTSTAMT
  EVNTCOD
  STLAMT
Pack-Credit-Dtls
  BCREFNO
  CLACCNO
  SEQNO
  LNKCCY
  OUTSTAMT
  EVNTCOD
Deferred-Chg-Comp-Details
  AMT_PAID
  STATUS
Bctbs-Int-Chg-Calc
  COMPCCYA
  INTBASISA
  WAIVEA
  COMPCCYB
  INTBASISB
  WAIVEB
  COMPCCYC
  INTBASISC
  WAIVEC
  COMPCCYD
  INTBASISD
  WAIVEDD
  COMPCCYE
  INTBASISE
  WAIVEE
  COMPCCYF

INTBASISF
WAIVEF
Contract-Multitnr
LIQDTNAMT
LIQDTDAMT
Taxes
CONREFNO
LATEVNSEQNO
TXNUDFDETAILS
FLDNAME
FLDVAL
Charges
LATEVNSEQNO
CONREFNO
Collateral-details
CONREFNO
LATEVNSEQNO
Linkages
CONREFNO
LATEVNSEQNO
Misdetails
CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Settlements
CONREFNO
LATEVNSEQNO
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Bcpref
CONREFNO
LATEVNSEQNO
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest

CONREFNO
LATEVNSEQNO
Bcfx
BILLREFNO
ESN
Loanacc
CONREFNO
LATEVNSEQNO
Extsys-Ws-Master
KEYID
Brok-Master
CONREFNO
LATEVNSEQNO
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
AMTQ_UT
AMTQ_RE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VDATECR

Attribute	Description	
Name	VDATECR	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRVALDT

Attribute	Description	
Name	DRVALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTLIQDMOD

Attribute	Description	
Name	INTLIQDMOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,I

TOP

OURCHGREF

Attribute	Description	
Name	OURCHGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHKNUM

Attribute	Description	
Name	CHKNUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBRK

Attribute	Description
Name	ALLWBRK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMT_PAID

Attribute	Description

Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTBASISA

Attribute	Description
Name	INTBASISA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>3,6,0,1,2,4,5,7,8,9,-1,-2</td></tr></table>

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

COMPCCYF

Attribute	**Description**	
Name	COMPCCYF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

Contract-Multitnr

Attribute	**Description**	
Name	Contract-Multitnr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LIQDTNAMT

Attribute	Description	
Name	LIQDTNAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDTDAMT

Attribute	Description	
Name	LIQDTDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Taxes

Attribute	Description	
Name	Taxes	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Collateral-details

Attribute	**Description**	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Linkages

Attribute	**Description**
Name	Linkages

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Split-Master

Attribute	Description

Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.ModifyAmendConfirm

Modify BC Amendment Confirmation

2.23.1.BC-ModifyAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT

Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description

Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.23.2.BC-ModifyAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-IO*
    - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *IBANACNO*
        - *CUSTSPREAD*
        - *SPREADDEFN*
        - *COMPNT*
        - *TAGCCY*
        - *ACCBRN*
        - *ACC*
        - *ACCCCY*
        - *EXRATE*
        - *NETIND*
        - *ERICCY*
        - *ERIAMT*
        - *GENMSG*

RATECD

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

- NOOFDEC
- ADDID
- SNDRRCVRINFO1
- SNDRRCVRINFO2
- SNDRRCVRINFO3
- SNDRRCVRINFO4
- SNDRRCVRINFO5
- SNDRRCVRINFO6
- DECLARTION
- REPRES1
- REPRES2
- REPRES3
- REPRES4
- RCVRACC

Intrest
- CONREFNO
- LATEVNSEQNO

Charges
- LATEVNSEQNO
- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Taxes
- CONREFNO
- LATEVNSEQNO

Tax

SCHEME

WAIVER

Tax-Details

BASISAMNTAG

COMPUEVNT

WAIVER

ESN

Rule-Details

COMPUTATIONDT

CCY

AMT

ESN

EFFECTIVEDT

STAT

BASISAMT

BASISAMTCCY

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description

Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2

Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**
	minOccurs / 1
Restrictions	**Restrictions** / **Description**
	maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 25

TOP

CREATESN

Attribute	**Description**

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG

Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date

Description	Indicates Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

2.23.3.BC-ModifyAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*

EVENTDESC

Amendadv

- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD

ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT

MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**

Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	Description	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	Description	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	Description	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTCALC

Attribute	**Description**	
Name	AMTCALC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description	Includes the Charges Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.4.BC-ModifyAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-PK*
      - *CONREFNO*
    - *Amendmaster-IO*
      - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
        - *Contract-Settlement*
          - *IBANACNO*
          - *CUSTSPREAD*
          - *SPREADDEFN*
          - *COMPNT*
          - *TAGCCY*
          - *ACCBRN*
          - *ACC*
          - *ACCCCY*
          - *EXRATE*
          - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
- *CONREFNO*
- *LATEVNSEQNO*

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxes
CONREFNO
LATEVNSEQNO
Tax
SCHEME
WAIVER
Tax-Details
BASISAMNTAG
COMPUEVNT
WAIVER
ESN
Rule-Details
COMPUTATIONDT
CCY
AMT
ESN
EFFECTIVEDT
STAT
BASISAMT
BASISAMTCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-PK

Attribute	Description
Name	Amendmaster-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3

Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT

Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT

Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.ModifyBCDisc

Modification of Bills and Collections Discrepancy Code

2.24.1.BC-ModifyBCDisc-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Disc-Master-Full

Attribute	Description

Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.24.2.BC-ModifyBCDisc-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-IO*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MODNO*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

2.24.3.BC-ModifyBCDisc-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.4.BC-ModifyBCDisc-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-PK*
      - *DISCCODE*
      - *LANGUAGECODE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Disc-Master-Full*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-PK

Attribute	Description
Name	Disc-Master-PK
Datatype	
Description	Includes Discrepancy Master primary key details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes Discrepancy Master IO details.

TOP

DISCCODE

Attribute	**Description**	
Name	DISCCODE	
Datatype	String	
Description	Indicates the Discrepancy Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	**Description**	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DISCDESC

Attribute	**Description**	
Name	DISCDESC	
Datatype	String	
Description	Indicates the Discrepancy description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Disc-Master-Full

Attribute	**Description**
Name	Disc-Master-Full
Datatype	
Description	Includes Discrepancy Master Full details.

TOP

DISCCODE

Attribute	**Description**	
Name	DISCCODE	
Datatype	String	
Description	Indicates the Discrepancy Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DISCDESC

Attribute	Description	
Name	DISCDESC	
Datatype	String	
Description	Indicates the Discrepancy description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.ModifyBCGoods

Modification of Bills and Collections Commodity Code

2.25.1.BC-ModifyBCGoods-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Goods-Master-Full

Attribute	Description

Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Modification details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.25.2.BC-ModifyBCGoods-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-IO*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MODNO*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections Commodity Code Modification-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.25.3.BC-ModifyBCGoods-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Modification details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.4.BC-ModifyBCGoods-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-PK*
      - *GOODSCODE*
      - *LANGUAGECODE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Goods-Master-Full*
      - *GOODSCODE*
      - *LANGUAGECODE*

GOODSDESC
BANNEDCOMMODITY
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-PK

Attribute	Description
Name	Goods-Master-PK
Datatype	
Description	Includes Bills and Collections Commodity Code Modification-Primary key details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String

Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections Commodity Code Modification-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description

Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Modification details

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description	Indicates Goods Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description	Indicates Goods Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

BANNEDCOMMODITY

Attribute	Description	
Name	BANNEDCOMMODITY	
Datatype	String	
Description	Indicates Banned Commodity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	

Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.ModifyBCPayment

Modify BC Payment

2.26.1.BC-ModifyBCPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	Description

Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.26.2.BC-ModifyBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *IBANACNO*
        - *CUSTSPREAD*
        - *SPREADDEFN*
        - *COMPNT*
        - *TAGCCY*
        - *ACCBRN*
        - *ACC*
        - *ACCCCY*
        - *EXRATE*
        - *NETIND*
        - *ERICCY*
        - *ERIAMT*
        - *GENMSG*

RATECD

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*

NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP

MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description

Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	**Description**	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4

Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

2.26.3.BC-ModifyBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*

Payment-Breakup
- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*

SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.26.4.BC-ModifyBCPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
        - *Contract-Settlement*
          - *IBANACNO*
          - *CUSTSPREAD*
          - *SPREADDEFN*
          - *COMPNT*
          - *TAGCCY*
          - *ACCBRN*
          - *ACC*
          - *ACCCCY*
          - *EXRATE*
          - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*

SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7

TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description

Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2

Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	**Description**	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	**Description**	
Name	REFXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.ModifyCollectRegistration

Modify Collection Registration

2.27.1.BC-ModifyCollectRegistration-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*

TENOR
VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
- *PRTYLANG*
- *PRTYCOUNTRY*
- *PRTYREF*
- *PRTYNAME*
- *PRTYADD1*
- *PRTYADD2*
- *PRTYADD3*
- *PRTYADD4*
- *PRTYID*
- *PRTYTYPE*
- *ESN*
- *BCREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	**Description**	
Name	USEREFNO	
Datatype	String	
Description	Indicates the User Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

COLLREF

Attribute	**Description**	
Name	COLLREF	
Datatype	String	
Description	Indicates Collection Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIRLCREF

Attribute	**Description**	
Name	THEIRLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description	Indicates the Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description	Indicates Internal Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BASEDATE

Attribute	**Description**	
Name	BASEDATE	
Datatype	Date	
Description	Indicates Base Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTEDESC

Attribute	**Description**
Name	BASEDTEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description	Indicates the Maturity Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	**Description**	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.27.2.BC-ModifyCollectRegistration-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *COLLREF*
    - *CUSTID*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF

Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.27.3.BC-ModifyCollectRegistration-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*
    - *TENOR*
    - *VALDATE*
    - *INTREMRKS*

BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
BCREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD

Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE

Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTMP

Attribute	Description
Name	MAKERDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the Transaction Status O - Open C - Close	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description	
Name	Contract-Parties	
Datatype		
Description	Indicates Party Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYCOUNTRY

Attribute	Description	
Name	PRTYCOUNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD3

Attribute	Description

Name	PRTYADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.4.BC-ModifyCollectRegistration-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *COLLREF*
      - *CUSTID*
      - *ORGDOCRECV*
      - *DUPDOCRECV*
      - *COVLETDATE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ORGDOCRECV

Attribute	Description	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	Description	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	Description	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.ModifyContract

Modify BC Contract

2.28.1.BC-ModifyContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

PRD
CCY
TENOR
UNITS
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
BRIDGL
CYSTALTYP
COLLLIQDAMT
LIQDLCCHGCOMM
MATDT
LOANAMT
BILLOS
CONTRACT_CURRENCY
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
ORGEXCHRATE
Bcprefdet
UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Effective-Int-Rate
CONREFNO
Effective-Intrate-Det
EFFECTDT
IRR
Intrest
CONREFNO
Intrest-Details

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- *FXREFNO*
- *TFAMT*
- *TFRATE*
- *CCY*

Loanacc

- *CONREFNO*
- *Loanaccdet*
  - *ACCNO*
  - *AMTFIN*
  - *CCY*

Extsys-Ws-Master

- *Extsys-Ws-Details*
  - *EXTWSRESP*
  - *USERREMARKS*

Brok-Master

- *CONREFNO*
- *CONTRACTCCY*
- *BROKPERCENT*
- *BROKAMT*
- *Brok-Detail*
  - *BROKNAME*
  - *BROKER*
  - *BRKACC*
  - *BRKACCCCY*
  - *BRKPERCENT*
  - *BRKAMTACCCCY*
  - *EXRATE*
  - *ORGEXRATE*
  - *NEGRATE*
  - *NEGREFNO*
  - *REMARKS*
  - *BRKAMTCONCCY*
  - *LIQSTATUS*

Lic-Master

- *License-Utils-Detail*
  - *IMPLICNO*
  - *GOODSCD*
  - *QTYUTIL*
  - *AMTUTIL*
  - *QTYREIN*
  - *AMTREIN*
  - *REMARKS*
  - *UNIT_OF_MEASUREMENT*
  - *LICENSE_AMOUNT*

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	**Description**	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	**Description**	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOCAL_CURRR

Attribute	**Description**	
Name	LOCAL_CURRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_LIAB_AMOUNT

Attribute	**Description**	
Name	LC_LIAB_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHG_REFUSED

Attribute	Description
Name	CHG_REFUSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description
Name	PASS_INT_TO_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATASDT

Attribute	Description
Name	STATASDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOAN_CONTREF

Attribute	Description
Name	LOAN_CONTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTID

Attribute	**Description**	
Name	PARTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTD

Attribute	Description	
Name	CHGAMTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSD

Attribute	Description	
Name	STATUSD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREFNOE

Attribute	Description	
Name	CONTREFNOE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENTE

Attribute	Description	
Name	COMPONENTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANAMT

Attribute	**Description**	
Name	LOANAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLOS

Attribute	**Description**	
Name	BILLOS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT_CURRENCY

Attribute	**Description**	
Name	CONTRACT_CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATECDPREF

Attribute	**Description**	
Name	RATECDPREF	
Datatype	String	
Description	Indicates Rate Code Prefernce	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B

TOP

MAXRATVAR

Attribute	**Description**
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	**Description**	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

GOODSCD

Attribute	**Description**	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

QTYUTIL

Attribute	**Description**	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTUTIL

Attribute	**Description**	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYREIN

Attribute	**Description**

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.28.2.BC-ModifyContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *AMOUNT*
    - *LCAMOUNT*
    - *VALDT*
    - *MATDT*
    - *TENOR_DAYS*
    - *TRANSITDAYS*
    - *BASDT*
    - *BASDTDES*
    - *VDATECR*
    - *DRVALDT*

LIQDDATE
INTLIQDMOD
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
FORFAITREQDT
FORFAITDOCDT
PURAMT
UNLNKFXRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
LATEVNSEQNO
ESN
USRDEFSTATS
SUBSYSSTAT
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ACPTOADVFLG
COLLCADVCHGFROM

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
Contract-Parties
- *ESN*
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *ESN*
  - *PARTTYP*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *ESN*
- *PARTTYP*
- *OPERATION*
- *CRLINE*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *ESN*
- *DOCCD*
- *DESC*
- *Doc-Clause*
  - *ESN*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *ESN*
- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *ESN*
- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *ESN*
- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ESN*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *ESN*
- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*

PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG

Acc-Fate

MANGENFLG
ESN
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART

Contract-Disc

ESN
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT

Contract-Reserve

ESN
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG

Roll-Pref

ESN
BASEDT
BASEDTDESC
TNRDAYS

- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *ESN*
- *AMTNAM*
- *AMT*

Invoice-Master

- *MARG*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *ESN*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *ESN*
- *COMP*
- *INTFRMDT*
- *INTTODT*

Pack-Credit-Dtls

Bctbs-Int-Chg-Calc

- *STDTA*
- *INTRATEA*
- *INTAMOUNTA*
- *STDTB*
- *INTRATEB*
- *INTAMOUNTB*
- *STDTC*
- *INTRATEC*
- *INTAMOUNTC*
- *STDTD*

- CHGPERD
- CHGAMTD
- STDTE
- CHGPERE
- CHGAMTE
- STDTF
- CHGPERF
- CHGAMTF

Contract-Multitnr

- BASDATE
- VALUDATE
- TNOR
- TRANSTDAYS
- MATDAT
- SPLITPCT
- BILLAMNT
- DISCOUNTAMT
- REBATAMT
- EXCRATE
- DISCOUNTDAMT
- FRMCALCDATE
- TOCALCDATE
- USRDFNDSTS
- UNDERPROTEST
- PROTESTDATE

Taxes

- CONREFNO
- LATEVNSEQNO
- Tax
  - SCHEME
  - WAIVER
  - Tax-Details
    - BASISAMNTAG
    - COMPUEVNT
    - WAIVER
    - ESN
    - Rule-Details
      - COMPUTATIONDT
      - CCY
      - AMT
      - ESN
      - EFFECTIVEDT
      - STAT
      - BASISAMT

BASISAMTCCY

TXNUDFDETAILS

FLDNAME

FLDVAL

Charges

LATEVNSEQNO

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

WAIVER

DISACCRAPPL

ACCRREQD

DESC

Charge-Application

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

CHRGCCY

CHRGAMT

LIQDSTAT

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

ESN

EVENTCD

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

Linkages

CONREFNO

LATEVNSEQNO

- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *CONREFNO*
  - *VERNO*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Misdetails*
  - *CONREFNO*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFXRATE*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*
  - *COMPMIS10*
  - *COMPMIS2*
  - *COMPMIS3*

- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*
    - *ITIMEIND1*
    - *ITIMEIND2*

ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6

DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
LOANACC
Bcpref
CONREFNO
LATEVNSEQNO
EXCHRT
RTTYP
MATDT
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
Bcprefdet
UDEID
RTCD
USAGE
INTRT
UDEDESC
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest
CONREFNO
LATEVNSEQNO
Bcfx
BILLREFNO
ESN
Loanacc
CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

BROKPERCENT

BROKAMT

Brok-Detail

BROKNAME

BCREFNO

EVENTSEQNO

BROKER

BRKACC

BRKACCCCY

BRKPERCENT

BRKAMTACCCCY

EXRATE

ORGEXRATE

NEGRATE

NEGREFNO

REMARKS

SQNO

BRKAMTCONCCY

LIQSTATUS

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

AMTQ_UT

AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	**Description**	
Name	THEIR_LCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	**Description**	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	**Description**
Name	VALDT

Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

VDATECR

Attribute	Description	
Name	VDATECR	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRVALDT

Attribute	Description	
Name	DRVALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDDATE

Attribute	Description	
Name	LIQDDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTLIQDMOD

Attribute	Description	
Name	INTLIQDMOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,I

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PURAMT

Attribute	Description
Name	PURAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,U,A

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FURTHER_IDENTIFICATION

Attribute	**Description**	
Name	FURTHER_IDENTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD2

Attribute	Description
Name	PARTADD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CRLINE

Attribute	**Description**	
Name	CRLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

LIMITAMT

Attribute	**Description**	
Name	LIMITAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUST_NO

Attribute	**Description**	
Name	CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKAGETYP

Attribute	**Description**	
Name	LINKAGETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DESTO

Attribute	**Description**	
Name	DESTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CARNAM

Attribute	**Description**	
Name	CARNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARSHIPINFO

Attribute	**Description**	
Name	PARSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDTLS

Attribute	**Description**	
Name	SHIPDTLS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	Description	
Name	ADVFTREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

ADVFTMED

Attribute	Description	
Name	ADVFTMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADVFTRECPART

Attribute	Description	
Name	ADVFTRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCMSGDT

Attribute	**Description**	
Name	ACCMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Fate

Attribute	**Description**	
Name	Acc-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ESN

Attribute	**Description**
Name	ESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description

Name	RESRELDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAYS

Attribute	Description	
Name	MATDAYS	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTLIQDMOD

Attribute	Description	
Name	INTLIQDMOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,I

TOP

FRMCALCDT

Attribute	Description	
Name	FRMCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	Description	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	Description	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	

Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

AMT

Attribute	Description
Name	AMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STDTA

Attribute	**Description**	
Name	STDTA	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTRATEA

Attribute	**Description**	
Name	INTRATEA	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAMOUNTA

Attribute	**Description**	
Name	INTAMOUNTA	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STDTB

Attribute	**Description**	
Name	STDTB	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTRATEB

Attribute	**Description**	
Name	INTRATEB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTC

Attribute	Description
Name	STDTC
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGAMTF

Attribute	Description
Name	CHGAMTF
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description

Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description

Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY

Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT

Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description

Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String

Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing

Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	Description	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	Description	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2

Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	**Description**	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINRTVAR

Attribute	**Description**	
Name	MINRTVAR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PMNTMD

Attribute	**Description**	
Name	PMNTMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description	Indicates Debit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DRPRODAC

Attribute	**Description**	
Name	DRPRODAC	
Datatype	String	
Description	It indicates Debit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SQNO

Attribute	**Description**	
Name	SQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTCONCCY

Attribute	**Description**
Name	BRKAMTCONCCY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.28.3.BC-ModifyContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF

Contract-Multitnr

SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY
PRD
CCY
TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- *CCY*
- *Loanacc*
  - *CONREFNO*
  - *Loanaccdet*
    - *ACCNO*
    - *AMTFIN*
    - *CCY*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*
    - *GOODSCD*
    - *QTYUTIL*
    - *AMTUTIL*
    - *QTYREIN*
    - *AMTREIN*
    - *REMARKS*
    - *UNIT_OF_MEASUREMENT*
    - *LICENSE_AMOUNT*
    - *GOODSDESC*
    - *AMTQ_UT*
    - *AMTQ_RE*

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,F,C,P</td></tr></table>

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

JVPARENT

Attribute	**Description**	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	**Description**	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	**Description**	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	**Description**	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVTRACDT

Attribute	**Description**	
Name	PREVTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NUMTRSENT

Attribute	**Description**	
Name	NUMTRSENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTTRACDT

Attribute	**Description**	
Name	NEXTTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACRECPART

Attribute	**Description**	
Name	TRACRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PAYMSGDT

Attribute	**Description**
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTD

Attribute	Description	
Name	CHGAMTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSD

Attribute	Description	
Name	STATUSD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREFNOE

Attribute	Description	
Name	CONTREFNOE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENTE

Attribute	Description	
Name	COMPONENTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	Description	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	Description	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRREQRD

Attribute	**Description**	
Name	ACRREQRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACQRCCY

Attribute	**Description**	
Name	ACQRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTYP

Attribute	**Description**	
Name	RTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENATYTYP

Attribute	**Description**	
Name	PENATYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENOMITORBASIS

Attribute	Description	
Name	DENOMITORBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPRE

Attribute	Description	
Name	NOINTPRE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPRD

Attribute	Description	
Name	MINSPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.4.BC-ModifyContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *EXTREFNO*
      - *USEREFNO*
      - *OPERATION*
      - *STAG*
      - *LCISSUEDATE*
      - *LCREFNO*
      - *THEIR_LCREF*
      - *AMOUNT*
      - *LCAMOUNT*
      - *VALDT*
      - *MATDT*
      - *TENOR_DAYS*
      - *TRANSITDAYS*
      - *BASDT*

BASDTDES
VDATECR
DRVALDT
LIQDDATE
INTLIQDMOD
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
FORFAITREQDT
FORFAITDOCDT
PURAMT
UNLNKFXRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
LATEVNSEQNO
ESN
USRDEFSTATS
SUBSYSSTAT
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID

SETTLEAMT
ACPTOADVFLG
COLLCADVCHGFROM
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
Contract-Parties
- *ESN*
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *ESN*
  - *PARTTYP*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *ESN*
- *PARTTYP*
- *OPERATION*
- *CRLINE*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *ESN*
- *DOCCD*
- *DESC*
- *Doc-Clause*

ESN
CLAUSECD
CLAUSEDESC
Goods-Details
ESN
GOODSCODE
GOODSDESC
INCOTRM
Shipment
ESN
SHIPMRKS
DESFROM
DESTO
CARNAM
PARSHIPINFO
SHIPDTLS
LATSHIPDT
TRNSSHIPFLAG
SHIPDT
ARRVDT
OTHRSHIPINFO
Pay-Excep
ESN
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
TRACRECPART
PAYMSGDT
NONPAYMSGDT
PROTFLG
DTOFPROT
MANGENFLG
Pay-Fate
ESN
ADVFTREQDFLG
ADVFTMED
ADVFTRECPART
MANGENFLG
Acc-Excep
ESN
TRCREQDFLG
NUMTRCTOSENT

TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG

Acc-Fate
MANGENFLG
ESN
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART

Contract-Disc
ESN
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT

Contract-Reserve
ESN
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG

Roll-Pref
ESN

- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *ESN*
- *AMTNAM*
- *AMT*

Invoice-Master

- *MARG*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *ESN*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *ESN*
- *COMP*
- *INTFRMDT*
- *INTTODT*

Pack-Credit-Dtls

Bctbs-Int-Chg-Calc

- *STDTA*
- *INTRATEA*
- *INTAMOUNTA*
- *STDTB*
- *INTRATEB*
- *INTAMOUNTB*
- *STDTC*

- *INTRATEC*
- *INTAMOUNTC*
- *STDTD*
- *CHGPERD*
- *CHGAMTD*
- *STDTE*
- *CHGPERE*
- *CHGAMTE*
- *STDTF*
- *CHGPERF*
- *CHGAMTF*

Contract-Multitnr

- *BASDATE*
- *VALUDATE*
- *TNOR*
- *TRANSTDAYS*
- *MATDAT*
- *SPLITPCT*
- *BILLAMNT*
- *DISCOUNTAMT*
- *REBATAMT*
- *EXCRATE*
- *DISCOUNTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *ESN*
    - *Rule-Details*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

EFFECTIVEDT
STAT
BASISAMT
BASISAMTCCY
TXNUDFDETAILS
FLDNAME
FLDVAL
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
CHRGCCY
CHRGAMT
LIQDSTAT
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
ESN
EVENTCD
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *CONREFNO*
  - *VERNO*
  - *LINKEDTOREF*
  - *LINKAGETYP*

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*

- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*

INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3

SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
LOANACC
Bcpref
CONREFNO
LATEVNSEQNO
EXCHRT
RTTYP
MATDT
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
Bcprefdet
UDEID
RTCD
USAGE
INTRT
UDEDESC
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest
CONREFNO
LATEVNSEQNO
Bcfx
BILLREFNO

ESN
Loanacc
CONREFNO
LATEVNSEQNO
Extsys-Ws-Master
KEYID
Brok-Master
CONREFNO
LATEVNSEQNO
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BCREFNO
EVENTSEQNO
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
SQNO
BRKAMTCONCCY
LIQSTATUS
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
AMTQ_UT
AMTQ_RE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCREFNO

Attribute	Description
Name	LCREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,I

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**	
Name	REC_INT_RTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REBATE_AMT

Attribute	**Description**	
Name	REBATE_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CRLINE

Attribute	Description
Name	CRLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6500</td></tr></table>

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Shipment

Attribute	Description	
Name	Shipment	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SHIPMRKS

Attribute	Description	
Name	SHIPMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

DESFROM

Attribute	Description	
Name	DESFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>400</td></tr></table>

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	**Description**	
Name	ADVFTREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

ADVFTMED

Attribute	**Description**	
Name	ADVFTMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADVFTRECPART

Attribute	**Description**	
Name	ADVFTRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Excep

Attribute	Description	
Name	Acc-Excep	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRCREQDFLG

Attribute	Description	
Name	TRCREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description	
Name	NUMTRCTOSENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACMED

Attribute	Description	
Name	TRACMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Fate

Attribute	**Description**	
Name	Acc-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	**Description**
Name	ADVFTREQDFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3500

TOP

DISCRESLFLG

Attribute	**Description**	
Name	DISCRESLFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,N

TOP

DISCRESDT

Attribute	**Description**	
Name	DISCRESDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCRECDT

Attribute	**Description**	
Name	DISCRECDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Reserve

Attribute	**Description**	
Name	Contract-Reserve	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ESN

Attribute	**Description**
Name	ESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description

Name	DISCAPPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTCOD

Attribute	Description
Name	BASEDTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description	
Name	ADDRLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTB

Attribute	Description
Name	STDTB
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STDTC

Attribute	**Description**	
Name	STDTC	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTRATEC

Attribute	**Description**	
Name	INTRATEC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAMOUNTC

Attribute	**Description**	
Name	INTAMOUNTC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STDTD

Attribute	**Description**	
Name	STDTD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGPERD

Attribute	**Description**	
Name	CHGPERD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGAMTF

Attribute	Description
Name	CHGAMTF
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description

Name	TOCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Includes Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

BASISAMNTAG

Attribute	**Description**	
Name	BASISAMNTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	**Description**	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String

Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Collateral-details

Attribute	**Description**	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Collateral

Attribute	**Description**
Name	Collateral

Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	**Description**	
Name	REFXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description

Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**
Name	ENVCONT2
Datatype	String

Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4

Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Adice

Attribute	**Description**	
Name	Adice	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LOANACC

Attribute	**Description**	
Name	LOANACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXCHRT

Attribute	**Description**

Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String

Description	Indicates Credit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BCREFNO

Attribute	**Description**	
Name	BCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTSEQNO

Attribute	**Description**	
Name	EVENTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRKACC

Attribute	**Description**	
Name	BRKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

BRKACCCCY

Attribute	Description	
Name	BRKACCCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SQNO

Attribute	Description
Name	SQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQSTATUS

Attribute	**Description**	
Name	LIQSTATUS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Lic-Master

Attribute	**Description**	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

License-Utils-Detail

Attribute	**Description**
Name	License-Utils-Detail
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.ModifyDocArrival

Modify BC Document Arrival

2.29.1.BC-ModifyDocArrival-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

2.29.2.BC-ModifyDocArrival-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *CONREFNOLOG*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*
      - *COVLETREF*

COVLETDATE
FRSTMAILORG
SECMAILORG
Goods-Details
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
TRNSSHIPFLAG
PARTIALSHPMNT
Adice

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.29.3.BC-ModifyDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*

COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

BRNCD

Attribute	Description

Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	Description	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	Description	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	Description	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.4.BC-ModifyDocArrival-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *CONREFNOLOG*
      - *MAKER*
      - *MAKDTTIME*
      - *CHKR*
      - *CHKDTTIME*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Doc-Details*
        - *DOCODE*
        - *DOCDESC*
        - *FRSTMAILCOP*
        - *SECMAILCOP*
        - *REIM_BANK*

DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
Goods-Details
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,A

TOP

Doc-Details

Attribute	Description	
Name	Doc-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DOCODE

Attribute	Description	
Name	DOCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DOCDESC

Attribute	Description	
Name	DOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

FRSTMAILCOP

Attribute	Description

Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description

Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

TRNSSHIPFLAG

Attribute	Description	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description	
Name	PARTIALSHPMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Adice

Attribute	Description	
Name	Adice	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.30.ModifyDocs

Modification of Bills and Collections Document Code

2.30.1.BC-ModifyDocs-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*

CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-IO*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *MODNO*
    - *Docs-Clauses*
      - *CLAUSECODE*
      - *LANGCODEDET*
      - *DOCCODE*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Indicates the Documents Master IO details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.30.3.BC-ModifyDocs-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*
      - *CLAUSECODE*
      - *LANGCODEDET*
      - *DOCCODE*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC

Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description

Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.4.BC-ModifyDocs-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-PK*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *MODNO*
      - *Docs-Clauses*
        - *CLAUSECODE*
        - *LANGCODEDET*
        - *DOCCODE*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE
Docs-Master-Full
DOCCODE
LANGCODE
DOCSHORTDESC
DOCLONGDESC
DOCTYPE
VALIDATESHIPGUA
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Docs-Clauses
CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-PK

Attribute	Description
Name	Docs-Master-PK
Datatype	
Description	Indicates the Documents master primary key details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Indicates the Documents master IO details.

TOP

DOCCODE

Attribute	Description	
Name	DOCCODE	
Datatype	String	
Description	Indicates the Document Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String

Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Indicates the Documents master Full details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	**Description**	
Name	VALIDATESHIPGUA	
Datatype	String	
Description	Indicates the Validate Ship Guarantee.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Docs-Clauses

Attribute	Description	
Name	Docs-Clauses	
Datatype		
Description	Includes the Documents Clauses.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE

Attribute	Description	
Name	CLAUSECODE	
Datatype	String	
Description	Indicates the Clause Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

LANGCODEDET

Attribute	Description

Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.ModifyFfts

Modification of Bills and Collections Free Format Code

2.31.1.BC-ModifyFfts-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Fft-Master-Full

Attribute	Description

Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Modification details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

2.31.2.BC-ModifyFfts-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-IO*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MODNO*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections Free Format Code Modification-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.31.3.BC-ModifyFfts-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Modification details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.4.BC-ModifyFfts-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-PK*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Fft-Master-Full*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*

MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-PK

Attribute	Description
Name	Fft-Master-PK
Datatype	
Description	Includes Bills and Collections Free Format Code Modification-Primary key details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections Free Format Code Modification-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Fft-Master-Full

Attribute	**Description**
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Modification details

TOP

FFTCODE

Attribute	**Description**	
Name	FFTCODE	
Datatype	String	
Description	Indicates Text Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description

Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.ModifyProduct

Modification of Bills and Collections Product

2.32.1.BC-ModifyProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*

DTC
PTC
DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N

BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N

- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*

- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
- Role-To-Head-Mapping
  - CLASCD
  - CLASDESC
  - Mapping-Details
    - ACCTRL
    - ROLDESC
    - ACCTHD
    - GLDESC
- Product-Events
  - CLASCD
  - CLASDESC
  - Event-Details
    - EVNTCD
    - EVENTDESC
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
      - RATE_TYPE_INDICATOR
    - Advices
      - MSGTYP
      - DESC
      - GENTIME
      - SUPRS
      - PRIOR
      - CHGREQD
- Branch-Ccy-Restrictions
  - CCYLST

- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*

- *AMNDAFTRASSOC*
- *ALWAMTAMND*
- *AMNDAFTRAPPL*
- *STPASOCIATN*
- *ADVCHG*
- *CAPTLIZE*
- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Discount-Accrual

- *CLASCD*
- *CLASDESC*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *CCYNAME*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*

STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Modification details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT

Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP

Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TC

Attribute	**Description**	
Name	TC	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,U

TOP

ATF

Attribute	**Description**	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	**Description**	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	**Description**	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N

Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N

Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	**Description**	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description

Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description

Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRANSITDAYS_N

Attribute	**Description**	
Name	TRANSITDAYS_N	
Datatype	Number	
Description	Indicates Transit Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INCOTERM_N

Attribute	**Description**	
Name	INCOTERM_N	
Datatype	String	
Description	Indicates INCO Term	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

LTL

Attribute	**Description**	
Name	LTL	
Datatype	String	
Description	Indicates whether Export Bill should be Linked to a Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPCOLTYPE

Attribute	**Description**	
Name	ACPCOLTYPE	
Datatype	String	
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	Indicates Transfer Collateral from LC Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description

Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String

Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String

Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description	
Name	TRANSACTIONCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Status-Advices-Details

Attribute	Description	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MESSAGECD

Attribute	Description	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message Code	
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DERVTNRUL

Attribute	Description	
Name	DERVTNRUL	
Datatype	String	
Description	Indicates Status Derivation Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	

Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description	
Name	UPWARDTRANSFERTOGL_N	
Datatype	String	
Description	Indicates Upward Transfer To GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description	
Name	UPWARDTRANSFERTOGLDESC_N	
Datatype	String	
Description	Indicates Upward Transfer To GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description	
Name	DWNWRDTRANSFERFRMGL_N	
Datatype	String	
Description	Indicates Downward Transfer From GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description	
Name	DWNWRDTRANSFERFRMGLDESC_N	
Datatype	String	
Description	Indicates Downward Transfer From GL Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Indicates Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AMNTTAG

Attribute	**Description**	
Name	AMNTTAG	
Datatype	String	
Description	Indicates the Tax Component of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description

Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description

Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Cust Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Customer Category Desription	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String

Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	Description	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences

Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	**Description**	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	**Description**	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.32.2.BC-ModifyProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *ATF*
    - *DTF*
    - *TARCKACCRDCOMPFLAG_N*
    - *TARCKDISCBILLFLAG_N*
    - *LIMTSTENORCALCTYPE*
    - *AUTOACPTOADVFLAG_N*

AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
FORFAITINTCOMP_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
MODNO
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details

- *INSCD_N*
- *INSCDDESC_N*
- *ADVCD_N*
- *INSSLNO*

Fft-Details

- *FFTTXTCD*
- *FFTCDDESC*
- *ADVCD_I*
- *FFTSLNO*

Document-Details

- *DOCODE_N*
- *DOCTYPE*
- *DOCDESR*
- *DOCSLNO*
- *Clause-Details*
  - *CLAUSECODE_N*
  - *CLAUSEDESCR_N*
  - *CLAUSESLNO*

Tracer-Details

- *RESEXTARCERFLAG_N*
- *RESEXNUMTARCERS_N*
- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*

- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Status-Control-Details*
  - *CMPNENT_N*
  - *TRANSFERDAYS_N*
  - *MATURITYDAYS_N*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*
- *Tax-Scheme*
  - *SCHME*
  - *Tax-Details*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *Mapping-Details*
    - *ACCTRL*
    - *ACCTHD*
    - *STAT*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*

REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
Advices
MSGTYP
SUPRS
PRIOR
CHGREQD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Fields
Field-Details
FLDNUM
FLDNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Charges
Charge-Details

- *SETTCCY*
- *DFTWAIV*
- *ALWRULAMND*
- *AMNDAFTRASSOC*
- *ALWAMTAMND*
- *AMNDAFTRAPPL*
- *STPASOCIATN*
- *ADVCHG*
- *DFTRULE*
- *COMPNT*

Product-Discount-Accrual

- *CLASCD*
- *CLASTYP*
- *PRD*
- *CLASDESC*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *CCYNAME*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*
  - *RESETTENOR*
  - *BRWLENDIND*
  - *LVLNO*
  - *PREPMTMETD*
  - *PROPREQD*
  - *MARGNBASIS*
  - *MARGNAPPLN*
  - *RATECALCTYP*
  - *ACQREQD*
  - *CHNGDRGAMNDMNT*

SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*
- *COMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Modification-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP

Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PTC

Attribute	**Description**	
Name	PTC	
Datatype	String	
Description	Indicates whether Purchase to Collection is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATF

Attribute	**Description**	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	**Description**	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	**Description**	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N

Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N

Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	**Description**	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description

Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description

Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE
Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Charge-Their-Details

Attribute	Description	
Name	Charge-Their-Details	
Datatype		
Description	Includes Charge their details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

COMPONENT

Attribute	Description	
Name	COMPONENT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTCODE

Attribute	Description	
Name	EVNTCODE	
Datatype	String	
Description	Indicates Liquidation Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Instructions-Details

Attribute	Description	
Name	Instructions-Details	
Datatype		
Description	Includes Instructions details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I

Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description

Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description	
Name	Status-Advices-Details	
Datatype		
Description	Includes Status Advices details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

MESSAGECD

Attribute	Description	
Name	MESSAGECD	
Datatype	String	
Description	Indicates Message Code	
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Status-Control-Details

Attribute	Description	
Name	Status-Control-Details	
Datatype		
Description	Includes Status Control details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

CMPNENT_N

Attribute	Description	
Name	CMPNENT_N	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TRANSFERDAYS_N

Attribute	Description	
Name	TRANSFERDAYS_N	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATURITYDAYS_N

Attribute	Description
Name	MATURITYDAYS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Includes Product Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Role To Head Mapping	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**

Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,C</td></tr></table>

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD

Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	Description	
Name	MISTYP	
Datatype	String	
Description	Indicates MIS type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fileds
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASTYP

Attribute	Description
Name	CLASTYP
Datatype	String
Description	Indicates Class Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description

Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Name

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S

TOP

RATCD

Attribute	**Description**	
Name	RATCD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SETTLMNTCCY

Attribute	**Description**	
Name	SETTLMNTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STPAPPLICTION

Attribute	**Description**	
Name	STPAPPLICTION	
Datatype	String	
Description	Indicates Stop Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	**Description**	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

EVNTDESC

Attribute	**Description**	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Interest-Ccy-Preferences

Attribute	**Description**	
Name	Interest-Ccy-Preferences	
Datatype		
Description	Includes Interest Currency preferences details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates Account Currency	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description

Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

2.32.3.BC-ModifyProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *DOC*

ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N

TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N
  ACCEXCTRACERFLAG_I
  ACCEXCNUMTRACERS_N
  PAYEXTARCERFLAG_T

- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*

- AMNTTAG
- BASISAMNTTAG
- COMPTATIONEVNT
- TYP

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Branch-Ccy-Restrictions

- CCYLST
- BRNLST
- CLASCD
- CLASDESC

- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

- *STPASOCIATN*
- *ADVCHG*
- *CAPTLIZE*
- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Discount-Accrual

- *CLASCD*
- *CLASDESC*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *CCYNAME*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*
  - *RESETTENOR*
  - *BRWLENDIND*

LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Modification details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indciates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OP

Attribute	**Description**	
Name	OP	
Datatype	String	
Description	Indicates Operation Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF
Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REKEYREQFLAG_N

Attribute	**Description**	
Name	REKEYREQFLAG_N	
Datatype	String	
Description	Indicates whether Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYAMNTFLAG_N

Attribute	**Description**	
Name	REKEYAMNTFLAG_N	
Datatype	String	
Description	Indicates Amount Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	**Description**	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	**Description**	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description
Name	REKYMATURTYDATE_N
Datatype	String
Description	Indicates whether Maturity Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N

Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD_N

Attribute	Description	
Name	LOANPRD_N	
Datatype	String	
Description	Indicates Loan Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DISCNTMETHOD

Attribute	Description	
Name	DISCNTMETHOD	
Datatype	String	
Description	Indicates Discounting Method Discounted : D True Discounted : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,T,

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

FREECOLLFLAG_N

Attribute	Description	
Name	FREECOLLFLAG_N	
Datatype	String	
Description	Indicates whether the Product is used for Free Collection	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description	
Name	BILLNOTICEDAYS_N	
Datatype	Number	
Description	Indicates Billing Notice Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description	
Name	BILLNOTICEREQDFLAG_N	
Datatype	String	
Description	Indicates whether Billing Notice is Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BILLNOTICEFLAG

Attribute	Description	
Name	BILLNOTICEFLAG	
Datatype	String	
Description	Indicates bill notice Before : B After : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

ACCRUALFREQ_N

Attribute	Description	
Name	ACCRUALFREQ_N	
Datatype	String	
Description	Indicates Accrual Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE

Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	**Description**	
Name	TRANSFERCOLLATFROMLC	
Datatype	String	
Description	Indicates Transfer Collateral from LC Flag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description

Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXMEDIUM_N

Attribute	**Description**	
Name	RESEXMEDIUM_N	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCEXCSTARTDAY_I

Attribute	**Description**	
Name	ACCEXCSTARTDAY_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCFREQ_I

Attribute	**Description**	
Name	ACCEXCFREQ_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Generation Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCMEDIUM_I

Attribute	**Description**	
Name	ACCEXCMEDIUM_I	
Datatype	String	
Description	Indicates Acceptance Exception Tracer Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYEXSTARTDAY_T

Attribute	**Description**
Name	PAYEXSTARTDAY_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM

Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description

Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String

Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates the Tax Component of Tax Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String

Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Cust Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	**Description**	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	**Description**	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String

Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description

Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String

Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPMTMETD

Attribute	**Description**	
Name	PREPMTMETD	
Datatype	String	
Description	Indicates Pre Payment Method Flexcube : F Custom : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,C

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	**Description**	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	**Description**	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.4.BC-ModifyProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *ATA*
      - *ATD*
      - *CTP*
      - *DTC*
      - *PTC*
      - *ATF*
      - *DTF*
      - *TARCKACCRDCOMPFLAG_N*

TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
FORFAITINTCOMP_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
MODNO
Charge-Their-Details

- *COMPONENT*
- *EVNTCODE*

Instructions-Details

- *INSCD_N*
- *INSCDDESC_N*
- *ADVCD_N*
- *INSSLNO*

Fft-Details

- *FFTTXTCD*
- *FFTCDDESC*
- *ADVCD_I*
- *FFTSLNO*

Document-Details

- *DOCODE_N*
- *DOCTYPE*
- *DOCDESR*
- *DOCSLNO*
- *Clause-Details*
  - *CLAUSECODE_N*
  - *CLAUSEDESCR_N*
  - *CLAUSESLNO*

Tracer-Details

- *RESEXTARCERFLAG_N*
- *RESEXNUMTARCERS_N*
- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Status-Control-Details*
  - *CMPNENT_N*
  - *TRANSFERDAYS_N*
  - *MATURITYDAYS_N*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*
- *Tax-Scheme*
  - *SCHME*
  - *Tax-Details*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *Mapping-Details*
    - *ACCTRL*
    - *ACCTHD*
    - *STAT*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*

MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
Advices
MSGTYP
SUPRS
PRIOR
CHGREQD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Fields
Field-Details
FLDNUM
FLDNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID

ALWD

Product-Charges

Charge-Details

SETTCCY

DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DFTRULE

COMPNT

Product-Discount-Accrual

CLASCD

CLASTYP

PRD

CLASDESC

Disc-Accr-Details

DISCACCRREQD

ACCRFREQ

PREPAYTBDTREAT

ACQTYP

Ccy-Preferences

CCYCODE

CCYNAME

DENOMDCNTMET

DENOMMETHOD

Product-Interest

Interest-Components

BASISAMNTTYP

BASISAMNTCATG

RATCDUSGE

RATTYP

RATCD

SETTLMNTCCY

STPAPPLICTION

RESETTENOR

BRWLENDIND

LVLNO

PREPMTMETD

PROPREQD

MARGNBASIS

MARGNAPPLN

RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
COMP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Includes Bills and Collections- Product Modification-Primary key details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Modification-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ATF

Attribute	Description	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	Description	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description	
Name	TARCKDISCBILLFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required for Discount Bills	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPINTCOMP

Attribute	Description	
Name	ACPINTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ICCFCOLTYPE

Attribute	Description	
Name	ICCFCOLTYPE	
Datatype	String	
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

GOODSARRFLAG_N

Attribute	Description	
Name	GOODSARRFLAG_N	
Datatype	String	
Description	Indicates whether Past Due Status should be based on Goods Arrival Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTNR

Attribute	**Description**	
Name	MINTNR	
Datatype	Number	
Description	Indicates Minimum Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	**Description**	
Name	MAXTNR	
Datatype	Number	
Description	Indicates Maximum Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STNDRDTNR_N

Attribute	**Description**	
Name	STNDRDTNR_N	
Datatype	Number	
Description	Indicates Standard Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REKEYREQFLAG_N

Attribute	**Description**	
Name	REKEYREQFLAG_N	
Datatype	String	
Description	Indicates whether Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYAMNTFLAG_N

Attribute	**Description**
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	**Description**	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	**Description**	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	**Description**	
Name	REKYVALDATE_N	
Datatype	String	
Description	Indicates whether Value Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description

Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD_N

Attribute	Description
Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String

Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE
Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description	
Name	CHGCLAIM	
Datatype	String	
Description	Indicates whether Charge Claim is Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBROK

Attribute	Description	
Name	ALLWBROK	
Datatype	String	
Description	Indicates whether Brokerage is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Charge-Their-Details

Attribute	Description	
Name	Charge-Their-Details	
Datatype		
Description	Includes Charge their details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description

Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Status-Control-Details

Attribute	Description
Name	Status-Control-Details
Datatype	
Description	Includes Status Control details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

CMPNENT_N

Attribute	Description
Name	CMPNENT_N
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TRANSFERDAYS_N

Attribute	Description
Name	TRANSFERDAYS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATURITYDAYS_N

Attribute	Description
Name	MATURITYDAYS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Includes Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Product Tax details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Role To Head Mapping	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	**Description**

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	Description	
Name	Accounting-Entries	
Datatype		
Description	Accounting Entry Details for Events	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

ACCRLCD

Attribute	Description	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description

Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	**Description**	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRS

Attribute	Description	
Name	SUPRS	
Datatype	String	
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	**Description**	
Name	MISTYP	
Datatype	String	
Description	Indicates MIS type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fileds
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges

Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASTYP

Attribute	Description
Name	CLASTYP
Datatype	String
Description	Indicates Class Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Name
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String

Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String

Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINRATE

Attribute	**Description**	
Name	MINRATE	
Datatype	Number	
Description	Indicates Minimum Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRAT

Attribute	**Description**	
Name	MAXRAT	
Datatype	Number	
Description	Indicates Maximum Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DFLTSPRD

Attribute	**Description**	
Name	DFLTSPRD	
Datatype	Number	
Description	Indicates Default Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPRD

Attribute	**Description**	
Name	MINSPRD	
Datatype	Number	
Description	Indicates Minimum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPRD

Attribute	**Description**	
Name	MAXSPRD	
Datatype	Number	
Description	Indicates Maximum Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.NewFfts

Input of Bills and Collections Free Format Code

2.33.1.BC-NewFfts-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Fft-Master-Full

Attribute	Description

Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Input details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

2.33.2.BC-NewFfts-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-IO*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections Free Format Code Input-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String

Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.33.3.BC-NewFfts-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Input details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.4.BC-NewFfts-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-PK*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE
FIELD_VALUE
VAL_TYPE
Fft-Master-Full
FFTCODE
LANGCODE
FREEFORMATTEXT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-PK

Attribute	Description
Name	Fft-Master-PK
Datatype	
Description	Includes Bills and Collections Free Format Code Input-Primary key details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections Free Format Code Input-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT

Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections Free Format Code Input details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FREEFORMATTEXT

Attribute	**Description**	
Name	FREEFORMATTEXT	
Datatype	String	
Description	Indicates Free Format Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User Identification who inputted the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the inputting time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Identification who authorised the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description

Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.34.AuthPayment

Authorization of Bills and Collections Payment

2.34.1.BC-Payment-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Liq-Summary*
      - *VALDATE*
      - *TOTPAID*
    - *Contract-Liq*
      - *FCCREF*
      - *ESN*
      - *COMP*
      - *AMTDUE*
      - *COMPCCY*
      - *PREPAYINT*
    - *Contract-Ovd*
      - *ERRMSG*
      - *STATUS*

AUTHBY

AUTHDTSTAMP

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the Contract that has been successfully Authorized

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Bills and Collections-Payment Authorization details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern: [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERRMSG

Attribute	Description
Name	ERRMSG
Datatype	String
Description	Indicates Error message
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String

Description	Indicates Status
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{1}</td></tr></table>

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

2.34.2.BC-Payment-Auth-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-IO*
    - *FCCREF*
    - *XREF*
    - *Contract-Liq-Summary*
      - *VALDATE*
      - *TOTPAID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract that is authorized

TOP

Contract-IO

Attribute	Description
Name	Contract-IO
Datatype	
Description	Includes Bills and Collections-Payment Authorization-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

2.34.3.BC-Payment-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract*
    - *FCCREF*
    - *XREF*
    - *Contract-Liq-Summary*
      - *VALDATE*
      - *TOTPAID*
    - *Contract-Liq*
      - *FCCREF*
      - *ESN*
      - *COMP*
      - *AMTDUE*
      - *COMPCCY*
      - *PREPAYINT*
    - *Contract-Ovd*
      - *ERRMSG*
      - *STATUS*
      - *AUTHBY*
      - *AUTHDTSTAMP*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract Authorized

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Bills and Collections-Payment Authorization details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID

Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern: [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERRMSG

Attribute	Description
Name	ERRMSG
Datatype	String
Description	Indicates Error message
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String

Description	Indicates Status
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{1}

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.4.BC-Payment-Auth-Res-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-PK*
      - *FCCREF*
      - *XREF*
      - *Contract-Liq-Summary*
        - *VALDATE*
        - *TOTPAID*
    - *Contract*
      - *FCCREF*
      - *XREF*
      - *Contract-Liq-Summary*
        - *VALDATE*
        - *TOTPAID*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*
        - *AMTDUE*
        - *COMPCCY*

PREPAYINT
Contract-Ovd
ERRMSG
STATUS
AUTHBY
AUTHDTSTAMP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full responce information relating the BC Contract for which interest has been paid

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-PK

Attribute	Description
Name	Contract-PK
Datatype	
Description	Includes Bills and Collections-Payment Authorization-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Bills and Collections-Payment Authorization details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERRMSG

Attribute	Description
Name	ERRMSG
Datatype	String
Description	Indicates Error message
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{1}</td></tr></table>

TOP

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	Indicates the User Identification who authorised the record
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AUTHDTSTAMP

Attribute	Description
Name	AUTHDTSTAMP
Datatype	Date
Description	Indicates the Authorised time of the record

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.DeletePayment

Deletion of Bills and Collections Payment

2.35.1.BC-Payment-Del-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*

FCCREF
ESN
COMP
AMTDUE
COMPCCY
PREPAYINT

STTLMENT

ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract interest payment delete

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections-Payment Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

2.35.2.BC-Payment-Del-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Contract-Details-IO*
  - *FCCREF*
  - *XREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract interest payment delete

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	Includes Bills and Collections-Payment Deletion-IO details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.35.3.BC-Payment-Del-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details*
    - *FCCREF*
    - *XREF*
    - *ESN*
    - *SUBSYSTEMSTAT*
    - *BDUEAMT*
    - *CONTCCY*
    - *CUSTNAME*
    - *Contract-Liq-Summary*
      - *FCCREF*
      - *CESN*
      - *TESN*
      - *VALDATE*
      - *TOTPAID*
      - *PMTREMARKS*
      - *Contract-Liq*
        - *FCCREF*
        - *ESN*
        - *COMP*

AMTDUE
COMPCCY
PREPAYINT
STTLMENT
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract interest payment delete

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections-Payment Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BDUEAMT

Attribute	**Description**	
Name	BDUEAMT	
Datatype	Number	
Description	Indicates Outstanding Balance	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**	
Name	RCVR_CORRESP3	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP4

Attribute	**Description**	
Name	RCVR_CORRESP4	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>8</td></tr><tr><td>totalDigits</td><td>13</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.4.BC-Payment-Del-Res-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *FCCREF*
      - *XREF*
    - *Contract-Details*
      - *FCCREF*
      - *XREF*
      - *ESN*
      - *SUBSYSTEMSTAT*
      - *BDUEAMT*
      - *CONTCCY*
      - *CUSTNAME*
      - *Contract-Liq-Summary*
        - *FCCREF*
        - *CESN*
        - *TESN*
        - *VALDATE*
        - *TOTPAID*
        - *PMTREMARKS*

- *Contract-Liq*
  - *FCCREF*
  - *ESN*
  - *COMP*
  - *AMTDUE*
  - *COMPCCY*
  - *PREPAYINT*

STTLMENT

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*

INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1

ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Mis-Change-Log
BRN
REFNO
MIS
TXNDT
OLDMIS
NEWMIS
Mis-Amend
CONTREF
RTYPE
RCODE
SPD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd gives the message format for detailing the Full information relating the BC Contract interest payment delete

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	Includes Bills and Collections-Payment Deletion-Primary key details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details

Attribute	Description
Name	Contract-Details
Datatype	
Description	Includes Bills and Collections-Payment Deletion details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDUEAMT

Attribute	Description
Name	BDUEAMT
Datatype	Number
Description	Indicates Outstanding Balance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Contract-Liq-Summary

Attribute	Description
Name	Contract-Liq-Summary
Datatype	
Description	Includes Contract Liquidation Summary details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CESN

Attribute	Description
Name	CESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TESN

Attribute	Description
Name	TESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date

Description	Indicates Value Date

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PMTREMARKS

Attribute	Description
Name	PMTREMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Contract-Liq

Attribute	Description
Name	Contract-Liq
Datatype	
Description	Includes Contract Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	Indicates Amount Due
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Currency
Restrictions	**Restrictions** / **Description** pattern / [A-Z]{3}

TOP

PREPAYINT

Attribute	Description
Name	PREPAYINT
Datatype	Number
Description	Indicates Amount Prepaid
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

STTLMENT

Attribute	Description
Name	STTLMENT
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Mis-Change-Log

Attribute	Description
Name	Mis-Change-Log
Datatype	
Description	Includes MIS-Change log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFNO

Attribute	Description

Name	REFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MIS

Attribute	Description
Name	MIS
Datatype	Date
Description	Indicates MIS Class
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMIS

Attribute	Description
Name	OLDMIS
Datatype	String
Description	Indicates Old MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NEWMIS

Attribute	Description
Name	NEWMIS
Datatype	String
Description	Indicates New MIS
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Mis-Amend

Attribute	Description
Name	Mis-Amend
Datatype	
Description	Includes MIS-Amend details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RTYPE

Attribute	Description
Name	RTYPE
Datatype	String
Description	Indicates Rate Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RCODE

Attribute	Description
Name	RCODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPD

Attribute	Description
Name	SPD
Datatype	Number
Description	Indicates Spread
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.CreateBCGoods

Input of Bills and Collections Commodity Code

2.36.1.BC-CreateBCGoods-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Goods-Master-Full

Attribute	Description

Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Input details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.36.2.BC-CreateBCGoods-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-IO*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Input-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.36.3.BC-CreateBCGoods-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE
Goods-Master-Full
GOODSCODE
LANGUAGECODE
GOODSDESC
BANNEDCOMMODITY
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Input-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Identification who authorised the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Input details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.4.BC-CreateBCGoods-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-PK*
      - *GOODSCODE*
      - *LANGUAGECODE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Goods-Master-Full
GOODSCODE
LANGUAGECODE
GOODSDESC
BANNEDCOMMODITY
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-PK

Attribute	Description
Name	Goods-Master-PK
Datatype	
Description	Includes Bills and Collections-Commodity Code Input-Primary key details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description**
	minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Input-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC

Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Input details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	**Description**	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description	Indicates Goods Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

BANNEDCOMMODITY

Attribute	**Description**	
Name	BANNEDCOMMODITY	
Datatype	String	
Description	Indicates Banned Commodity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User Identification who inputted the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.37.CreateBCPayment

Create BC Payment

2.37.1.BC-CreateBCPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	Description

Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.37.2.BC-CreateBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*
    - *VALDT*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *ESN*
    - *Payment-Breakup*
      - *CCY*
      - *AMT_DUE*
      - *AMOUNT_PREPAID*
      - *COMP*
      - *DUE_DT*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *CUSTSPREAD*

SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2

ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*

ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE

MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8

FUNDMIS9

MISGRPFUN

Txnmisdetails

Compmisdetails

Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description

Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 255

TOP

TOTAMTDUE

Attribute	Description

Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	Description	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.37.3.BC-CreateBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*

Payment-Breakup
- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*

SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRPART

Attribute	Description	
Name	SNDRRCVRPART	
Datatype	Number	
Description	Indicates Sender Receiver Participant	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.37.4.BC-CreateBCPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
      - *VALDT*
      - *REKYTTLPAID*
      - *PAYMENT_REMARKS*
      - *TOTAMTDUE*
      - *Auth-Details*
        - *ESN*
      - *Payment-Breakup*
        - *CCY*
        - *AMT_DUE*
        - *AMOUNT_PREPAID*
        - *COMP*
        - *DUE_DT*
      - *Settlements*
        - *CONREFNO*

LATEVNSEQNO

Contract-Settlement

- *CUSTSPREAD*
- *SPREADDEFN*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*
- *SNDTRRCVINFO3*
- *SNDTRRCVINFO4*
- *SNDTRRCVINFO5*
- *COVREQRD*
- *RECVCVR*
- *RECEIVER*
- *REIMINST1*
- *REIMINST4*
- *RCVRCORRS1*
- *RCVRCORRS2*
- *RCVRCORRS3*
- *RCVRCORRS4*
- *INTERMEDIARY1*
- *INTERMEDIARY2*
- *INTERMEDIARY3*

INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*

INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Misdetails
CONREFNO
LATESN

MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5

FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Auth-Details

Attribute	Description
Name	Auth-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description

Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.CreateCollectRegistration

Create Collection Registration

2.38.1.BC-CreateCollectRegistration-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*

TENOR
VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
- *PRTYLANG*
- *PRTYCOUNTRY*
- *PRTYREF*
- *PRTYNAME*
- *PRTYADD1*
- *PRTYADD2*
- *PRTYADD3*
- *PRTYADD4*
- *PRTYID*
- *PRTYTYPE*
- *ESN*
- *BCREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTPRTYTYPE

Attribute	Description	
Name	CUSTPRTYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ORGDOCRECV

Attribute	Description	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	Description	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description	Indicates the Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description	Indicates Internal Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BASEDATE

Attribute	**Description**	
Name	BASEDATE	
Datatype	Date	
Description	Indicates Base Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTEDESC

Attribute	**Description**
Name	BASEDTEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MATURITYDATE

Attribute	Description	
Name	MATURITYDATE	
Datatype	Date	
Description	Indicates the Maturity Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	Description	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.38.2.BC-CreateCollectRegistration-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *PRDCD*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*
    - *TENOR*
    - *VALDATE*
    - *INTREMRKS*
    - *BASEDATE*

BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
- *PRTYLANG*
- *PRTYCOUNTRY*
- *PRTYREF*
- *PRTYNAME*
- *PRTYADD1*
- *PRTYADD2*
- *PRTYADD3*
- *PRTYADD4*
- *PRTYID*
- *PRTYTYPE*
- *ESN*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

USEREFNO

Attribute	Description

Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ORGDOCRECV

Attribute	**Description**	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	**Description**	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAGE

Attribute	**Description**	
Name	STAGE	
Datatype	String	
Description	Indicates Stage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTMP

Attribute	Description
Name	MAKERDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description	
Name	PRTYLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYCOUNTRY

Attribute	Description	
Name	PRTYCOUNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYREF

Attribute	Description	
Name	PRTYREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.38.3.BC-CreateCollectRegistration-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*
    - *TENOR*
    - *VALDATE*
    - *INTREMRKS*

BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
BCREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRDCD

Attribute	Description
Name	PRDCD

Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTPRTYTYPE

Attribute	**Description**	
Name	CUSTPRTYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ORGDOCRECV

Attribute	**Description**	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	**Description**	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE

Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTMP

Attribute	Description
Name	MAKERDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD3

Attribute	Description

Name	PRTYADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.4.BC-CreateCollectRegistration-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *PRDCD*
      - *USEREFNO*
      - *COLLREF*
      - *THEIRLCREF*
      - *CUSTID*
      - *CUSTPRTYTYPE*
      - *ORGDOCRECV*
      - *DUPDOCRECV*
      - *COVLETDATE*
      - *STAGE*
      - *BILLCCY*
      - *BILLAMT*
      - *TXNDATE*
      - *TENOR*

VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF

Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	**Description**	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAGE

Attribute	**Description**	
Name	STAGE	
Datatype	String	
Description	Indicates Stage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILLCCY

Attribute	**Description**	
Name	BILLCCY	
Datatype	String	
Description	Indicates Bill Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	**Description**	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTMP

Attribute	**Description**	
Name	CHECKERDTSTMP	
Datatype	String	
Description	Indicates User id who has authorized the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CNAME

Attribute	**Description**	
Name	CNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description	
Name	PRTYCOUNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRTYREF

Attribute	Description	
Name	PRTYREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRTYADD1

Attribute	Description	
Name	PRTYADD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.CreateContract

Create BC Contract

2.39.1.BC-CreateContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

ADVFTRECPART
MANGENFLG
Acc-Excep
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

- *PRD*
- *CCY*
- *TENOR*
- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	**Description**	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	**Description**	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOCAL_CURRR

Attribute	**Description**	
Name	LOCAL_CURRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_LIAB_AMOUNT

Attribute	**Description**	
Name	LC_LIAB_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description	
Name	MATDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR_DAYS

Attribute	Description	
Name	TENOR_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	Description	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDT

Attribute	Description	
Name	BASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TFR_COLL_AMT

Attribute	**Description**	
Name	TFR_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUT_COLL_AMT

Attribute	**Description**	
Name	OUT_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED, CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTTRACDT

Attribute	Description	
Name	NEXTTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NUMTRSENT

Attribute	Description	
Name	NUMTRSENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NONACCPAYMSGDT

Attribute	Description	
Name	NONACCPAYMSGDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROTFLG

Attribute	Description	
Name	PROTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	Description	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	Description	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TFRATE

Attribute	**Description**	
Name	TFRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Loanacc

Attribute	**Description**	
Name	Loanacc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Loanaccdet

Attribute	**Description**
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.39.2.BC-CreateContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CURRENCY*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*
    - *VALDT*
    - *MATDT*

TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
COLLCCY
COLLAMT
COLLDESC
CHKNUM
FORFAITREQDT
FORFAITDOCDT
PROVAMT

INTREMRKS
PURAMT
UNLNKFXRATE
TXNSTAT
AUTHSTAT
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*

- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details

- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*

- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref

- *BASEDTDESC*

- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *MARGIND*
- *MARG*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *INSCOMPCOD*
- *INSPOLNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

Pack-Credit-Dtls

- *CLACCNO*

Deferred-Chg-Comp-Details

- *LCREFNO*
- *COMPONENT*
- *AMT_TRANSFERRED*
- *COMP_CCY*
- *AMT_PAID*

Bctbs-Int-Chg-Calc

- *STDTA*
- *INTRATEA*
- *INTBASISA*
- *WAIVEA*
- *INTRATEB*
- *INTBASISB*
- *WAIVEB*
- *INTRATEC*

INTBASISC
WAIVEC
CONTREFNOD
INTCHGCOMPD
STDTD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
INTCHGCOMPE
STDTE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
INTCHGCOMPF
STDTF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE

- *LIQDTNAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *WAIVER*
  - *Tax-Details*
    - *Rule-Details*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Collateral-details

- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*
  - *EXRATE*
  - *COLLTDESC*
  - *ADJSTSIGN*
  - *ADJSTAMT*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*

- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*

INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4

BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
MEDIUM
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
SPTAMTTAG
SPTACBRN
SPTACCCY
SPRACNO
SPTPRTYID
LOANACC
NEGORATE
NEGO_REF_NO

- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *PRD*
  - *CCY*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *LOANAMT*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*
  - *LOANVALDATE*
  - *Bcprefdet*
    - *UDEID*
    - *INTBASIS*
    - *SPLAMT*
    - *INTRT*
    - *UDEDESC*
- *Effective-Int-Rate*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Effective-Intrate-Det*
    - *EFFECTDT*
    - *IRR*
- *Intrest*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Intrest-Details*
    - *INTBASIS*
    - *RATE*
    - *RATECD*
    - *ACRDAMT*
    - *WAIVER*
    - *ACRREQRD*
    - *RTYP*

RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
NOUNIT
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
COMPONENT
EVNT
Intrest-View
INTBASIS
ACQUIRDAMT
WAIVER
ACCREQUIRD
RTTYP
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
RATCD
DISACCRAPP
VALDT
TRDT
Bcfx
BILLREFNO
ESN
Bcfx-Details
TFAMT
TFRATE
CCY
Loanacc
CONREFNO
LATEVNSEQNO
Loanaccdet
Extsys-Ws-Master
KEYID
Extsys-Ws-Details
USERREMARKS
Brok-Master
CONREFNO
LATEVNSEQNO
BROKPERCENT
BROKAMT

Brok-Detail

BRKACC

BRKACCCCY

BRKPERCENT

EXRATE

REMARKS

BRKAMTCONCCY

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

AMTQ_UT

AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	**Description**	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	**Description**	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	**Description**	
Name	THEIR_LCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	**Description**	
Name	MATDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR_DAYS

Attribute	**Description**	
Name	TENOR_DAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSITDAYS

Attribute	**Description**	
Name	TRANSITDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDT

Attribute	**Description**	
Name	BASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COLLCCY

Attribute	Description	
Name	COLLCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLAMT

Attribute	Description	
Name	COLLAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

SOURCE

Attribute	**Description**	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	**Description**	
Name	CHGCLAIM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDCOLLAT

Attribute	**Description**	
Name	LIQDCOLLAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	**Description**	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKPAIDBYUS

Attribute	Description
Name	BROKPAIDBYUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**	
Name	REC_INT_RTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REBATE_AMT

Attribute	**Description**	
Name	REBATE_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FURTHER_IDENTIFICATION

Attribute	**Description**	
Name	FURTHER_IDENTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description
Name	PARTNAM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTID

Attribute	**Description**	
Name	PARTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CUST_NO

Attribute	Description

Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description	
Name	Document-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Doc-Clause

Attribute	**Description**	
Name	Doc-Clause	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECD

Attribute	**Description**	
Name	CLAUSECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSEDESC

Attribute	**Description**	
Name	CLAUSEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6500</td></tr></table>

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

Shipment

Attribute	Description
Name	Shipment

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Pay-Fate

Attribute	**Description**	
Name	Pay-Fate	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	**Description**	
Name	ADVFTREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

ADVFTMED

Attribute	**Description**	
Name	ADVFTMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADVFTRECPART

Attribute	**Description**	
Name	ADVFTRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIND

Attribute	Description

Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT_TRANSFERRED

Attribute	Description

Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRATEA

Attribute	Description

Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STDTF

Attribute	Description
Name	STDTF

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISF

Attribute	Description
Name	INTBASISF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEF

Attribute	Description
Name	WAIVEF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHGAMTF

Attribute	Description
Name	CHGAMTF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSF

Attribute	Description
Name	STATUSF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String

Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description

Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Collateral

Attribute	Description	
Name	Collateral	
Datatype		
Description	Includes Collateral details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLTCCY

Attribute	Description	
Name	COLLTCCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description

Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description

Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description

Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Intrate-Det

Attribute	Description

Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,L,M</td></tr></table>

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,D,I,R</td></tr></table>

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	**Description**	
Name	DISCACCAPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DENOMITORBASIS

Attribute	**Description**	
Name	DENOMITORBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,I

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQUIRDAMT

Attribute	Description

Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M,

TOP

RATECALCTYP

Attribute	Description	
Name	RATECALCTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISACCRAPP

Attribute	Description	
Name	DISACCRAPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

Extsys-Ws-Details

Attribute	**Description**	
Name	Extsys-Ws-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

USERREMARKS

Attribute	**Description**	
Name	USERREMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brok-Master

Attribute	**Description**	
Name	Brok-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Lic-Master

Attribute	**Description**	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

License-Utils-Detail

Attribute	**Description**	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	**Description**
Name	IMPLICNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description

Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.39.3.BC-CreateContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- REPRES4
- RCVRACC

Adice

- ADV_CODE
- SUPRESS
- PRIORITY
- PRTY
- MEDIUM
- PRTYID
- PRTYNAME
- Fft
  - FFT_CODE
  - FFTTXT
- Ins
  - INSCD
  - INSTXT

Split-Master

- CONREFNO
- Split-Master
  - BASISAMTTAG
  - BASISAMTCCY
  - BASISAMT
  - Split-Detail
    - SPTSEQNO
    - SPTAMTTAG
    - SPTAMT
    - SPTACBRN
    - SPTACCCY
    - SPRACNO
    - SPTEXCHRT
    - SPTPRTYID
    - SPTPERCENTAGE
    - LOANACC
    - NEGORATE
    - NEGO_REF_NO

Bcpref

- CONREFNO
- LATEVNSEQNO
- BCREFNO
- ESN
- CNTRPARTY
- PRD
- CCY
- TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- *CCY*
- *Loanacc*
  - *CONREFNO*
  - *Loanaccdet*
    - *ACCNO*
    - *AMTFIN*
    - *CCY*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*
    - *GOODSCD*
    - *QTYUTIL*
    - *AMTUTIL*
    - *QTYREIN*
    - *AMTREIN*
    - *REMARKS*
    - *UNIT_OF_MEASUREMENT*
    - *LICENSE_AMOUNT*
    - *GOODSDESC*
    - *AMTQ_UT*
    - *AMTQ_RE*

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description	
Name	CONTRACT_DERIVED_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR_FIELD1

Attribute	Description	
Name	CHAR_FIELD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CNFRMD

Attribute	Description	
Name	CNFRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

CONF_AMT

Attribute	Description	
Name	CONF_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,F,C,P</td></tr></table>

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr></table>

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.4.BC-CreateContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *EXTREFNO*
      - *USEREFNO*
      - *PRODCD*
      - *CURRENCY*
      - *OPERATION*
      - *STAG*
      - *LCISSUEDATE*
      - *LC_CUST*
      - *LCREFNO*
      - *THEIR_LCREF*
      - *COLLREF*
      - *THECHGCCY*
      - *THECHGAMT*
      - *LIQAMT*

AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
COLLCCY
COLLAMT
COLLDESC
CHKNUM

FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PURAMT
UNLNKFXRATE
TXNSTAT
AUTHSTAT
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *CUST_NO*
- *LINKAGETYP*

- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details

- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *TRACRECPART*

- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*

- *UNDRESFLG*
- *Roll-Pref*
  - *BASEDTDESC*
  - *TRNSDAYS*
  - *MATDAYS*
  - *INTLIQDMOD*
  - *FRMCALCDT*
  - *TOCALCDT*
- *Drafts*
  - *AMTNAM*
  - *AMT*
- *Invoice-Master*
  - *MARGIND*
  - *MARG*
  - *Invoice-Details*
    - *INVCNO*
    - *INVCDT*
    - *AMT*
- *Insurance-Master*
  - *INSCOMPCOD*
  - *INSPOLNO*
- *Iccf-Calc-Dates*
  - *COMP*
  - *INTFRMDT*
  - *INTTODT*
- *Account-Master*
  - *ACCNO*
  - *AMTFIN*
  - *CCY*
- *Pack-Credit*
- *Pack-Credit-Dtls*
  - *CLACCNO*
- *Deferred-Chg-Comp-Details*
  - *LCREFNO*
  - *COMPONENT*
  - *AMT_TRANSFERRED*
  - *COMP_CCY*
  - *AMT_PAID*
- *Bctbs-Int-Chg-Calc*
  - *STDTA*
  - *INTRATEA*
  - *INTBASISA*
  - *WAIVEA*
  - *INTRATEB*

INTBASISB
WAIVEB
INTRATEC
INTBASISC
WAIVEC
CONTREFNOD
INTCHGCOMPD
STDTD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
INTCHGCOMPE
STDTE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
INTCHGCOMPF
STDTF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT

- *DISCOUNTAMT*
- *REBATAMT*
- *EXCRATE*
- *LIQDTNAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *WAIVER*
  - *Tax-Details*
    - *Rule-Details*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Collateral-details

- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*
  - *EXRATE*
  - *COLLTDESC*

ADJSTSIGN
ADJSTAMT
Linkages
CONREFNO
LATEVNSEQNO
Linkage-Details
LINKEDAMT
LINKEDTOREF
LINKAGETYP
Ui-Fields
ACCOUNT
DEPOSIT
UNCOVAMT
Misdetails
CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN

- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*

PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
MEDIUM
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
SPTAMTTAG
SPTACBRN
SPTACCCY
SPRACNO
SPTPRTYID

- *LOANACC*
- *NEGORATE*
- *NEGO_REF_NO*

Bcpref

- *CONREFNO*
- *LATEVNSEQNO*
- *BCREFNO*
- *PRD*
- *CCY*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *LOANAMT*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *Bcprefdet*
  - *UDEID*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *LATEVNSEQNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *LATEVNSEQNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*
  - *ACRDAMT*

WAIVER
ACRREQRD
RTYP
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
NOUNIT
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
COMPONENT
EVNT
Intrest-View
INTBASIS
ACQUIRDAMT
WAIVER
ACCREQUIRD
RTTYP
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
RATCD
DISACCRAPP
VALDT
TRDT
Bcfx
BILLREFNO
ESN
Bcfx-Details
TFAMT
TFRATE
CCY
Loanacc
CONREFNO
LATEVNSEQNO
Loanaccdet
Extsys-Ws-Master
KEYID
Extsys-Ws-Details
USERREMARKS
Brok-Master
CONREFNO

LATEVNSEQNO
BROKPERCENT
BROKAMT
Brok-Detail
BRKACC
BRKACCCCY
BRKPERCENT
EXRATE
REMARKS
BRKAMTCONCCY
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
AMTQ_UT
AMTQ_RE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODCD

Attribute	Description
Name	PRODCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	**Description**	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	**Description**	
Name	THEIR_LCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COLLREF

Attribute	**Description**	
Name	COLLREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THECHGCCY

Attribute	Description	
Name	THECHGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

THECHGAMT

Attribute	Description	
Name	THECHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQAMT

Attribute	Description	
Name	LIQAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	Description	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHG_REFUSED

Attribute	Description
Name	CHG_REFUSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description
Name	PASS_INT_TO_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description	
Name	CHGCLAIM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDCOLLAT

Attribute	Description	
Name	LIQDCOLLAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	Description	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	Description
Name	BROKPAIDBYUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**	
Name	REC_INT_RTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REBATE_AMT

Attribute	**Description**	
Name	REBATE_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FURTHER_IDENTIFICATION

Attribute	**Description**	
Name	FURTHER_IDENTIFICATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD1

Attribute	Description
Name	PARTADD1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	**Description**	
Name	ADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGETYP

Attribute	Description

Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVFTREQDFLG

Attribute	**Description**	
Name	ADVFTREQDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N,R

TOP

ADVFTMED

Attribute	**Description**	
Name	ADVFTMED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADVFTRECPART

Attribute	**Description**	
Name	ADVFTRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MANGENFLG

Attribute	**Description**	
Name	MANGENFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOCALCDT

Attribute	Description
Name	TOCALCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Drafts

Attribute	Description
Name	Drafts

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deferred-Chg-Comp-Details

Attribute	Description
Name	Deferred-Chg-Comp-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description

Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISA

Attribute	Description

Name	INTBASISA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTD

Attribute	Description	
Name	CHGAMTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSD

Attribute	Description	
Name	STATUSD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREFNOE

Attribute	Description	
Name	CONTREFNOE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INTCHGCOMPE

Attribute	Description	
Name	INTCHGCOMPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGPERF

Attribute	Description
Name	CHGPERF

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISF

Attribute	Description
Name	INTBASISF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVEF

Attribute	Description
Name	WAIVEF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHGAMTF

Attribute	Description
Name	CHGAMTF
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSF

Attribute	Description
Name	STATUSF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLAMNT

Attribute	**Description**	
Name	BILLAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNTAMT

Attribute	**Description**	
Name	DISCOUNTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REBATAMT

Attribute	**Description**	
Name	REBATAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXCRATE

Attribute	**Description**	
Name	EXCRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDTNAMT

Attribute	**Description**	
Name	LIQDTNAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Rule-Details

Attribute	**Description**	
Name	Rule-Details	
Datatype		
Description	Includes Rule details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLTAMT

Attribute	**Description**	
Name	COLLTAMT	
Datatype	Number	
Description	Indicates Collateral Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLTDESC

Attribute	**Description**	
Name	COLLTDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ADJSTSIGN

Attribute	**Description**	
Name	ADJSTSIGN	
Datatype	Number	
Description	Indicates Adjustment Type Increase : 1 Decrease : -1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADJSTAMT

Attribute	**Description**
Name	ADJSTAMT
Datatype	Number

Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT

Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Settlement

Attribute	Description

Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2

Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3

Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5

Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B

TOP

MAXRATVAR

Attribute	**Description**	
Name	MAXRATVAR	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINRTVAR

Attribute	**Description**	
Name	MINRTVAR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PMNTMD

Attribute	**Description**	
Name	PMNTMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRACCBRN

Attribute	**Description**	
Name	DRACCBRN	
Datatype	String	
Description	Indicates Debit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,M,B,S</td></tr></table>

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRREQRD

Attribute	**Description**	
Name	ACRREQRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RTYP

Attribute	**Description**	
Name	RTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

RESTTENOR

Attribute	**Description**	
Name	RESTTENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,L,M</td></tr></table>

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,D,I,R</td></tr></table>

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,D,M,Y</td></tr></table>

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M,

TOP

RATECALCTYP

Attribute	Description	
Name	RATECALCTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISACCRAPP

Attribute	Description	
Name	DISACCRAPP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VALDT

Attribute	Description	
Name	VALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

License-Utils-Detail

Attribute	**Description**	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	**Description**	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

GOODSCD

Attribute	**Description**

Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description

Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.CreateDocArrival

Create BC Document Arrival

2.40.1.BC-CreateDocArrival-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

2.40.2.BC-CreateDocArrival-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*
      - *COVLETREF*
      - *COVLETDATE*
      - *FRSTMAILORG*
      - *SECMAILORG*
      - *DOCTYPE*

Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
MEDIUM
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

LATSHIPDT

Attribute	**Description**	
Name	LATSHIPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SHIPDT

Attribute	**Description**	
Name	SHIPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ARRVDT

Attribute	**Description**	
Name	ARRVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**
Name	GOODSCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADV_CODE

Attribute	**Description**	
Name	ADV_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	**Description**	
Name	SUPRESS	
Datatype	String	
Description	Indicates Supress Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDIUM

Attribute	**Description**	
Name	MEDIUM	
Datatype	String	
Description	Indicates Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	**Description**
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

2.40.3.BC-CreateDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*

COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description

Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.4.BC-CreateDocArrival-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *BRNCD*
      - *Doc-Details*
        - *DOCODE*
        - *DOCDESC*
        - *DOCSLNO*
        - *FRSTMAILCOP*
        - *SECMAILCOP*
        - *REIM_BANK*
        - *DOCREF*
        - *DOCDATE*
        - *COVLETREF*
        - *COVLETDATE*

FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
MEDIUM
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,A

TOP

BRNCD

Attribute	**Description**	
Name	BRNCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Details

Attribute	**Description**	
Name	Doc-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DOCODE

Attribute	**Description**	
Name	DOCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DOCDESC

Attribute	**Description**	
Name	DOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Doc-Clauses

Attribute	**Description**	
Name	Doc-Clauses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE

Attribute	**Description**	
Name	CLAUSECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSEDESC

Attribute	**Description**	
Name	CLAUSEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DESTO

Attribute	**Description**	
Name	DESTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CARNAM

Attribute	**Description**	
Name	CARNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SHIPMENT_DETAILS

Attribute	**Description**	
Name	SHIPMENT_DETAILS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

LATSHIPDT

Attribute	**Description**	
Name	LATSHIPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	**Description**	
Name	PARTIALSHPMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Adice

Attribute	**Description**	
Name	Adice	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADV_CODE

Attribute	**Description**	
Name	ADV_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.CreateDocs

Input of Bills and Collections Document Code

2.41.1.BC-CreateDocs-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*

CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

2.41.2.BC-CreateDocs-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-IO*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*
      - *CLAUSECODE*
      - *LANGCODEDET*
      - *DOCCODE*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Document Master IO details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type.I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

2.41.3.BC-CreateDocs-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*
      - *CLAUSECODE*
      - *LANGCODEDET*
      - *DOCCODE*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC

Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Docs-Clauses

Attribute	Description	
Name	Docs-Clauses	
Datatype		
Description	Includes the Documents Clauses.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE

Attribute	Description	
Name	CLAUSECODE	
Datatype	String	
Description	Indicates the Clause Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

LANGCODEDET

Attribute	Description

Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.4.BC-CreateDocs-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-PK*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *DOCTYPE*
      - *VALIDATESHIPGUA*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

- Docs-Clauses
  - CLAUSECODE
  - LANGCODEDET
  - DOCCODE
- UDFDETAILS
  - FUNCTIONID
  - FIELD_NAME
  - DATATYPE
  - FIELD_VALUE
  - VAL_TYPE
- Docs-Master-Full
  - DOCCODE
  - LANGCODE
  - DOCSHORTDESC
  - DOCLONGDESC
  - DOCTYPE
  - VALIDATESHIPGUA
  - MAKERID
  - MAKERDTSTAMP
  - CHECKERID
  - CHECKERDTSTAMP
  - MODNO
  - AUTHSTAT
  - RECSTAT
  - ONCEAUTH
  - Docs-Clauses
    - CLAUSECODE
    - LANGCODEDET
    - DOCCODE
  - UDFDETAILS
    - FUNCTIONID
    - FIELD_NAME
    - DATATYPE
    - FIELD_VALUE
    - VAL_TYPE
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP
  - WARNING
    - WCODE
    - WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-PK

Attribute	Description
Name	Docs-Master-PK
Datatype	
Description	Includes the Documents Master Primary key details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DOCSHORTDESC

Attribute	Description	
Name	DOCSHORTDESC	
Datatype	String	
Description	Indicates the Document short description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCLONGDESC

Attribute	Description	
Name	DOCLONGDESC	
Datatype	String	
Description	Indicates the Document Long Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DOCTYPE

Attribute	Description	
Name	DOCTYPE	
Datatype	String	
Description	Indicates the Document Type.I - Insurance, O - Others, T - Transport, V - Invoice	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type.I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,O,T,V</td></tr></table>

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Docs-Clauses

Attribute	**Description**	
Name	Docs-Clauses	
Datatype		
Description	Includes the Documents Clauses.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.CreateProduct

Input of Bills and Collections Product

2.42.1.BC-CreateProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*

DTC
PTC
DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N

BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N

- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*

- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
- Role-To-Head-Mapping
  - CLASCD
  - CLASDESC
  - Mapping-Details
    - ACCTRL
    - ROLDESC
    - ACCTHD
    - GLDESC
- Product-Events
  - CLASCD
  - CLASDESC
  - Event-Details
    - EVNTCD
    - EVENTDESC
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
      - RATE_TYPE_INDICATOR
    - Advices
      - MSGTYP
      - DESC
      - GENTIME
      - SUPRS
      - PRIOR
      - CHGREQD
- Branch-Ccy-Restrictions
  - CCYLST

- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*

- *AMNDAFTRASSOC*
- *ALWAMTAMND*
- *AMNDAFTRAPPL*
- *STPASOCIATN*
- *ADVCHG*
- *CAPTLIZE*
- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Discount-Accrual

- *CLASCD*
- *CLASDESC*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *CCYNAME*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*

STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Creation details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT

Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP

Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TC

Attribute	**Description**	
Name	TC	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,U

TOP

ATF

Attribute	**Description**	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	**Description**	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	**Description**	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N

Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N

Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	**Description**	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description

Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description

Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRANSITDAYS_N

Attribute	**Description**	
Name	TRANSITDAYS_N	
Datatype	Number	
Description	Indicates Transit Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INCOTERM_N

Attribute	**Description**	
Name	INCOTERM_N	
Datatype	String	
Description	Indicates INCO Term	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

LTL

Attribute	**Description**	
Name	LTL	
Datatype	String	
Description	Indicates whether Export Bill should be Linked to a Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPCOLTYPE

Attribute	**Description**	
Name	ACPCOLTYPE	
Datatype	String	
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	Indicates Transfer Collateral from LC Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description

Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String

Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCEXCSTARTDAY_I

Attribute	**Description**	
Name	ACCEXCSTARTDAY_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCFREQ_I

Attribute	**Description**	
Name	ACCEXCFREQ_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Generation Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCMEDIUM_I

Attribute	**Description**	
Name	ACCEXCMEDIUM_I	
Datatype	String	
Description	Indicates Acceptance Exception Tracer Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYEXSTARTDAY_T

Attribute	**Description**	
Name	PAYEXSTARTDAY_T	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYEXCFREQ_T

Attribute	**Description**
Name	PAYEXCFREQ_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String

Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	

Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Indicates Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AMNTTAG

Attribute	**Description**	
Name	AMNTTAG	
Datatype	String	
Description	Indicates the Tax Component of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description

Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Product Events	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description

Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Cust Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Customer Category Desription	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String

Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	Description	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences

Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	Description	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	Description	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	Description	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	Description	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.42.2.BC-CreateProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *OP*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *DOC*
    - *ULOC*
    - *TC*

ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
LTL

ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
Charge-Their-Details
- *COMPONENT*
- *EVNTCODE*

Instructions-Details
- *INSCD_N*
- *INSCDDESC_N*
- *ADVCD_N*
- *INSSLNO*

Fft-Details
- *FFTTXTCD*
- *ADVCD_I*
- *FFTSLNO*

Document-Details
- *DOCODE_N*
- *DOCDESR*
- *DOCSLNO*
- *Clause-Details*
  - *CLAUSECODE_N*
  - *CLAUSEDESCR_N*
  - *CLAUSESLNO*

Tracer-Details
- *RESEXTARCERFLAG_N*
- *RESEXNUMTARCERS_N*
- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*

- CHGEXCFREQ_G
- CHGEXMEDIUM
- TEMPLATEID

Status-Details

- AUTOFRWD_N
- AUTOREVERSE_N
- COMPLETEACCRUALS_N
- REVERSEACCRUALS_N
- STATUS
- STPACCRUALS_N
- TRANSACTIONCD
- Status-Advices-Details
  - MESSAGECD
- Status-Control-Details
  - CMPNENT_N
  - TRANSFERDAYS_N
- Status-Gl-Details
  - ACCNTROLE
  - ACCROLEDESC_N
  - UPWARDTRANSFERFRMGL_N
  - UPWARDTRANSFERFRMGLDESC
  - UPWARDTRANSFERTOGL_N
  - UPWARDTRANSFERTOGLDESC_N
  - DWNWRDTRANSFERFRMGL_N
  - DWNWRDTRANSFERFRMGLDESC_N
  - DWNWRDTRANSFERTOGL_N
  - DWNWRDTRANSFERTOGLDESC

Tax-Scheme

- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP

Role-To-Head-Mapping

- CLASCD
- Mapping-Details
  - ACCTRL
  - ACCTHD
  - STAT

Product-Events

- CLASCD
- Event-Details
  - EVNTCD

Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
GENTIME
SUPRS
PRIOR
CHGREQD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Fields
Field-Details
FLDNUM

- *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
- *Customers*
  - *CSTID*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *DISCACCRAPLB*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*

Product-Discount-Accrual

- *CLASCD*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*

RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
RUL
COLTYP
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Creation-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP

Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF

Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String

Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE

Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N
Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description
Name	REKYMATURTYDATE_N
Datatype	String
Description	Indicates whether Maturity Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N

Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N
Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description
Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE
Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	**Description**	
Name	CHGCLAIM	
Datatype	String	
Description	Indicates whether Charge Claim is Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBROK

Attribute	**Description**	
Name	ALLWBROK	
Datatype	String	
Description	Indicates whether Brokerage is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COLLTOTRF

Attribute	**Description**	
Name	COLLTOTRF	
Datatype	String	
Description	Indicates whether Collection to Transfer is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	**Description**	
Name	LIQ_USING_COLLATERAL	
Datatype	String	
Description	Indicates Liquidate Using Collateral Flag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I

Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details

Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description

Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Status-Control-Details

Attribute	Description
Name	Status-Control-Details
Datatype	
Description	Includes Status Control details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNENT_N

Attribute	Description
Name	CMPNENT_N
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRANSFERDAYS_N

Attribute	Description
Name	TRANSFERDAYS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE

Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	**Description**	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates the Event of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	**Description**	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Role-To-Head-Mapping

Attribute	**Description**
Name	Role-To-Head-Mapping
Datatype	
Description	Role To head Mapping

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	**Description**	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	**Description**	
Name	Accounting-Entries	
Datatype		
Description	Accounting Entry Details for Events	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCRLCD

Attribute	**Description**	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD

Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description

Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	**Description**	
Name	MISTYP	
Datatype	String	
Description	Indicates MIS type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number

Description	Indicates Field Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLSDFLT

Attribute	Description	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description	
Name	Disc-Accr-Details	
Datatype		
Description	Includes Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCACCRREQD

Attribute	Description	
Name	DISCACCRREQD	
Datatype	String	
Description	Indicates Discount Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interests
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP

Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.42.3.BC-CreateProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *DOC*

ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N

TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N
  ACCEXCTRACERFLAG_I
  ACCEXCNUMTRACERS_N
  PAYEXTARCERFLAG_T

- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*

- AMNTTAG
- BASISAMNTTAG
- COMPTATIONEVNT
- TYP

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Branch-Ccy-Restrictions

- CCYLST
- BRNLST
- CLASCD
- CLASDESC

- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND

LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Creation details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indciates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OP

Attribute	**Description**	
Name	OP	
Datatype	String	
Description	Indicates Operation Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF
Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REKEYREQFLAG_N

Attribute	**Description**	
Name	REKEYREQFLAG_N	
Datatype	String	
Description	Indicates whether Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYAMNTFLAG_N

Attribute	**Description**	
Name	REKEYAMNTFLAG_N	
Datatype	String	
Description	Indicates Amount Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	**Description**	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	**Description**	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description
Name	REKYMATURTYDATE_N
Datatype	String
Description	Indicates whether Maturity Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N

Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description
Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE

Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	**Description**	
Name	TRANSFERCOLLATFROMLC	
Datatype	String	
Description	Indicates Transfer Collateral from LC Flag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description

Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXMEDIUM_N

Attribute	**Description**	
Name	RESEXMEDIUM_N	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCEXCSTARTDAY_I

Attribute	**Description**	
Name	ACCEXCSTARTDAY_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCFREQ_I

Attribute	**Description**	
Name	ACCEXCFREQ_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Generation Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCMEDIUM_I

Attribute	**Description**	
Name	ACCEXCMEDIUM_I	
Datatype	String	
Description	Indicates Acceptance Exception Tracer Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYEXSTARTDAY_T

Attribute	**Description**
Name	PAYEXSTARTDAY_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM

Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description

Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String

Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates the Tax Component of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	**Description**	
Name	COMPTATIONEVNT	
Datatype	String	
Description	Indicates the Event of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	**Description**	
Name	TYP	
Datatype	String	
Description	Indicates Tax Type WITHHOLDING : W Expense : E	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Role To Head Mapping	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String

Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Cust Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	**Description**	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	**Description**	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String

Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description

Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String

Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPMTMETD

Attribute	**Description**	
Name	PREPMTMETD	
Datatype	String	
Description	Indicates Pre Payment Method Flexcube : F Custom : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,C

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	Description	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	Description	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	Description	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	Description	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.4.BC-CreateProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *OP*
      - *PRDTYP*
      - *RC*
      - *ATA*
      - *ATD*
      - *CTP*
      - *DTC*
      - *PTC*

DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N

FORFAITINTCOMP_N
TRANSITDAYS_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N
  ACCEXCTRACERFLAG_I
  ACCEXCNUMTRACERS_N
  PAYEXTARCERFLAG_T
  PAYEXNUMTRACERS_T
  CHGEXTRACERFLAG_G
  CHGEXNUMTRACERS_G
  RESEXSTARTDAY
  RESEXCFREQ_N
  RESEXMEDIUM_N
  ACCEXCSTARTDAY_I
  ACCEXCFREQ_I
  ACCEXCMEDIUM_I
  PAYEXSTARTDAY_T

- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *Status-Control-Details*
  - *CMPNENT_N*
  - *TRANSFERDAYS_N*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *Tax-Details*
  - *RUL*
  - *AMNTTAG*
  - *BASISAMNTTAG*
  - *COMPTATIONEVNT*
  - *TYP*

Role-To-Head-Mapping

- *CLASCD*
- *Mapping-Details*
  - *ACCTRL*
  - *ACCTHD*
  - *STAT*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *Branch-List*
    - *BRNDISALOW*
  - *Ccy-List*
    - *BGTDLCCY*
    - *SOLDCCY*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISTYP*
    - *MISCLS*
    - *MISCD*
    - *KYID*

- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
  - *Customers*
    - *CSTID*
    - *ALWD*
- *Product-Charges*
  - *Charge-Details*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *DISCACCRAPLB*
    - *DISCNTBASIS*
    - *DFTRULE*
    - *COMPNT*
- *Product-Discount-Accrual*
  - *CLASCD*
  - *CLSDFLT*
  - *Disc-Accr-Details*
    - *DISCACCRREQD*
    - *ACCRFREQ*
    - *PREPAYTBDTREAT*
    - *ACQTYP*
  - *Ccy-Preferences*
    - *CCYCODE*
    - *DENOMDCNTMET*
    - *DENOMMETHOD*
- *Product-Interest*
  - *Interest-Components*
    - *BASISAMNTTYP*
    - *BASISAMNTCATG*
    - *RATCDUSGE*
    - *RATTYP*

RATCD
SETTLMNTCCY
STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
RUL
COLTYP
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Includes Bills and Collections- Product Creation-Primary key details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Creation-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String

Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP
Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	C,D

TOP

ULOC

Attribute	Description	
Name	ULOC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TC

Attribute	Description	
Name	TC	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,U

TOP

ATF

Attribute	Description	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	Description	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

GOODSARRFLAG_N

Attribute	**Description**	
Name	GOODSARRFLAG_N	
Datatype	String	
Description	Indicates whether Past Due Status should be based on Goods Arrival Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

GOODSARRPDODAYS_N

Attribute	**Description**	
Name	GOODSARRPDODAYS_N	
Datatype	Number	
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTNR

Attribute	**Description**	
Name	MINTNR	
Datatype	Number	
Description	Indicates Minimum Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	**Description**	
Name	MAXTNR	
Datatype	Number	
Description	Indicates Maximum Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STNDRDTNR_N

Attribute	**Description**

Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N
Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	**Description**	
Name	REKYVALDATE_N	
Datatype	String	
Description	Indicates whether Value Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	Description	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description	
Name	ACCRUALSTRTMONTH_N	
Datatype	String	
Description	Indicates Accrual Start Month	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description	
Name	ALLWPREPAY_N	
Datatype	String	
Description	Indicates whether Prepayment is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description	
Name	ADVANCEBYLOAN_N	
Datatype	String	
Description	Indicates whether Advance by Loan is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BRIDGEGL_N

Attribute	Description

Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description
Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description

Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	**Description**	
Name	FORFAITINTCOMP_N	
Datatype	String	
Description	Indicates Forfaiting Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRANSITDAYS_N

Attribute	**Description**	
Name	TRANSITDAYS_N	
Datatype	Number	
Description	Indicates Transit Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LTL

Attribute	**Description**	
Name	LTL	
Datatype	String	
Description	Indicates whether Export Bill should be Linked to a Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPCOLTYPE

Attribute	**Description**	
Name	ACPCOLTYPE	
Datatype	String	
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String

Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCSLNO

Attribute	**Description**	
Name	DOCSLNO	
Datatype	Number	
Description	Indicates Document Serial Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Clause-Details

Attribute	**Description**	
Name	Clause-Details	
Datatype		
Description	Includes Clause details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE_N

Attribute	**Description**	
Name	CLAUSECODE_N	
Datatype	String	
Description	Indicates Clause Code	
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSEDESCR_N

Attribute	**Description**	
Name	CLAUSEDESCR_N	
Datatype	String	
Description	Indicates Clause Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

CLAUSESLNO

Attribute	**Description**

Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXSTARTDAY

Attribute	**Description**	
Name	RESEXSTARTDAY	
Datatype	Number	
Description	Indicates Reserve Exception Start Tracers After Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXCFREQ_N

Attribute	**Description**	
Name	RESEXCFREQ_N	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXMEDIUM_N

Attribute	**Description**	
Name	RESEXMEDIUM_N	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCEXCSTARTDAY_I

Attribute	**Description**	
Name	ACCEXCSTARTDAY_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCFREQ_I

Attribute	**Description**
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Status-Control-Details

Attribute	Description
Name	Status-Control-Details
Datatype	
Description	Includes Status Control details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNENT_N

Attribute	Description
Name	CMPNENT_N
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRANSFERDAYS_N

Attribute	Description
Name	TRANSFERDAYS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates Tax Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	Description

Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	Description	
Name	MISTYP	
Datatype	String	
Description	Indicates MIS type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Discount-Accrual

Attribute	**Description**	
Name	Product-Discount-Accrual	
Datatype		
Description	Includes Product Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLSDFLT

Attribute	Description	
Name	CLSDFLT	
Datatype	String	
Description	Indicates Class Default	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Disc-Accr-Details

Attribute	Description	
Name	Disc-Accr-Details	
Datatype		
Description	Includes Discount Accrual details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCACCRREQD

Attribute	Description	
Name	DISCACCRREQD	
Datatype	String	
Description	Indicates Discount Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interests
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP

Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SETTLMNTCCY

Attribute	Description	
Name	SETTLMNTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

STPAPPLICTION

Attribute	Description	
Name	STPAPPLICTION	
Datatype	String	
Description	Indicates Stop Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RESETTENOR

Attribute	Description	
Name	RESETTENOR	
Datatype	Number	
Description	Indicates Reset Tenor	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String
Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description

Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description

Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DENOMBASIS

Attribute	Description
Name	DENOMBASIS
Datatype	String
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I

TOP

BAS366

Attribute	Description
Name	BAS366
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

NOOFINTPRD

Attribute	Description
Name	NOOFINTPRD
Datatype	Number
Description	Indicates No. of Interest Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRPMTRT

Attribute	Description
Name	PRPMTRT
Datatype	Number
Description	Indicates Pre Payment Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.43.DeleteAmendConfirm

Delete BC Amendment Confirmation

2.43.1.BC-DeleteAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT

Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description

Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,L,M</td></tr></table>

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,D,I,R</td></tr></table>

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTCALC

Attribute	**Description**	
Name	AMTCALC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description	Includes the Charges Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.43.2.BC-DeleteAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.43.3.BC-DeleteAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*

EVENTDESC

Amendadv

- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD

ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT

MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**

Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.4.BC-DeleteAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-PK*
      - *CONREFNO*
    - *Amendmaster-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-PK

Attribute	Description
Name	Amendmaster-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.44.DeleteBCDisc

Deletion of Bills and Collectons Descrepancy Code

2.44.1.BC-DeleteBCDisc-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Disc-Master-Full

Attribute	Description

Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.44.2.BC-DeleteBCDisc-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Disc-Master-IO*
  - *DISCCODE*
  - *LANGUAGECODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.44.3.BC-DeleteBCDisc-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.4.BC-DeleteBCDisc-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
    - *Disc-Master-PK*
      - *DISCCODE*
      - *LANGUAGECODE*
    - *Disc-Master-Full*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Disc-Master-PK

Attribute	Description
Name	Disc-Master-PK

Datatype	
Description	Includes the Discrepancy Master Primary Key details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE

Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description

Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.45.DeleteBCGoods

Deletion of Bills and Collections Commodity Code

2.45.1.BC-DeleteBCGoods-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Goods-Master-Full

Attribute	Description

Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion details

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description	Indicates Goods Code	
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates Language Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description	Indicates Goods Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

BANNEDCOMMODITY

Attribute	Description	
Name	BANNEDCOMMODITY	
Datatype	String	
Description	Indicates Banned Commodity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.45.2.BC-DeleteBCGoods-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Goods-Master-IO*
  - *GOODSCODE*
  - *LANGUAGECODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.45.3.BC-DeleteBCGoods-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.4.BC-DeleteBCGoods-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
    - *Goods-Master-PK*
      - *GOODSCODE*
      - *LANGUAGECODE*
    - *Goods-Master-Full*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Goods-Master-PK

Attribute	Description

Name	Goods-Master-PK
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion-Primary key details

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description	Indicates Goods Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections Commodity Code Deletion details

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description	Indicates Goods Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description

Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Identification who authorised the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.DeleteBCPayment

Delete BC Payment

2.46.1.BC-DeleteBCPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	Description

Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TOTPAYMNT

Attribute	Description	
Name	TOTPAYMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRPAYMNT

Attribute	Description	
Name	CURRPAYMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTAMTDUE

Attribute	Description	
Name	TOTAMTDUE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Auth-Details

Attribute	Description	
Name	Auth-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.46.2.BC-DeleteBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.46.3.BC-DeleteBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*

Payment-Breakup
- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*

SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	**Description**	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	**Description**	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	**Description**	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	**Description**	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.46.4.BC-DeleteBCPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.47.DeleteCollectRegistration

Delete Collection Registration

2.47.1.BC-DeleteCollectRegistration-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*

TENOR
VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
- *PRTYLANG*
- *PRTYCOUNTRY*
- *PRTYREF*
- *PRTYNAME*
- *PRTYADD1*
- *PRTYADD2*
- *PRTYADD3*
- *PRTYADD4*
- *PRTYID*
- *PRTYTYPE*
- *ESN*
- *BCREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTPRTYTYPE

Attribute	Description	
Name	CUSTPRTYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ORGDOCRECV

Attribute	Description	
Name	ORGDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DUPDOCRECV

Attribute	Description	
Name	DUPDOCRECV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description	Indicates the Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description	Indicates Internal Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BASEDATE

Attribute	**Description**	
Name	BASEDATE	
Datatype	Date	
Description	Indicates Base Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTEDESC

Attribute	**Description**
Name	BASEDTEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description	Indicates the Maturity Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	**Description**	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.47.2.BC-DeleteCollectRegistration-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.47.3.BC-DeleteCollectRegistration-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*
    - *TENOR*
    - *VALDATE*
    - *INTREMRKS*

BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
BCREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD

Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE

Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTMP

Attribute	Description
Name	MAKERDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD3

Attribute	Description

Name	PRTYADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.4.BC-DeleteCollectRegistration-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.48.DeleteContract

Delete BC Contract

2.48.1.BC-DeleteContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

- *ADVFTRECPART*
- *MANGENFLG*

Acc-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

- *Roll-Pref*
  - *BASEDT*
  - *BASEDTDESC*
  - *TNRDAYS*
  - *TRNSDAYS*
  - *MATDAYS*
  - *INTLIQDMOD*
  - *FRMCALCDT*
  - *TOCALCDT*
  - *BASEDTCOD*
- *Drafts*
  - *AMTNAM*
  - *AMT*
- *Invoice-Master*
  - *INVCCY*
  - *MARGIND*
  - *MARG*
  - *ELGAMT*
  - *MARGAMT*
  - *Invoice-Details*
    - *INVCNO*
    - *INVCDT*
    - *AMT*
- *Insurance-Master*
  - *CONTREFNNO*
  - *INSCOMPCOD*
  - *INSPOLNO*
  - *INSCOMPNAM*
  - *ADDRLN1*
  - *ADDRLN2*
  - *ADDRLN3*
  - *ADDRLN4*
  - *TELENO*
  - *FAXNO*
- *Iccf-Calc-Dates*
  - *COMP*
  - *INTFRMDT*
  - *INTTODT*
- *Account-Master*
  - *ACCNO*
  - *AMTFIN*
  - *CCY*
- *Pack-Credit*
  - *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

PRD
CCY
TENOR
UNITS
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
BRIDGL
CYSTALTYP
COLLLIQDAMT
LIQDLCCHGCOMM
MATDT
LOANAMT
BILLOS
CONTRACT_CURRENCY
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
ORGEXCHRATE
Bcprefdet
UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Effective-Int-Rate
CONREFNO
Effective-Intrate-Det
EFFECTDT
IRR
Intrest
CONREFNO
Intrest-Details

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_LIAB_AMOUNT

Attribute	Description
Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED, CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASISAMTTAG

Attribute	**Description**	
Name	BASISAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMTCCY

Attribute	**Description**	
Name	BASISAMTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BASISAMT

Attribute	**Description**	
Name	BASISAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Split-Detail

Attribute	**Description**	
Name	Split-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRREQRD

Attribute	**Description**	
Name	ACRREQRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACQRCCY

Attribute	**Description**	
Name	ACQRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTYP

Attribute	**Description**	
Name	RTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENATYTYP

Attribute	**Description**	
Name	PENATYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.48.2.BC-DeleteContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.48.3.BC-DeleteContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- REPRES4
- RCVRACC

Adice

- ADV_CODE
- SUPRESS
- PRIORITY
- PRTY
- MEDIUM
- PRTYID
- PRTYNAME
- Fft
  - FFT_CODE
  - FFTTXT
- Ins
  - INSCD
  - INSTXT

Split-Master

- CONREFNO
- Split-Master
  - BASISAMTTAG
  - BASISAMTCCY
  - BASISAMT
  - Split-Detail
    - SPTSEQNO
    - SPTAMTTAG
    - SPTAMT
    - SPTACBRN
    - SPTACCCY
    - SPRACNO
    - SPTEXCHRT
    - SPTPRTYID
    - SPTPERCENTAGE
    - LOANACC
    - NEGORATE
    - NEGO_REF_NO

Bcpref

- CONREFNO
- LATEVNSEQNO
- BCREFNO
- ESN
- CNTRPARTY
- PRD
- CCY
- TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SETTLEAMT

Attribute	Description
Name	SETTLEAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWBRK

Attribute	Description
Name	ALLWBRK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKPAIDBYUS

Attribute	Description
Name	BROKPAIDBYUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPTOADVFLG

Attribute	Description
Name	ACPTOADVFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description	
Name	CONTRACT_DERIVED_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR_FIELD1

Attribute	Description	
Name	CHAR_FIELD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CNFRMD

Attribute	Description	
Name	CNFRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

CONF_AMT

Attribute	Description	
Name	CONF_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,F,C,P</td></tr></table>

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

JVPARENT

Attribute	**Description**	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	**Description**	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	**Description**	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	**Description**	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTRATEB

Attribute	Description	
Name	INTRATEB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISB

Attribute	Description	
Name	INTBASISB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description	
Name	WAIVEB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INTAMOUNTB

Attribute	Description	
Name	INTAMOUNTB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.4.BC-DeleteContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.49.DeleteDocArrival

Delete BC Document Arrival

2.49.1.BC-DeleteDocArrival-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECMAILCOP

Attribute	**Description**	
Name	SECMAILCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIM_BANK

Attribute	**Description**	
Name	REIM_BANK	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

2.49.2.BC-DeleteDocArrival-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.49.3.BC-DeleteDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*

COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

BRNCD

Attribute	Description

Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description	
Name	ARRVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	Description	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description	Indicates Priority High : 1 Normal : 2 Low : 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRTY

Attribute	Description	
Name	PRTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MEDIUM

Attribute	Description	
Name	MEDIUM	
Datatype	String	
Description	Indicates Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description	Indicates Party Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.4.BC-DeleteDocArrival-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.50.DeleteDocs

Deletion of Bills and Collections Document Code

2.50.1.BC-DeleteDocs-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*

CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.50.2.BC-DeleteDocs-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Docs-Master-IO*
  - *DOCCODE*
  - *LANGCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.50.3.BC-DeleteDocs-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*
      - *CLAUSECODE*
      - *LANGCODEDET*
      - *DOCCODE*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC

Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Docs-Clauses

Attribute	Description	
Name	Docs-Clauses	
Datatype		
Description	Includes the Documents Clauses.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CLAUSECODE

Attribute	Description	
Name	CLAUSECODE	
Datatype	String	
Description	Indicates the Clause Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

LANGCODEDET

Attribute	Description

Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.4.BC-DeleteDocs-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-PK*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-Full*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *DOCTYPE*
      - *VALIDATESHIPGUA*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*

AUTHSTAT
RECSTAT
ONCEAUTH
Docs-Clauses
CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Docs-Master-PK

Attribute	Description
Name	Docs-Master-PK
Datatype	
Description	Includes the Documents Master Primary key Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	**Description**	
Name	LANGCODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DOCSHORTDESC

Attribute	**Description**	
Name	DOCSHORTDESC	
Datatype	String	
Description	Indicates the Document short description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCLONGDESC

Attribute	**Description**	
Name	DOCLONGDESC	
Datatype	String	
Description	Indicates the Document Long Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.DeleteFfts

Deletion of Bills and Collections Free Format Code

2.51.1.BC-DeleteFfts-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Fft-Master-Full

Attribute	Description

Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

2.51.2.BC-DeleteFfts-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Fft-Master-IO*
  - *FFTCODE*
  - *LANGCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.51.3.BC-DeleteFfts-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.4.BC-DeleteFfts-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-PK*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-Full*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Fft-Master-PK

Attribute	Description
Name	Fft-Master-PK

Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion-Primary key details

TOP

FFTCODE

Attribute	Description	
Name	FFTCODE	
Datatype	String	
Description	Indicates Text Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Deletion details

TOP

FFTCODE

Attribute	Description	
Name	FFTCODE	
Datatype	String	
Description	Indicates Text Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE

Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.AuthBCDisc

Authorization of Bills and Collections Discrepancy Code

2.52.1.BC-AuthBCDisc-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Disc-Master-Full

Attribute	Description

Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.52.2.BC-AuthBCDisc-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Disc-Master-IO*
  - *DISCCODE*
  - *LANGUAGECODE*
  - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.52.3.BC-AuthBCDisc-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *MODNO*
    - *Disc-Master-Full*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full details.

TOP

DISCCODE

Attribute	Description	
Name	DISCCODE	
Datatype	String	
Description	Indicates the Discrepancy Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DISCDESC

Attribute	Description	
Name	DISCDESC	
Datatype	String	
Description	Indicates the Discrepancy description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.4.BC-AuthBCDisc-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-PK*
      - *DISCCODE*
      - *LANGUAGECODE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *MODNO*
    - *Disc-Master-Full*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-PK

Attribute	Description
Name	Disc-Master-PK
Datatype	
Description	Includes the Discrepancy Master Primary key details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Disc-Master-IO

Attribute	Description

Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full details.

TOP

DISCCODE

Attribute	Description

Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.AuthBCGoods

Authorization of Bills and Collections Commodity Code

2.53.1.BC-AuthBCGoods-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-Full*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *GOODSDESC*
    - *BANNEDCOMMODITY*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Goods-Master-Full

Attribute	Description

Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.53.2.BC-AuthBCGoods-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Goods-Master-IO*
    - *GOODSCODE*
    - *LANGUAGECODE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.53.3.BC-AuthBCGoods-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *MODNO*
    - *Goods-Master-Full*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization-IO details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.4.BC-AuthBCGoods-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Goods-Master-PK*
      - *GOODSCODE*
      - *LANGUAGECODE*
    - *Goods-Master-IO*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *MODNO*
    - *Goods-Master-Full*
      - *GOODSCODE*
      - *LANGUAGECODE*
      - *GOODSDESC*
      - *BANNEDCOMMODITY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Goods-Master-PK

Attribute	Description
Name	Goods-Master-PK
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization-Primary key details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Goods-Master-IO

Attribute	Description
Name	Goods-Master-IO
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization-IO details

TOP

GOODSCODE

Attribute	Description	
Name	GOODSCODE	
Datatype	String	
Description	Indicates Goods Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGUAGECODE

Attribute	Description	
Name	LANGUAGECODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Goods-Master-Full

Attribute	Description
Name	Goods-Master-Full
Datatype	
Description	Includes Bills and Collections-Commodity Code Authorization details

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	Indicates Goods Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	Indicates Goods Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

BANNEDCOMMODITY

Attribute	Description
Name	BANNEDCOMMODITY
Datatype	String
Description	Indicates Banned Commodity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.54.AuthDocs

Authorization of Bills and Collections Document Code

2.54.1.BC-AuthDocs-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Docs-Master-Full*
    - *DOCCODE*
    - *LANGCODE*
    - *DOCSHORTDESC*
    - *DOCLONGDESC*
    - *DOCTYPE*
    - *VALIDATESHIPGUA*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Docs-Clauses*

CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

2.54.2.BC-AuthDocs-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Docs-Master-IO*
  - *DOCCODE*
  - *LANGCODE*
  - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

2.54.3.BC-AuthDocs-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
      - *MODNO*
    - *Docs-Master-Full*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *DOCTYPE*
      - *VALIDATESHIPGUA*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH
Docs-Clauses
CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Documents Master IO Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Documents Master Full Details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC

Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String
Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.54.4.BC-AuthDocs-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Docs-Master-PK*
      - *DOCCODE*
      - *LANGCODE*
    - *Docs-Master-IO*
      - *DOCCODE*
      - *LANGCODE*
      - *MODNO*
    - *Docs-Master-Full*
      - *DOCCODE*
      - *LANGCODE*
      - *DOCSHORTDESC*
      - *DOCLONGDESC*
      - *DOCTYPE*
      - *VALIDATESHIPGUA*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*

MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Docs-Clauses
CLAUSECODE
LANGCODEDET
DOCCODE
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Docs-Master-PK

Attribute	Description
Name	Docs-Master-PK
Datatype	
Description	Includes the Document Master Primay Key details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Docs-Master-IO

Attribute	Description
Name	Docs-Master-IO
Datatype	
Description	Includes the Document Master IO details.

TOP

DOCCODE

Attribute	**Description**	
Name	DOCCODE	
Datatype	String	
Description	Indicates the Document Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	**Description**	
Name	LANGCODE	
Datatype	String	
Description	Indicates the Language Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Docs-Master-Full

Attribute	Description
Name	Docs-Master-Full
Datatype	
Description	Includes the Document Master Full details.

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DOCSHORTDESC

Attribute	Description
Name	DOCSHORTDESC
Datatype	String
Description	Indicates the Document short description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCLONGDESC

Attribute	Description
Name	DOCLONGDESC
Datatype	String
Description	Indicates the Document Long Description.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates the Document Type. I - Insurance, O - Others, T - Transport, V - Invoice
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,T,V

TOP

VALIDATESHIPGUA

Attribute	Description
Name	VALIDATESHIPGUA
Datatype	String
Description	Indicates the Validate Ship Guarantee.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Docs-Clauses

Attribute	Description
Name	Docs-Clauses
Datatype	
Description	Includes the Documents Clauses.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	Indicates the Clause Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGCODEDET

Attribute	Description
Name	LANGCODEDET
Datatype	String

Description	Indicates the Language Code Details.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DOCCODE

Attribute	Description
Name	DOCCODE
Datatype	String
Description	Indicates the Document Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.AuthFfts

Authorization of Bills and Collections Free Format Code

2.55.1.BC-AuthFfts-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-Full*
    - *FFTCODE*
    - *LANGCODE*
    - *FREEFORMATTEXT*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Fft-Master-Full

Attribute	Description

Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

2.55.2.BC-AuthFfts-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Fft-Master-IO*
    - *FFTCODE*
    - *LANGCODE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.55.3.BC-AuthFfts-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
      - *MODNO*
    - *Fft-Master-Full*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	

Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.4.BC-AuthFfts-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Fft-Master-PK*
      - *FFTCODE*
      - *LANGCODE*
    - *Fft-Master-IO*
      - *FFTCODE*
      - *LANGCODE*
      - *MODNO*
    - *Fft-Master-Full*
      - *FFTCODE*
      - *LANGCODE*
      - *FREEFORMATTEXT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Fft-Master-PK

Attribute	Description
Name	Fft-Master-PK
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization-Primary key details

TOP

FFTCODE

Attribute	Description	
Name	FFTCODE	
Datatype	String	
Description	Indicates Text Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LANGCODE

Attribute	Description	
Name	LANGCODE	
Datatype	String	
Description	Indicates Language Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Fft-Master-IO

Attribute	Description
Name	Fft-Master-IO
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization-IO details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Fft-Master-Full

Attribute	Description
Name	Fft-Master-Full
Datatype	
Description	Includes Bills and Collections-Free Format Code Authorization details

TOP

FFTCODE

Attribute	Description
Name	FFTCODE
Datatype	String
Description	Indicates Text Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGCODE

Attribute	Description
Name	LANGCODE
Datatype	String
Description	Indicates Language Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FREEFORMATTEXT

Attribute	Description
Name	FREEFORMATTEXT
Datatype	String
Description	Indicates Free Format Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.AuthorizeAmendConfirm

Authorize BC Amendment Confirmation

2.56.1.BC-AuthorizeAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT

Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	Attribute: minOccurs; Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization status
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,U,A

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description

Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.56.2.BC-AuthorizeAmendConfirm-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Amendmaster-IO*
  - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.56.3.BC-AuthorizeAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*

EVENTDESC

Amendadv

- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD

ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT

MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**

Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	Description	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	Description	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	Description	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPERIOD

Attribute	**Description**	
Name	NOINTPERIOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN

Attribute	**Description**
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-PK*
      - *CONREFNO*
    - *Amendmaster-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-PK

Attribute	Description
Name	Amendmaster-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.57.AuthorizeBCPayment

Authorize BC Payment

2.57.1.BC-AuthorizeBCPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

- *ESN*
- *TXNSTAT*
- *AUTHSTAT*

Payment-Breakup

- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*

SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*

RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3

COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9

TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	Description

Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TOTPAYMNT

Attribute	Description	
Name	TOTPAYMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRPAYMNT

Attribute	Description	
Name	CURRPAYMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTAMTDUE

Attribute	Description	
Name	TOTAMTDUE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Auth-Details

Attribute	Description	
Name	Auth-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.57.2.BC-AuthorizeBCPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.57.3.BC-AuthorizeBCPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONREFNO*
    - *VALDT*
    - *CONTCCY*
    - *REKYTTLPAID*
    - *PAYMENT_REMARKS*
    - *BILLDUEAMT*
    - *CNAME*
    - *TOTPAYMNT*
    - *CURRPAYMNT*
    - *TOTAMTDUE*
    - *Auth-Details*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*

Payment-Breakup
- *CCY*
- *AMT_DUE*
- *AMOUNT_PREPAID*
- *COMP*
- *DUE_DT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*

SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REKYTTLPAID

Attribute	Description
Name	REKYTTLPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMENT_REMARKS

Attribute	Description
Name	PAYMENT_REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

TOTPAYMNT

Attribute	Description
Name	TOTPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRPAYMNT

Attribute	Description
Name	CURRPAYMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTAMTDUE

Attribute	Description
Name	TOTAMTDUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Auth-Details

Attribute	Description
Name	Auth-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Payment-Breakup

Attribute	Description
Name	Payment-Breakup
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_DUE

Attribute	Description
Name	AMT_DUE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT_PREPAID

Attribute	Description
Name	AMOUNT_PREPAID
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DUE_DT

Attribute	Description
Name	DUE_DT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO

Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String

Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4

Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	

Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET

Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.57.4.BC-AuthorizeBCPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.58.AuthorizeBrnPrm

Authorization of Bills and Collections Branch Parameter

2.58.1.BC-AuthorizeBrnPrm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bcbranch-Parameters-Full*
    - *BRANCH*
    - *PRCSSTILLNWDFLG*
    - *USEUSERREFINMSGS*
    - *USEULTIPARENTREF*
    - *BTN_UDF*
    - *BRNNAME*
    - *ACQRLVL*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bcbranch-Parameters-Full

Attribute	Description

Name	Bcbranch-Parameters-Full
Datatype	
Description	Indicates the branch parameters

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRCSSTILLNWDFLG

Attribute	Description
Name	PRCSSTILLNWDFLG
Datatype	String
Description	Indicates the Process Till Next Working Day. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USEUSERREFINMSGS

Attribute	Description
Name	USEUSERREFINMSGS
Datatype	String
Description	Indicates the Use User Reference No In Messages. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

USEULTIPARENTREF

Attribute	Description
Name	USEULTIPARENTREF
Datatype	String
Description	Indicates the User Ultimate Parent User Refernce For Child Contracts. Y - Yes, N - No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates the User Defined Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates the Branch Name.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQRLVL

Attribute	Description
Name	ACQRLVL
Datatype	String
Description	Indicates the Accrual Level. P - Product, C - Contract.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,C

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker date stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction status. O-Open, C-Closed.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation status. A- Authorised, U - Unauthorised.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Once Auth or not.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.58.2.BC-AuthorizeBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bcbranch-Parameters-IO*
    - *BRANCH*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bcbranch-Parameters-IO

Attribute	Description
Name	Bcbranch-Parameters-IO
Datatype	
Description	Indicates IO BC branch parameters details in FCUBS Request.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

2.58.3.BC-AuthorizeBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bcbranch-Parameters-Full*
    - *BRANCH*
    - *PRCSSTILLNWDFLG*
    - *USEUSERREFINMSGS*
    - *USEULTIPARENTREF*
    - *BTN_UDF*
    - *BRNNAME*
    - *ACQRLVL*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bcbranch-Parameters-Full

Attribute	Description
Name	Bcbranch-Parameters-Full
Datatype	
Description	Contain

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

PRCSSTILLNWDFLG

Attribute	Description
Name	PRCSSTILLNWDFLG
Datatype	String
Description	Indicates the Process Till Next Working Day. Y - Yes, N - No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

USEUSERREFINMSGS

Attribute	Description
Name	USEUSERREFINMSGS
Datatype	String
Description	Indicates the Use User Reference No In Messages. Y - Yes, N - No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

USEULTIPARENTREF

Attribute	Description
Name	USEULTIPARENTREF
Datatype	String
Description	Indicates the User Ultimate Parent User Refernce For Child Contracts. Y - Yes, N - No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BTN_UDF

Attribute	**Description**	
Name	BTN_UDF	
Datatype	String	
Description	Indicates the User Defined Fields.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACQRLVL

Attribute	**Description**	
Name	ACQRLVL	
Datatype	String	
Description	Indicates the Accrual Level. P - Product, C - Contract.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,C

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	Indicates the Maker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP

Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker date stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction status. O-Open, C-Closed.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation status. A- Authorised, U - Unauthorised.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Once Auth or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	**Description**	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**

Name	FCUBS_ERROR_RESP
Datatype	
Description	Contain FCUBS Error List, if Any.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contain FCUBS Warning List, if Any.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.58.4.BC-AuthorizeBrnPrm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bcbranch-Parameters-PK*
      - *BRANCH*
    - *Bcbranch-Parameters-IO*
      - *BRANCH*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bcbranch-Parameters-PK

Attribute	Description
Name	Bcbranch-Parameters-PK
Datatype	
Description	Contains Primary Key Response of Authorize Branch Parameters

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

Bcbranch-Parameters-IO

Attribute	Description
Name	Bcbranch-Parameters-IO
Datatype	
Description	Contains Input Only Response of Authorize Branch Parameters

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.59.AuthorizeCollectRegistration

Authorize Collection Registration

2.59.1.BC-AuthorizeCollectRegistration-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*

TENOR
VALDATE
INTREMRKS
BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
- *PRTYLANG*
- *PRTYCOUNTRY*
- *PRTYREF*
- *PRTYNAME*
- *PRTYADD1*
- *PRTYADD2*
- *PRTYADD3*
- *PRTYADD4*
- *PRTYID*
- *PRTYTYPE*
- *ESN*
- *BCREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STAGE

Attribute	Description	
Name	STAGE	
Datatype	String	
Description	Indicates Stage	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILLCCY

Attribute	Description	
Name	BILLCCY	
Datatype	String	
Description	Indicates Bill Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILLAMT

Attribute	Description	
Name	BILLAMT	
Datatype	Number	
Description	Indicates Bill Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TENOR

Attribute	**Description**	
Name	TENOR	
Datatype	Number	
Description	Indicates the Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDATE

Attribute	**Description**	
Name	VALDATE	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description	Indicates Internal Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

BASEDATE

Attribute	**Description**	
Name	BASEDATE	
Datatype	Date	
Description	Indicates Base Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTEDESC

Attribute	**Description**
Name	BASEDTEDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

MATURITYDATE

Attribute	**Description**	
Name	MATURITYDATE	
Datatype	Date	
Description	Indicates the Maturity Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTMP

Attribute	**Description**	
Name	MAKERDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRTYADD3

Attribute	Description
Name	PRTYADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.59.2.BC-AuthorizeCollectRegistration-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.59.3.BC-AuthorizeCollectRegistration-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *PRDCD*
    - *OPERATION*
    - *USEREFNO*
    - *COLLREF*
    - *THEIRLCREF*
    - *CUSTID*
    - *CUSTPRTYTYPE*
    - *ORGDOCRECV*
    - *DUPDOCRECV*
    - *COVLETDATE*
    - *STAGE*
    - *BILLCCY*
    - *BILLAMT*
    - *TXNDATE*
    - *TENOR*
    - *VALDATE*
    - *INTREMRKS*

BASEDATE
BASEDTEDESC
MATURITYDATE
AUTHSTAT
MAKERID
MAKERDTSTMP
CHECKERID
CHECKERDTSTMP
CNAME
CUSTNO
TXNSTAT
Contract-Parties
PRTYLANG
PRTYCOUNTRY
PRTYREF
PRTYNAME
PRTYADD1
PRTYADD2
PRTYADD3
PRTYADD4
PRTYID
PRTYTYPE
ESN
BCREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD

Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	Indicates the User Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	Indicates Collection Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIRLCREF

Attribute	Description
Name	THEIRLCREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTPRTYTYPE

Attribute	Description
Name	CUSTPRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ORGDOCRECV

Attribute	Description
Name	ORGDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DUPDOCRECV

Attribute	Description
Name	DUPDOCRECV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STAGE

Attribute	Description
Name	STAGE
Datatype	String
Description	Indicates Stage
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE

Datatype	Date
Description	Indicates Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	Indicates Internal Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BASEDATE

Attribute	Description
Name	BASEDATE
Datatype	Date
Description	Indicates Base Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEDTEDESC

Attribute	Description
Name	BASEDTEDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MATURITYDATE

Attribute	Description
Name	MATURITYDATE
Datatype	Date
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTMP

Attribute	Description
Name	MAKERDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTMP

Attribute	Description
Name	CHECKERDTSTMP
Datatype	String
Description	Indicates User id who has authorized the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CNAME

Attribute	Description
Name	CNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	This specifies the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	Indicates Party Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTYLANG

Attribute	Description
Name	PRTYLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYCOUNTRY

Attribute	Description
Name	PRTYCOUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRTYREF

Attribute	Description
Name	PRTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD1

Attribute	Description
Name	PRTYADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD2

Attribute	Description
Name	PRTYADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD3

Attribute	Description

Name	PRTYADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYADD4

Attribute	Description
Name	PRTYADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PRTYTYPE

Attribute	Description
Name	PRTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.59.4.BC-AuthorizeCollectRegistration-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.60.AuthorizeContract

Authorize BC Contract

2.60.1.BC-AuthorizeContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
  PARTLANG
  PARTCTRCOD
  PARTREFNO
  PARTNAM
  PARTADD1
  PARTADD2
  PARTADD3
  PARTADD4
  PARTID
  PARTTYP
  Party-Addr
    MEDIA
    ADDR
Party-Limits
  PARTTYP
  OPERATION
  LIMITAMT
  CUST_NO
  LINKAGETYP
  LINKAGEPERC
  LINKEDREFNO
  JVPARENT
  LIABILITY_NUMBER
  AMOUNTTAG
  SLNO
Document-Details
  DOCCD
  DESC
  FRSTMAILCOP
  SECMAILCOP
  REIMBNKCOP
  DOCREF
  DOCDATE

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

ADVFTRECPART
MANGENFLG
Acc-Excep
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG

- *Roll-Pref*
  - *BASEDT*
  - *BASEDTDESC*
  - *TNRDAYS*
  - *TRNSDAYS*
  - *MATDAYS*
  - *INTLIQDMOD*
  - *FRMCALCDT*
  - *TOCALCDT*
  - *BASEDTCOD*
- *Drafts*
  - *AMTNAM*
  - *AMT*
- *Invoice-Master*
  - *INVCCY*
  - *MARGIND*
  - *MARG*
  - *ELGAMT*
  - *MARGAMT*
  - *Invoice-Details*
    - *INVCNO*
    - *INVCDT*
    - *AMT*
- *Insurance-Master*
  - *CONTREFNNO*
  - *INSCOMPCOD*
  - *INSPOLNO*
  - *INSCOMPNAM*
  - *ADDRLN1*
  - *ADDRLN2*
  - *ADDRLN3*
  - *ADDRLN4*
  - *TELENO*
  - *FAXNO*
- *Iccf-Calc-Dates*
  - *COMP*
  - *INTFRMDT*
  - *INTTODT*
- *Account-Master*
  - *ACCNO*
  - *AMTFIN*
  - *CCY*
- *Pack-Credit*
  - *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

- *PRD*
- *CCY*
- *TENOR*
- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMOUNT

Attribute	**Description**	
Name	AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCAMOUNT

Attribute	**Description**	
Name	LCAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOCAL_CURRR

Attribute	**Description**	
Name	LOCAL_CURRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUTSTAMT

Attribute	**Description**	
Name	OUTSTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_LIAB_AMOUNT

Attribute	**Description**	
Name	LC_LIAB_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED, CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASISAMTTAG

Attribute	**Description**	
Name	BASISAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMTCCY

Attribute	**Description**	
Name	BASISAMTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BASISAMT

Attribute	**Description**	
Name	BASISAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Split-Detail

Attribute	**Description**	
Name	Split-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.60.2.BC-AuthorizeContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.60.3.BC-AuthorizeContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NEXTTRACDT*
- *NUMTRSENT*
- *NONACCPAYMSGDT*
- *PROTFLG*
- *TRACRECPART*
- *DTOFPROT*
- *ACCMSGDT*
- *MANGENFLG*

Acc-Fate

- *MANGENFLG*
- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*
- *ADVFTRECPART*

Contract-Disc

- *DISCCD*
- *DISCDESC*
- *DISCRESLFLG*
- *DISCRESDT*
- *DISCRECDT*

Contract-Reserve

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACFREQ*
- *TRACSRTDT*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *RESRELDT*
- *DISCAPPDT*
- *TRACER_RECEIVER_TYP*
- *UNDRESFLG*

Roll-Pref

- *BASEDT*
- *BASEDTDESC*

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY
PRD
CCY
TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description	
Name	MARGAMTLIQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGDUEAMT

Attribute	Description	
Name	MARGDUEAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLCCY

Attribute	Description	
Name	COLLCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COLLAMT

Attribute	Description	
Name	COLLAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COLLDESC

Attribute	Description	
Name	COLLDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANAMT

Attribute	**Description**	
Name	LOANAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLOS

Attribute	**Description**	
Name	BILLOS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT_CURRENCY

Attribute	**Description**	
Name	CONTRACT_CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATECDPREF

Attribute	**Description**	
Name	RATECDPREF	
Datatype	String	
Description	Indicates Rate Code Prefernce	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B

TOP

MAXRATVAR

Attribute	**Description**
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.60.4.BC-AuthorizeContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.61.AuthorizeDocArrival

Authorize BC Document Arrival

2.61.1.BC-AuthorizeDocArrival-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECMAILCOP

Attribute	**Description**	
Name	SECMAILCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIM_BANK

Attribute	**Description**	
Name	REIM_BANK	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

2.61.2.BC-AuthorizeDocArrival-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.61.3.BC-AuthorizeDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*

COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

BRNCD

Attribute	Description

Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.61.4.BC-AuthorizeDocArrival-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.62.AuthorizeProduct

Authorization of Bills and Collections Product

2.62.1.BC-AuthorizeProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*

DTC
PTC
DOC
ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N

BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N
TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N

- *ACCEXCTRACERFLAG_I*
- *ACCEXCNUMTRACERS_N*
- *PAYEXTARCERFLAG_T*
- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*

- SCHEMEDESC
- Tax-Details
  - RUL
  - AMNTTAG
  - BASISAMNTTAG
  - COMPTATIONEVNT
  - TYP
- Role-To-Head-Mapping
  - CLASCD
  - CLASDESC
  - Mapping-Details
    - ACCTRL
    - ROLDESC
    - ACCTHD
    - GLDESC
- Product-Events
  - CLASCD
  - CLASDESC
  - Event-Details
    - EVNTCD
    - EVENTDESC
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
      - RATE_TYPE_INDICATOR
    - Advices
      - MSGTYP
      - DESC
      - GENTIME
      - SUPRS
      - PRIOR
      - CHGREQD
- Branch-Ccy-Restrictions
  - CCYLST

- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*

AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Discount-Accrual
CLASCD
CLASDESC
CLSDFLT
Disc-Accr-Details
DISCACCRREQD
ACCRFREQ
PREPAYTBDTREAT
ACQTYP
Ccy-Preferences
CCYCODE
CCYNAME
DENOMDCNTMET
DENOMMETHOD
Product-Interest
Interest-Components
BASISAMNTTYP
BASISAMNTCATG
RATCDUSGE
RATTYP
RATCD
SETTLMNTCCY

STPAPPLICTION
RESETTENOR
BRWLENDIND
LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
- *CCY*
- *DEFRAT*
- *MINRATE*
- *MAXRAT*
- *DFLTSPRD*
- *MINSPRD*
- *MAXSPRD*
- *INTBASIS*
- *DENOMBASIS*
- *BAS366*
- *NOOFINTPRD*
- *PRPMTRT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Authorization details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT

Datatype	Date
Description	Indciates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OP

Attribute	Description
Name	OP
Datatype	String
Description	Indicates Operation Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CTP

Attribute	Description
Name	CTP

Datatype	String
Description	Indicates whether Collection to Purchase is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTC

Attribute	Description
Name	DTC
Datatype	String
Description	Indicates whether Discount to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PTC

Attribute	Description
Name	PTC
Datatype	String
Description	Indicates whether Purchase to Collection is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOC

Attribute	Description
Name	DOC
Datatype	String
Description	Indicates whether Document Type. C - Clean and D - Documentary
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TC

Attribute	**Description**	
Name	TC	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,U

TOP

ATF

Attribute	**Description**	
Name	ATF	
Datatype	String	
Description	Indicates whether Acceptance to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTF

Attribute	**Description**	
Name	DTF	
Datatype	String	
Description	Indicates whether Discount to Forfaiting is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	**Description**	
Name	TARCKACCRDCOMPFLAG_N	
Datatype	String	
Description	Indicates whether Limit Tracking is Required on Accrued Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N

Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REKEYREQFLAG_N

Attribute	Description
Name	REKEYREQFLAG_N

Datatype	String
Description	Indicates whether Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYAMNTFLAG_N

Attribute	Description
Name	REKEYAMNTFLAG_N
Datatype	String
Description	Indicates Amount Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCYFLAG

Attribute	Description
Name	REKYCCYFLAG
Datatype	String
Description	Indicates Rekey Currency Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKEYCUSTFLAG_N

Attribute	Description
Name	REKEYCUSTFLAG_N
Datatype	String
Description	Indicates Customer Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATURTYDATE_N

Attribute	**Description**	
Name	REKYMATURTYDATE_N	
Datatype	String	
Description	Indicates whether Maturity Date Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYTTLPAID_N

Attribute	**Description**	
Name	REKYTTLPAID_N	
Datatype	String	
Description	Indicates whether Total Paid Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	**Description**	
Name	ACCRUALSTRTDAY_N	
Datatype	Number	
Description	Indicates Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRACEDAYS_N

Attribute	**Description**	
Name	GRACEDAYS_N	
Datatype	Number	
Description	Indicates Grace Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD_N

Attribute	Description

Name	LOANPRD_N
Datatype	String
Description	Indicates Loan Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DISCNTMETHOD

Attribute	Description
Name	DISCNTMETHOD
Datatype	String
Description	Indicates Discounting Method Discounted : D True Discounted : T
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,T,

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,M

TOP

FREECOLLFLAG_N

Attribute	Description
Name	FREECOLLFLAG_N
Datatype	String
Description	Indicates whether the Product is used for Free Collection
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description

Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRANSITDAYS_N

Attribute	**Description**	
Name	TRANSITDAYS_N	
Datatype	Number	
Description	Indicates Transit Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INCOTERM_N

Attribute	**Description**	
Name	INCOTERM_N	
Datatype	String	
Description	Indicates INCO Term	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

LTL

Attribute	**Description**	
Name	LTL	
Datatype	String	
Description	Indicates whether Export Bill should be Linked to a Loan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPCOLTYPE

Attribute	**Description**	
Name	ACPCOLTYPE	
Datatype	String	
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	Indicates Transfer Collateral from LC Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description

Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String

Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXMEDIUM_N

Attribute	Description
Name	RESEXMEDIUM_N
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCEXCSTARTDAY_I

Attribute	Description
Name	ACCEXCSTARTDAY_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCFREQ_I

Attribute	Description
Name	ACCEXCFREQ_I
Datatype	Number
Description	Indicates Acceptance Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCEXCMEDIUM_I

Attribute	Description
Name	ACCEXCMEDIUM_I
Datatype	String
Description	Indicates Acceptance Exception Tracer Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYEXSTARTDAY_T

Attribute	Description
Name	PAYEXSTARTDAY_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM
Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String

Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description
Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	

Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String
Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Tax-Details

Attribute	**Description**	
Name	Tax-Details	
Datatype		
Description	Indicates Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RUL

Attribute	**Description**	
Name	RUL	
Datatype	String	
Description	Indicates Tax Rule	
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

AMNTTAG

Attribute	**Description**	
Name	AMNTTAG	
Datatype	String	
Description	Indicates the Tax Component of Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description

Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description

Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Cust Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates Customer Category Desription	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String

Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String
Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRFREQ

Attribute	Description	
Name	ACCRFREQ	
Datatype	String	
Description	Indicates Accrual Frequency Daily : D Monthly : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,

TOP

PREPAYTBDTREAT

Attribute	Description	
Name	PREPAYTBDTREAT	
Datatype	String	
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,R,

TOP

ACQTYP

Attribute	Description	
Name	ACQTYP	
Datatype	String	
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences

Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description
Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPMTMETD

Attribute	Description
Name	PREPMTMETD
Datatype	String
Description	Indicates Pre Payment Method Flexcube : F Custom : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,C

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MARGNBASIS

Attribute	Description
Name	MARGNBASIS
Datatype	String
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,D,C

TOP

MARGNAPPLN

Attribute	Description
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	**Description**	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	**Description**	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.62.2.BC-AuthorizeProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Authorization-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.62.3.BC-AuthorizeProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYPDESC*
    - *OP*
    - *PRDGRPDESC*
    - *PRDTYP*
    - *RC*
    - *ATA*
    - *ATD*
    - *CTP*
    - *DTC*
    - *PTC*
    - *DOC*

ULOC
TC
ATF
DTF
TARCKACCRDCOMPFLAG_N
TARCKDISCBILLFLAG_N
LIMTSTENORCALCTYPE
AUTOACPTOADVFLAG_N
AUTOLIQFLAG_N
STATUSCNTRLCD_N
BASECRITYFLAG_N
XRATETYP_N
XRATEOVRDLIMIT_N
XRATESTPLIMIT
AR
ACPINTCOMP
ICCFCOLTYPE
GOODSARRFLAG_N
GOODSARRPDODAYS_N
MINTNR
MAXTNR
STNDRDTNR_N
REKEYREQFLAG_N
REKEYAMNTFLAG_N
REKYCCYFLAG
REKEYCUSTFLAG_N
REKYVALDATE_N
REKYMATURTYDATE_N
REKYTTLPAID_N
ACCRUALSTRTDAY_N
GRACEDAYS_N
ACCRUALSTRTMONTH_N
ALLWPREPAY_N
ADVANCEBYLOAN_N
BRIDGEGL_N
LOANPRD_N
DISCNTMETHOD
RTCODEPRFERD
FREECOLLFLAG_N
BILLNOTICEDAYS_N
BILLNOTICEREQDFLAG_N
BILLNOTICEFLAG
ACCRUALFREQ_N
FORFAITINTCOMP_N

TRANSITDAYS_N
INCOTERM_N
LTL
ACPCOLTYPE
CHGCLAIM
ALLWBROK
COLLTOTRF
LIQ_USING_COLLATERAL
TRANSFERCOLLATFROMLC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Charge-Their-Details
  COMPONENT
  EVNTCODE
Instructions-Details
  INSCD_N
  INSCDDESC_N
  ADVCD_N
  INSSLNO
Fft-Details
  FFTTXTCD
  FFTCDDESC
  ADVCD_I
  FFTSLNO
Document-Details
  DOCODE_N
  DOCTYPE
  DOCDESR
  DOCSLNO
  Clause-Details
    CLAUSECODE_N
    CLAUSEDESCR_N
    CLAUSESLNO
Tracer-Details
  RESEXTARCERFLAG_N
  RESEXNUMTARCERS_N
  ACCEXCTRACERFLAG_I
  ACCEXCNUMTRACERS_N
  PAYEXTARCERFLAG_T

- *PAYEXNUMTRACERS_T*
- *CHGEXTRACERFLAG_G*
- *CHGEXNUMTRACERS_G*
- *RESEXSTARTDAY*
- *RESEXCFREQ_N*
- *RESEXMEDIUM_N*
- *ACCEXCSTARTDAY_I*
- *ACCEXCFREQ_I*
- *ACCEXCMEDIUM_I*
- *PAYEXSTARTDAY_T*
- *PAYEXCFREQ_T*
- *PAYEXMEDIUM_T*
- *CHGEXSTARTDAY_G*
- *CHGEXCFREQ_G*
- *CHGEXMEDIUM*
- *TEMPLATEID*

Status-Details

- *AUTOFRWD_N*
- *AUTOREVERSE_N*
- *COMPLETEACCRUALS_N*
- *REVERSEACCRUALS_N*
- *STATUS*
- *STATUSSEQ_N*
- *STPACCRUALS_N*
- *TRANSACTIONCD*
- *Status-Advices-Details*
  - *MESSAGECD*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCNTROLE*
  - *ACCROLEDESC_N*
  - *UPWARDTRANSFERFRMGL_N*
  - *UPWARDTRANSFERFRMGLDESC*
  - *UPWARDTRANSFERTOGL_N*
  - *UPWARDTRANSFERTOGLDESC_N*
  - *DWNWRDTRANSFERFRMGL_N*
  - *DWNWRDTRANSFERFRMGLDESC_N*
  - *DWNWRDTRANSFERTOGL_N*
  - *DWNWRDTRANSFERTOGLDESC*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *RUL*

- AMNTTAG
- BASISAMNTTAG
- COMPTATIONEVNT
- TYP

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Branch-Ccy-Restrictions

- CCYLST
- BRNLST
- CLASCD
- CLASDESC

- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

- *STPASOCIATN*
- *ADVCHG*
- *CAPTLIZE*
- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Discount-Accrual

- *CLASCD*
- *CLASDESC*
- *CLSDFLT*
- *Disc-Accr-Details*
  - *DISCACCRREQD*
  - *ACCRFREQ*
  - *PREPAYTBDTREAT*
  - *ACQTYP*
- *Ccy-Preferences*
  - *CCYCODE*
  - *CCYNAME*
  - *DENOMDCNTMET*
  - *DENOMMETHOD*

Product-Interest

- *Interest-Components*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *RATCDUSGE*
  - *RATTYP*
  - *RATCD*
  - *SETTLMNTCCY*
  - *STPAPPLICTION*
  - *RESETTENOR*
  - *BRWLENDIND*

LVLNO
PREPMTMETD
PROPREQD
MARGNBASIS
MARGNAPPLN
RATECALCTYP
ACQREQD
CHNGDRGAMNDMNT
SHWNINCNTRTMAINSCR
BLKAMTFLG
DEPORATECD
DISCACCRAPP
UNIT
NOUNIT
EVNT
COMPNENT
COMPNENTDESC
RUL
COLTYP
EVNTDESC
RULEDESC
Interest-Ccy-Preferences
CCY
DEFRAT
MINRATE
MAXRAT
DFLTSPRD
MINSPRD
MAXSPRD
INTBASIS
DENOMBASIS
BAS366
NOOFINTPRD
PRPMTRT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	Includes Bills and Collections- Product Authorization details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product code Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indciates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OP

Attribute	**Description**	
Name	OP	
Datatype	String	
Description	Indicates Operation Code	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RC

Attribute	Description
Name	RC
Datatype	String
Description	Indicates whether Reimbursement Claim is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATA

Attribute	Description
Name	ATA
Datatype	String
Description	Indicates Acceptance to Advance is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ATD

Attribute	Description
Name	ATD
Datatype	String
Description	Indicates whether Acceptance to Discount is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CTP

Attribute	Description	
Name	CTP	
Datatype	String	
Description	Indicates whether Collection to Purchase is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DTC

Attribute	Description	
Name	DTC	
Datatype	String	
Description	Indicates whether Discount to Collection is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PTC

Attribute	Description	
Name	PTC	
Datatype	String	
Description	Indicates whether Purchase to Collection is Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOC

Attribute	Description	
Name	DOC	
Datatype	String	
Description	Indicates whether Document Type. C - Clean and D - Documentary	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D

TOP

ULOC

Attribute	Description
Name	ULOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TC

Attribute	Description
Name	TC
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

ATF

Attribute	Description
Name	ATF
Datatype	String
Description	Indicates whether Acceptance to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DTF

Attribute	Description
Name	DTF
Datatype	String
Description	Indicates whether Discount to Forfaiting is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TARCKACCRDCOMPFLAG_N

Attribute	Description
Name	TARCKACCRDCOMPFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required on Accrued Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TARCKDISCBILLFLAG_N

Attribute	Description
Name	TARCKDISCBILLFLAG_N
Datatype	String
Description	Indicates whether Limit Tracking is Required for Discount Bills
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIMTSTENORCALCTYPE

Attribute	Description
Name	LIMTSTENORCALCTYPE
Datatype	String
Description	Indicates Limits Tenor Calculation Type Fixed : F Rolling : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,R,

TOP

AUTOACPTOADVFLAG_N

Attribute	Description
Name	AUTOACPTOADVFLAG_N
Datatype	String
Description	Indicates whether Acceptance to Advance should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOLIQFLAG_N

Attribute	Description
Name	AUTOLIQFLAG_N
Datatype	String
Description	Indicates whether Liquidation should be Automatic
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

STATUSCNTRLCD_N

Attribute	Description
Name	STATUSCNTRLCD_N
Datatype	String
Description	Indicates Status Control Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

BASECRITYFLAG_N

Attribute	Description
Name	BASECRITYFLAG_N
Datatype	String
Description	Indicates whether the Product is Associated with Bankers Acceptance
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XRATETYP_N

Attribute	Description
Name	XRATETYP_N
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

XRATEOVRDLIMIT_N

Attribute	Description
Name	XRATEOVRDLIMIT_N

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XRATESTPLIMIT

Attribute	Description
Name	XRATESTPLIMIT
Datatype	Number
Description	Indicates Maximum Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AR

Attribute	Description
Name	AR
Datatype	String
Description	Indicates whether Rollover is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPINTCOMP

Attribute	Description
Name	ACPINTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ICCFCOLTYPE

Attribute	Description
Name	ICCFCOLTYPE
Datatype	String
Description	Indicates Interest Components To Be Collected In Advance : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

GOODSARRFLAG_N

Attribute	Description
Name	GOODSARRFLAG_N
Datatype	String
Description	Indicates whether Past Due Status should be based on Goods Arrival Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GOODSARRPDODAYS_N

Attribute	Description
Name	GOODSARRPDODAYS_N
Datatype	Number
Description	Indicates the No of Days after Goods Arrival Date, Past Due Status is Determined
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates Minimum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates Maximum Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STNDRDTNR_N

Attribute	Description
Name	STNDRDTNR_N
Datatype	Number
Description	Indicates Standard Tenor

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REKEYREQFLAG_N

Attribute	**Description**	
Name	REKEYREQFLAG_N	
Datatype	String	
Description	Indicates whether Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYAMNTFLAG_N

Attribute	**Description**	
Name	REKEYAMNTFLAG_N	
Datatype	String	
Description	Indicates Amount Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYCCYFLAG

Attribute	**Description**	
Name	REKYCCYFLAG	
Datatype	String	
Description	Indicates Rekey Currency Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKEYCUSTFLAG_N

Attribute	**Description**	
Name	REKEYCUSTFLAG_N	
Datatype	String	
Description	Indicates Customer Rekey is Required during Authorization	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDATE_N

Attribute	Description
Name	REKYVALDATE_N
Datatype	String
Description	Indicates whether Value Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATURTYDATE_N

Attribute	Description
Name	REKYMATURTYDATE_N
Datatype	String
Description	Indicates whether Maturity Date Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTTLPAID_N

Attribute	Description
Name	REKYTTLPAID_N
Datatype	String
Description	Indicates whether Total Paid Rekey is Required during Authorization
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALSTRTDAY_N

Attribute	Description
Name	ACCRUALSTRTDAY_N
Datatype	Number
Description	Indicates Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRACEDAYS_N

Attribute	Description
Name	GRACEDAYS_N

Datatype	Number
Description	Indicates Grace Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRUALSTRTMONTH_N

Attribute	Description
Name	ACCRUALSTRTMONTH_N
Datatype	String
Description	Indicates Accrual Start Month
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / JAN,FEB,MAR,APR,MAY,JUN,JUL,AUG,SEP,OCT,NOV,DEC,

TOP

ALLWPREPAY_N

Attribute	Description
Name	ALLWPREPAY_N
Datatype	String
Description	Indicates whether Prepayment is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVANCEBYLOAN_N

Attribute	Description
Name	ADVANCEBYLOAN_N
Datatype	String
Description	Indicates whether Advance by Loan is Allowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BRIDGEGL_N

Attribute	Description
Name	BRIDGEGL_N
Datatype	String
Description	Indicates Settlement Bridge GL
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD_N

Attribute	Description	
Name	LOANPRD_N	
Datatype	String	
Description	Indicates Loan Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DISCNTMETHOD

Attribute	Description	
Name	DISCNTMETHOD	
Datatype	String	
Description	Indicates Discounting Method Discounted : D True Discounted : T	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,T,

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Prefered Rate Code Mid Rate "M" Buy/Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,M

TOP

FREECOLLFLAG_N

Attribute	Description	
Name	FREECOLLFLAG_N	
Datatype	String	
Description	Indicates whether the Product is used for Free Collection	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEDAYS_N

Attribute	Description
Name	BILLNOTICEDAYS_N
Datatype	Number
Description	Indicates Billing Notice Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLNOTICEREQDFLAG_N

Attribute	Description
Name	BILLNOTICEREQDFLAG_N
Datatype	String
Description	Indicates whether Billing Notice is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BILLNOTICEFLAG

Attribute	Description
Name	BILLNOTICEFLAG
Datatype	String
Description	Indicates bill notice Before : B After : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

ACCRUALFREQ_N

Attribute	Description
Name	ACCRUALFREQ_N
Datatype	String
Description	Indicates Accrual Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,Y,

TOP

FORFAITINTCOMP_N

Attribute	Description
Name	FORFAITINTCOMP_N
Datatype	String
Description	Indicates Forfaiting Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TRANSITDAYS_N

Attribute	Description
Name	TRANSITDAYS_N
Datatype	Number
Description	Indicates Transit Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCOTERM_N

Attribute	Description
Name	INCOTERM_N
Datatype	String
Description	Indicates INCO Term
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

LTL

Attribute	Description
Name	LTL
Datatype	String
Description	Indicates whether Export Bill should be Linked to a Loan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACPCOLTYPE

Attribute	Description
Name	ACPCOLTYPE

Datatype	String
Description	Indicates Acceptance Component Collect Type. A - Advance and R - Arrears
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	Indicates whether Charge Claim is Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWBROK

Attribute	Description
Name	ALLWBROK
Datatype	String
Description	Indicates whether Brokerage is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLTOTRF

Attribute	Description
Name	COLLTOTRF
Datatype	String
Description	Indicates whether Collection to Transfer is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQ_USING_COLLATERAL

Attribute	Description
Name	LIQ_USING_COLLATERAL
Datatype	String
Description	Indicates Liquidate Using Collateral Flag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSFERCOLLATFROMLC

Attribute	**Description**	
Name	TRANSFERCOLLATFROMLC	
Datatype	String	
Description	Indicates Transfer Collateral from LC Flag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaiton of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Their-Details

Attribute	Description
Name	Charge-Their-Details
Datatype	
Description	Includes Charge their details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTCODE

Attribute	Description
Name	EVNTCODE
Datatype	String
Description	Indicates Liquidation Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Instructions-Details

Attribute	Description
Name	Instructions-Details
Datatype	
Description	Includes Instructions details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD_N

Attribute	Description
Name	INSCD_N
Datatype	String
Description	Indicates Instruction Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSCDDESC_N

Attribute	Description
Name	INSCDDESC_N
Datatype	String
Description	Indicates Instruction Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_N

Attribute	Description
Name	ADVCD_N
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSSLNO

Attribute	Description
Name	INSSLNO
Datatype	Number
Description	Indicates Instruction Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	FFT Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTTXTCD

Attribute	Description
Name	FFTTXTCD
Datatype	String
Description	Includes Free Format Text Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTCDDESC

Attribute	Description
Name	FFTCDDESC
Datatype	String
Description	Includes Free Format Text Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD_I

Attribute	Description
Name	ADVCD_I
Datatype	String
Description	Indicates Advice Code
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FFTSLNO

Attribute	Description
Name	FFTSLNO
Datatype	Number
Description	Indicates Free Format Text Serial Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	Includes Document details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCODE_N

Attribute	Description
Name	DOCODE_N
Datatype	String
Description	Indicates Document Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	Indicates Document Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOCDESR

Attribute	Description
Name	DOCDESR
Datatype	String
Description	Indicates Document Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	Indicates Document Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	Description

Name	Clause-Details
Datatype	
Description	Includes Clause details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECODE_N

Attribute	Description
Name	CLAUSECODE_N
Datatype	String
Description	Indicates Clause Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESCR_N

Attribute	Description
Name	CLAUSEDESCR_N
Datatype	String
Description	Indicates Clause Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

CLAUSESLNO

Attribute	Description
Name	CLAUSESLNO
Datatype	Number
Description	Indicates Clause Serial Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	Includes Tracer details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXTARCERFLAG_N

Attribute	Description
Name	RESEXTARCERFLAG_N
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

RESEXNUMTARCERS_N

Attribute	Description
Name	RESEXNUMTARCERS_N
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCEXCTRACERFLAG_I

Attribute	Description
Name	ACCEXCTRACERFLAG_I
Datatype	String
Description	Indicates whether Acceptance Exception Tracer is Required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,R</td></tr></table>

TOP

ACCEXCNUMTRACERS_N

Attribute	Description
Name	ACCEXCNUMTRACERS_N
Datatype	Number
Description	Indicates No of Acceptance Exception Tracers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYEXTARCERFLAG_T

Attribute	Description
Name	PAYEXTARCERFLAG_T
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

PAYEXNUMTRACERS_T

Attribute	Description
Name	PAYEXNUMTRACERS_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGEXTRACERFLAG_G

Attribute	Description
Name	CHGEXTRACERFLAG_G
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

CHGEXNUMTRACERS_G

Attribute	Description
Name	CHGEXNUMTRACERS_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXSTARTDAY

Attribute	Description
Name	RESEXSTARTDAY
Datatype	Number
Description	Indicates Reserve Exception Start Tracers After Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESEXCFREQ_N

Attribute	Description
Name	RESEXCFREQ_N
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESEXMEDIUM_N

Attribute	**Description**	
Name	RESEXMEDIUM_N	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCEXCSTARTDAY_I

Attribute	**Description**	
Name	ACCEXCSTARTDAY_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCFREQ_I

Attribute	**Description**	
Name	ACCEXCFREQ_I	
Datatype	Number	
Description	Indicates Acceptance Exception Tracer Generation Frequency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCEXCMEDIUM_I

Attribute	**Description**	
Name	ACCEXCMEDIUM_I	
Datatype	String	
Description	Indicates Acceptance Exception Tracer Medium	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYEXSTARTDAY_T

Attribute	**Description**
Name	PAYEXSTARTDAY_T

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXCFREQ_T

Attribute	Description
Name	PAYEXCFREQ_T
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYEXMEDIUM_T

Attribute	Description
Name	PAYEXMEDIUM_T
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHGEXSTARTDAY_G

Attribute	Description
Name	CHGEXSTARTDAY_G
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXCFREQ_G

Attribute	Description
Name	CHGEXCFREQ_G
Datatype	Number
Description	Indicates Charge Exception Tracer Generation Frequency
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGEXMEDIUM

Attribute	Description
Name	CHGEXMEDIUM

Datatype	String
Description	Indicates Charge Exception Preferred Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	Includes Status details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AUTOFRWD_N

Attribute	Description
Name	AUTOFRWD_N
Datatype	String
Description	Indicates whether Automatic Forward Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE_N

Attribute	Description
Name	AUTOREVERSE_N
Datatype	String
Description	Indicates whether Automatic Reverse Status Movement is Allowed
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS_N

Attribute	Description
Name	COMPLETEACCRUALS_N
Datatype	String
Description	Indicates whether Pending Accruals should be Completed prior to Status Movement
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS_N

Attribute	Description
Name	REVERSEACCRUALS_N
Datatype	String
Description	Indicates whether Outstanding Accruals should be Reversed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	Indicates Status
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUSSEQ_N

Attribute	Description
Name	STATUSSEQ_N
Datatype	Number
Description	Indicates Status Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS_N

Attribute	Description

Name	STPACCRUALS_N
Datatype	String
Description	Indicates whether Accruals should be Stopped
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Status-Advices-Details

Attribute	Description
Name	Status-Advices-Details
Datatype	
Description	Includes Status Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MESSAGECD

Attribute	Description
Name	MESSAGECD
Datatype	String
Description	Indicates Message Code
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	Indicates Status Derivation Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	Includes Upward And Downward Movement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	Indicates Accounting Role
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCROLEDESC_N

Attribute	Description
Name	ACCROLEDESC_N
Datatype	String
Description	Indicates Accounting Role Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UPWARDTRANSFERFRMGL_N

Attribute	Description
Name	UPWARDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Upward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERFRMGLDESC

Attribute	Description
Name	UPWARDTRANSFERFRMGLDESC
Datatype	String

Description	Indicates Upward Movement FROM GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UPWARDTRANSFERTOGL_N

Attribute	Description
Name	UPWARDTRANSFERTOGL_N
Datatype	String
Description	Indicates Upward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UPWARDTRANSFERTOGLDESC_N

Attribute	Description
Name	UPWARDTRANSFERTOGLDESC_N
Datatype	String
Description	Indicates Upward Transfer To GL Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERFRMGL_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGL_N
Datatype	String
Description	Indicates Downward Transfer From GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERFRMGLDESC_N

Attribute	Description
Name	DWNWRDTRANSFERFRMGLDESC_N
Datatype	String
Description	Indicates Downward Transfer From GL Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DWNWRDTRANSFERTOGL_N

Attribute	Description
Name	DWNWRDTRANSFERTOGL_N
Datatype	String
Description	Indicates Downward Transfer To GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DWNWRDTRANSFERTOGLDESC

Attribute	Description
Name	DWNWRDTRANSFERTOGLDESC
Datatype	String
Description	Indicates Downward Movement To GL Account Head Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	Indicates Tax Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Specifies the Scheme ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Indicates Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

AMNTTAG

Attribute	Description
Name	AMNTTAG
Datatype	String
Description	Indicates the Tax Component of Tax Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	Indicates the Event of Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	Indicates Tax Type WITHHOLDING : W Expense : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String

Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates the class description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Product Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Cust Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the class code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	**Description**	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	Description	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	Description	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	Description	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	**Description**	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Discount-Accrual

Attribute	Description
Name	Product-Discount-Accrual
Datatype	
Description	Includes Product Discount Accrual details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the class code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates the class description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CLSDFLT

Attribute	Description
Name	CLSDFLT
Datatype	String
Description	Indicates Class Default
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Disc-Accr-Details

Attribute	Description
Name	Disc-Accr-Details
Datatype	
Description	Includes Discount Accrual details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCACCRREQD

Attribute	Description
Name	DISCACCRREQD
Datatype	String

Description	Indicates Discount Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRFREQ

Attribute	Description
Name	ACCRFREQ
Datatype	String
Description	Indicates Accrual Frequency Daily : D Monthly : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,

TOP

PREPAYTBDTREAT

Attribute	Description
Name	PREPAYTBDTREAT
Datatype	String
Description	Indicates Handling of Fore Closure Complete Accrual : C Refund : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,R,

TOP

ACQTYP

Attribute	Description
Name	ACQTYP
Datatype	String
Description	Indicates Acquisition Type Partial : R Par/Discount : D Par/Premium : P Par/Discount/Premium : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,D,P,A,

TOP

Ccy-Preferences

Attribute	Description
Name	Ccy-Preferences
Datatype	
Description	Includes Currency Preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DENOMDCNTMET

Attribute	Description
Name	DENOMDCNTMET
Datatype	String
Description	Indicates Numerator Method 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

DENOMMETHOD

Attribute	Description

Name	DENOMMETHOD
Datatype	String
Description	Indicates Denominator Method The possible values are L, H, X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Product Interest Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Components

Attribute	Description
Name	Interest-Components
Datatype	
Description	Includes Interest Components details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	Indicates Amount Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	Indicates amount Category Expected : X Overdue : D Normal : N Outstanding : O

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,D,N,O

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	Indicates rate Code Usage Auto : A Periodic : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type Fixed : X Floating : F Special : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,S

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String

Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	Indicates Stop Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	Indicates Reset Tenor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRWLENDIND

Attribute	Description
Name	BRWLENDIND
Datatype	String
Description	Indicates Borrow Lend Indicator Borrow : B Lend : L Mid : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

TOP

LVLNO

Attribute	Description
Name	LVLNO
Datatype	Number
Description	Indicates Level No.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREPMTMETD

Attribute	**Description**	
Name	PREPMTMETD	
Datatype	String	
Description	Indicates Pre Payment Method Flexcube : F Custom : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,C

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MARGNBASIS

Attribute	**Description**	
Name	MARGNBASIS	
Datatype	String	
Description	Indicates Margin Basis Facility : F Tranche : T Drawdown : D Customer : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,D,C

TOP

MARGNAPPLN

Attribute	**Description**
Name	MARGNAPPLN
Datatype	String

Description	Indicates Margin Application Periodic : P Automatic : A None : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,A,N

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	Indicates Rate Cycle Type UP : U DOWN : D INTERPOLATE : I ROUNDOFF : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,D,I,R

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	Indicates Allow Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	Indicates Main Component Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BLKAMTFLG

Attribute	Description
Name	BLKAMTFLG
Datatype	String
Description	Indicates Bulk Amount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEPORATECD

Attribute	Description
Name	DEPORATECD
Datatype	String
Description	Indicates Link Contract As Ratecode Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPP

Attribute	Description
Name	DISCACCRAPP
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	Indicates Units Days : D Months : M Years : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Y

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	Number
Description	Indicates Grace Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates Component
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RUL

Attribute	Description
Name	RUL
Datatype	String
Description	Indicates Tax Rule
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

COLTYP

Attribute	Description
Name	COLTYP
Datatype	String
Description	Indicates Collection Type Advance: A Arrear : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULEDESC

Attribute	Description

Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Interest-Ccy-Preferences

Attribute	Description
Name	Interest-Ccy-Preferences
Datatype	
Description	Includes Interest Currency preferences details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Account Currency
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	Indicates Default Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	Indicates Minimum Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	Indicates Maximum Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFLTSPRD

Attribute	Description
Name	DFLTSPRD
Datatype	Number
Description	Indicates Default Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	Indicates Minimum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	Indicates Maximum Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	Indicates Interest Basis 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DENOMBASIS

Attribute	**Description**	
Name	DENOMBASIS	
Datatype	String	
Description	Indicates Denominator Basis Per Annum : A Per Interest Basis : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I

TOP

BAS366

Attribute	**Description**	
Name	BAS366	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

NOOFINTPRD

Attribute	**Description**	
Name	NOOFINTPRD	
Datatype	Number	
Description	Indicates No. of Interest Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRPMTRT

Attribute	**Description**	
Name	PRPMTRT	
Datatype	Number	
Description	Indicates Pre Payment Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.4.BC-AuthorizeProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	Includes Bills and Collections- Product Authorization-Primary key details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	Includes Bills and Collections- Product Authorization-IO details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.CloseAmendConfirm

Close BC Amendment Confirmation

2.63.1.BC-CloseAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT

Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description

Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPERIOD

Attribute	**Description**	
Name	NOINTPERIOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN

Attribute	**Description**
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTCALC

Attribute	**Description**	
Name	AMTCALC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description	Includes the Charges Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.63.2.BC-CloseAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-IO*
    - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Intrest*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Taxes*
      - *CONREFNO*
      - *LATEVNSEQNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.63.3.BC-CloseAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*

EVENTDESC

Amendadv

- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD

ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT

MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**

Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPERIOD

Attribute	**Description**	
Name	NOINTPERIOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN

Attribute	**Description**
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.4.BC-CloseAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-PK*
      - *CONREFNO*
    - *Amendmaster-IO*
      - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Intrest*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Taxes*
        - *CONREFNO*
        - *LATEVNSEQNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-PK

Attribute	Description
Name	Amendmaster-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.CloseContract

Close BC Contract

2.64.1.BC-CloseContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*

THECHGAMT
LIQAMT
AMOUNT
LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF

CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT
LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM

TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT
RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*

- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*
- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*

Goods-Details

- *GOODSCODE*
- *GOODSDESC*
- *INCOTRM*

Shipment

- *SHIPMRKS*
- *DESFROM*
- *DESTO*
- *CARNAM*
- *PARSHIPINFO*
- *SHIPDTLS*
- *LATSHIPDT*
- *TRNSSHIPFLAG*
- *SHIPDT*
- *ARRVDT*
- *OTHRSHIPINFO*

Pay-Excep

- *TRCREQDFLG*
- *NUMTRCTOSENT*
- *TRACMED*
- *TRACSRTDT*
- *TRACFREQ*
- *PREVTRACDT*
- *NUMTRSENT*
- *NEXTTRACDT*
- *TRACRECPART*
- *PAYMSGDT*
- *NONPAYMSGDT*
- *PROTFLG*
- *DTOFPROT*
- *MANGENFLG*

Pay-Fate

- *ADVFTREQDFLG*
- *ADVFTMED*
- *PRVADVFTDT*
- *NUMADVFTSNT*
- *NXTADVFTDT*

ADVFTRECPART
MANGENFLG
Acc-Excep
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG

Roll-Pref
- *BASEDT*
- *BASEDTDESC*
- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts
- *AMTNAM*
- *AMT*

Invoice-Master
- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master
- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates
- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master
- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit
- *CLACCNO*

SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD

INTBASISD
WAIVEDD
CHGAMTD
STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT

- *LIQDTNAMT*
- *LIQDTDAMT*
- *FRMCALCDATE*
- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*

- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*

ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*

BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG
SPTAMT
SPTACBRN
SPTACCCY
SPRACNO
SPTEXCHRT
SPTPRTYID
SPTPERCENTAGE
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
ESN
CNTRPARTY

PRD
CCY
TENOR
UNITS
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
BRIDGL
CYSTALTYP
COLLLIQDAMT
LIQDLCCHGCOMM
MATDT
LOANAMT
BILLOS
CONTRACT_CURRENCY
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
ORGEXCHRATE
Bcprefdet
UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Effective-Int-Rate
CONREFNO
Effective-Intrate-Det
EFFECTDT
IRR
Intrest
CONREFNO
Intrest-Details

INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS

ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details

- FXREFNO
- TFAMT
- TFRATE
- CCY

Loanacc

- CONREFNO
- Loanaccdet
  - ACCNO
  - AMTFIN
  - CCY

Extsys-Ws-Master

- Extsys-Ws-Details
  - EXTWSRESP
  - USERREMARKS

Brok-Master

- CONREFNO
- CONTRACTCCY
- BROKPERCENT
- BROKAMT
- Brok-Detail
  - BROKNAME
  - BROKER
  - BRKACC
  - BRKACCCCY
  - BRKPERCENT
  - BRKAMTACCCCY
  - EXRATE
  - ORGEXRATE
  - NEGRATE
  - NEGREFNO
  - REMARKS
  - BRKAMTCONCCY
  - LIQSTATUS

Lic-Master

- License-Utils-Detail
  - IMPLICNO
  - GOODSCD
  - QTYUTIL
  - AMTUTIL
  - QTYREIN
  - AMTREIN
  - REMARKS
  - UNIT_OF_MEASUREMENT
  - LICENSE_AMOUNT

GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR

Attribute	**Description**	
Name	CHAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRENCY

Attribute	**Description**	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

STAG

Attribute	Description	
Name	STAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description	
Name	LCISSUEDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_CUST

Attribute	Description	
Name	LC_CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LCREFNO

Attribute	Description	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_LIAB_AMOUNT

Attribute	Description
Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

ADVBYLOAN

Attribute	**Description**	
Name	ADVBYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWROLLOVR

Attribute	**Description**	
Name	ALLWROLLOVR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LINKTOLOAN

Attribute	**Description**	
Name	LINKTOLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

USE_LC_REF_MESS

Attribute	**Description**	
Name	USE_LC_REF_MESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_DTL_PAYMSG

Attribute	Description
Name	LC_DTL_PAYMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FROMDATE

Attribute	Description
Name	FROMDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TODATE

Attribute	Description
Name	TODATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GRCDAYS

Attribute	Description
Name	GRCDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPFRMDT

Attribute	**Description**	
Name	ACPFRMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACPTODT

Attribute	**Description**	
Name	ACPTODT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCORGRECFG

Attribute	**Description**	
Name	DOCORGRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DOCDUPRECFG

Attribute	**Description**	
Name	DOCDUPRECFG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	Description	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	Description	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	Description	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	Description	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROVAMT

Attribute	**Description**	
Name	PROVAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTREMRKS

Attribute	**Description**	
Name	INTREMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PARENT_CON_REF

Attribute	**Description**	
Name	PARENT_CON_REF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PURAMT

Attribute	**Description**	
Name	PURAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNLNKFXRATE

Attribute	**Description**
Name	UNLNKFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H,L</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description
Name	CONTRACT_DERIVED_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR_FIELD1

Attribute	Description
Name	CHAR_FIELD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CNFRMD

Attribute	Description
Name	CNFRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

CONF_AMT

Attribute	Description
Name	CONF_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,I

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TFR_COLL_AMT

Attribute	**Description**	
Name	TFR_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OUT_COLL_AMT

Attribute	**Description**	
Name	OUT_COLL_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RFNDINT

Attribute	**Description**	
Name	RFNDINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RCVRY_RT

Attribute	**Description**	
Name	RCVRY_RT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC_INT_RTCD

Attribute	**Description**
Name	REC_INT_RTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Parties

Attribute	Description
Name	Contract-Parties
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTLANG

Attribute	Description
Name	PARTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTCTRCOD

Attribute	Description
Name	PARTCTRCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PARTREFNO

Attribute	Description
Name	PARTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PARTNAM

Attribute	Description

Name	PARTNAM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTADD4

Attribute	Description
Name	PARTADD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PARTID

Attribute	**Description**	
Name	PARTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

PARTTYP

Attribute	**Description**	
Name	PARTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Addr

Attribute	**Description**	
Name	Party-Addr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description

Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

JVPARENT

Attribute	Description	
Name	JVPARENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,BILL_OS_AMT,AMT_PURCHASED, CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REIMBNKCOP

Attribute	**Description**	
Name	REIMBNKCOP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCREF

Attribute	**Description**	
Name	DOCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCDATE

Attribute	**Description**	
Name	DOCDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COVLETREF

Attribute	**Description**	
Name	COVLETREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**
Name	COVLETDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDT

Attribute	Description	
Name	SHIPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ARRVDT

Attribute	Description	
Name	ARRVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	Description	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Pay-Excep

Attribute	Description	
Name	Pay-Excep	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVTRACDT

Attribute	**Description**	
Name	PREVTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NUMTRSENT

Attribute	**Description**	
Name	NUMTRSENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTTRACDT

Attribute	**Description**	
Name	NEXTTRACDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACRECPART

Attribute	**Description**	
Name	TRACRECPART	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PAYMSGDT

Attribute	**Description**
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSCOMPNAM

Attribute	Description
Name	INSCOMPNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEB

Attribute	Description
Name	INTRATEB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISB

Attribute	Description
Name	INTBASISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description
Name	WAIVEB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTB

Attribute	Description
Name	INTAMOUNTB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Effective-Intrate-Det

Attribute	Description
Name	Effective-Intrate-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EFFECTDT

Attribute	Description
Name	EFFECTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

IRR

Attribute	Description
Name	IRR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	**Description**	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	**Description**	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	**Description**	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	**Description**	
Name	NEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	**Description**	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

GOODSCD

Attribute	**Description**	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

QTYUTIL

Attribute	**Description**	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTUTIL

Attribute	**Description**	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYREIN

Attribute	**Description**

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.64.2.BC-CloseContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *Taxes*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Collateral-details*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Linkages*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*

Settlements
CONREFNO
LATEVNSEQNO
Adice
Split-Master
CONREFNO
LATEVNSEQNO
Bcpref
CONREFNO
LATEVNSEQNO
Effective-Int-Rate
CONREFNO
LATEVNSEQNO
Intrest
CONREFNO
LATEVNSEQNO
Bcfx
BILLREFNO
ESN
Loanacc
CONREFNO
LATEVNSEQNO
Extsys-Ws-Master
KEYID
Brok-Master
CONREFNO
LATEVNSEQNO
Lic-Master
CONREFNO
LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Linkages

Attribute	**Description**	
Name	Linkages	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BILLREFNO

Attribute	**Description**	
Name	BILLREFNO	
Datatype	String	
Description	Indicates Bill Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Loanacc

Attribute	**Description**	
Name	Loanacc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.64.3.BC-CloseContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *EXTREFNO*
    - *USEREFNO*
    - *PRODCD*
    - *CHAR*
    - *CURRENCY*
    - *PRDDESC*
    - *OPERATION*
    - *STAG*
    - *LCISSUEDATE*
    - *LC_CUST*
    - *LCREFNO*
    - *THEIR_LCREF*
    - *COLLREF*
    - *THECHGCCY*
    - *THECHGAMT*
    - *LIQAMT*
    - *AMOUNT*

LCAMOUNT
LOCAL_CURRR
OUTSTAMT
LC_LIAB_AMOUNT
VALDT
MATDT
TENOR_DAYS
TRANSITDAYS
BASDT
BASDTDES
REIMDYS
VDATECR
DRVALDT
BASE_DATE_CODE
TXNDT
LIQDDATE
INTLIQDMOD
CUSTOMER_ID
PRTYTYP
LMTMONFLG
REDISFLG
STATCNFLG
AUTOLIQFLG
ADVBYLOAN
ALLWROLLOVR
LINKTOLOAN
USE_LC_REF_MESS
LC_DTL_PAYMSG
FROMDATE
TODATE
GRCDAYS
ALLOWREPAY
ACPFRMDT
ACPTODT
DOCORGRECFG
DOCDUPRECFG
COVLETDT
ACKNREC
ACKNDT
PASS_TO_CHG_DRDE
OURCHGREF
CHG_REFUSED
PASS_INT_TO_DRDE
STATASDT

LOAN_CONTREF
MARGAMTLIQ
MARGDUEAMT
COLLCCY
COLLAMT
COLLDESC
CHKNUM
ICCPCKCCY
EXHRATE
FORFAITREQDT
FORFAITDOCDT
PROVAMT
INTREMRKS
PARENT_CON_REF
PURAMT
UNLNKFXRATE
EFFLCYCOLEXRT
EFFLCYPURRATE
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTAT
USRDEFSTATS
SOURCE
CHGCLAIM
LIQDCOLLAT
TEMPLATEID
SETTLEAMT
ALLWBRK
BROKPAIDBYUS
ACPTOADVFLG
CONTRACT_DERIVED_STATUS
CHAR_FIELD1
CNFRMD
CONF_AMT
UNCONF_AMT
AVL_CONF_AMT
AVL_UNCONF_AMT
COLLCADVCHGFROM
TRANSFERCOLLATFROMLC
TFR_COLL_AMT
OUT_COLL_AMT

RFNDINT
RCVRY_RT
REC_INT_RTCD
REBATE_AMT
FURTHER_IDENTIFICATION
TXT_CUSTNAME
Deferred-Chg-Comp-Master
Contract-Parties
- *PARTLANG*
- *PARTCTRCOD*
- *PARTREFNO*
- *PARTNAM*
- *PARTADD1*
- *PARTADD2*
- *PARTADD3*
- *PARTADD4*
- *PARTID*
- *PARTTYP*
- *Party-Addr*
  - *MEDIA*
  - *ADDR*

Party-Limits
- *PARTTYP*
- *OPERATION*
- *LIMITAMT*
- *CUST_NO*
- *LINKAGETYP*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *JVPARENT*
- *LIABILITY_NUMBER*
- *AMOUNTTAG*
- *SLNO*

Document-Details
- *DOCCD*
- *DESC*
- *FRSTMAILCOP*
- *SECMAILCOP*
- *REIMBNKCOP*
- *DOCREF*
- *DOCDATE*
- *COVLETREF*
- *COVLETDATE*
- *FRSTMAILORG*

- *SECMAILORG*
- *Doc-Clause*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Goods-Details*
  - *GOODSCODE*
  - *GOODSDESC*
  - *INCOTRM*
- *Shipment*
  - *SHIPMRKS*
  - *DESFROM*
  - *DESTO*
  - *CARNAM*
  - *PARSHIPINFO*
  - *SHIPDTLS*
  - *LATSHIPDT*
  - *TRNSSHIPFLAG*
  - *SHIPDT*
  - *ARRVDT*
  - *OTHRSHIPINFO*
- *Pay-Excep*
  - *TRCREQDFLG*
  - *NUMTRCTOSENT*
  - *TRACMED*
  - *TRACSRTDT*
  - *TRACFREQ*
  - *PREVTRACDT*
  - *NUMTRSENT*
  - *NEXTTRACDT*
  - *TRACRECPART*
  - *PAYMSGDT*
  - *NONPAYMSGDT*
  - *PROTFLG*
  - *DTOFPROT*
  - *MANGENFLG*
- *Pay-Fate*
  - *ADVFTREQDFLG*
  - *ADVFTMED*
  - *PRVADVFTDT*
  - *NUMADVFTSNT*
  - *NXTADVFTDT*
  - *ADVFTRECPART*
  - *MANGENFLG*
- *Acc-Excep*

TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACSRTDT
TRACFREQ
PREVTRACDT
NEXTTRACDT
NUMTRSENT
NONACCPAYMSGDT
PROTFLG
TRACRECPART
DTOFPROT
ACCMSGDT
MANGENFLG
Acc-Fate
MANGENFLG
ADVFTREQDFLG
ADVFTMED
PRVADVFTDT
NUMADVFTSNT
NXTADVFTDT
ADVFTRECPART
Contract-Disc
DISCCD
DISCDESC
DISCRESLFLG
DISCRESDT
DISCRECDT
Contract-Reserve
TRCREQDFLG
NUMTRCTOSENT
TRACMED
TRACFREQ
TRACSRTDT
PREVTRACDT
NUMTRSENT
NEXTTRACDT
RESRELDT
DISCAPPDT
TRACER_RECEIVER_TYP
UNDRESFLG
Roll-Pref
BASEDT
BASEDTDESC

- *TNRDAYS*
- *TRNSDAYS*
- *MATDAYS*
- *INTLIQDMOD*
- *FRMCALCDT*
- *TOCALCDT*
- *BASEDTCOD*

Drafts

- *AMTNAM*
- *AMT*

Invoice-Master

- *INVCCY*
- *MARGIND*
- *MARG*
- *ELGAMT*
- *MARGAMT*
- *Invoice-Details*
  - *INVCNO*
  - *INVCDT*
  - *AMT*

Insurance-Master

- *CONTREFNNO*
- *INSCOMPCOD*
- *INSPOLNO*
- *INSCOMPNAM*
- *ADDRLN1*
- *ADDRLN2*
- *ADDRLN3*
- *ADDRLN4*
- *TELENO*
- *FAXNO*

Iccf-Calc-Dates

- *COMP*
- *INTFRMDT*
- *INTTODT*

Account-Master

- *ACCNO*
- *AMTFIN*
- *CCY*

Pack-Credit

- *CLACCNO*
- *SEQNO*
- *LNKCCY*
- *OUTSTAMT*

EVNTCOD
STLAMT
Pack-Credit-Dtls
CLACCNO
SEQNO
LNKCCY
OUTSTAMT
EVNTCOD
Deferred-Chg-Comp-Details
LCREFNO
COMPONENT
AMT_TRANSFERRED
COMP_CCY
AMT_PAID
Bctbs-Int-Chg-Calc
CONTREFNOA
COMPONENTA
STDTA
COMPCCYA
INTRATEA
INTBASISA
WAIVEA
INTAMOUNTA
COMPONENTB
COMPCCYB
INTRATEB
INTBASISB
WAIVEB
INTAMOUNTB
COMPONENTC
COMPCCYC
INTRATEC
INTBASISC
WAIVEC
INTAMOUNTC
CONTREFNOD
COMPONENTD
INTCHGCOMPD
STDTD
COMPCCYD
CHGPERD
INTBASISD
WAIVEDD
CHGAMTD

STATUSD
CONTREFNOE
COMPONENTE
INTCHGCOMPE
STDTE
COMPCCYE
CHGPERE
INTBASISE
WAIVEE
CHGAMTE
STATUSE
CONTREFNOF
COMPONENTF
INTCHGCOMPF
STDTF
COMPCCYF
CHGPERF
INTBASISF
WAIVEF
CHGAMTF
STATUSF
COMPDESCA
COMPDESCB
COMPDESCC
COMPDESCD
COMPDESCE
COMPDESCF
Contract-Multitnr
SERIALNUM
BASDATE
BASEDATE_CODE
VALUDATE
TNOR
TRANSTDAYS
MATDAT
SPLITPCT
BILLAMNT
DISCOUNTAMT
REBATAMT
EXCRATE
DISCOUNTDAMT
LIQDTNAMT
LIQDTDAMT
FRMCALCDATE

- *TOCALCDATE*
- *USRDFNDSTS*
- *STSAFDATE*
- *UNDERPROTEST*
- *PROTESTDATE*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*

- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*
    - *EXRATE*
    - *COLLTDESC*
    - *ADJSTSIGN*
    - *ADJSTAMT*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1

ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*

REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3

- REPRES4
- RCVRACC

Adice

- ADV_CODE
- SUPRESS
- PRIORITY
- PRTY
- MEDIUM
- PRTYID
- PRTYNAME
- Fft
  - FFT_CODE
  - FFTTXT
- Ins
  - INSCD
  - INSTXT

Split-Master

- CONREFNO
- Split-Master
  - BASISAMTTAG
  - BASISAMTCCY
  - BASISAMT
  - Split-Detail
    - SPTSEQNO
    - SPTAMTTAG
    - SPTAMT
    - SPTACBRN
    - SPTACCCY
    - SPRACNO
    - SPTEXCHRT
    - SPTPRTYID
    - SPTPERCENTAGE
    - LOANACC
    - NEGORATE
    - NEGO_REF_NO

Bcpref

- CONREFNO
- LATEVNSEQNO
- BCREFNO
- ESN
- CNTRPARTY
- PRD
- CCY
- TENOR

- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*

Effective-Int-Rate

- *CONREFNO*
- *Effective-Intrate-Det*
  - *EFFECTDT*
  - *IRR*

Intrest

- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*

SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD

ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Bcfx
BILLREFNO
ESN
Uicolumns
RATE
AMOUNT
Bcfx-Details
FXREFNO
TFAMT
TFRATE

- CCY
- Loanacc
  - CONREFNO
  - Loanaccdet
    - ACCNO
    - AMTFIN
    - CCY
- Extsys-Ws-Master
  - Extsys-Ws-Details
    - EXTWSRESP
    - USERREMARKS
- Brok-Master
  - CONREFNO
  - CONTRACTCCY
  - BROKPERCENT
  - BROKAMT
  - Brok-Detail
    - BROKNAME
    - BROKER
    - BRKACC
    - BRKACCCCY
    - BRKPERCENT
    - BRKAMTACCCCY
    - EXRATE
    - ORGEXRATE
    - NEGRATE
    - NEGREFNO
    - REMARKS
    - BRKAMTCONCCY
    - LIQSTATUS
- Lic-Master
  - License-Utils-Detail
    - IMPLICNO
    - GOODSCD
    - QTYUTIL
    - AMTUTIL
    - QTYREIN
    - AMTREIN
    - REMARKS
    - UNIT_OF_MEASUREMENT
    - LICENSE_AMOUNT
    - GOODSDESC
    - AMTQ_UT
    - AMTQ_RE

AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRODCD

Attribute	Description
Name	PRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHAR

Attribute	Description
Name	CHAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

STAG

Attribute	Description
Name	STAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / INI,FIN,REG

TOP

LCISSUEDATE

Attribute	Description
Name	LCISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_CUST

Attribute	Description
Name	LC_CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LCREFNO

Attribute	Description
Name	LCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THEIR_LCREF

Attribute	Description
Name	THEIR_LCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLREF

Attribute	Description
Name	COLLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

THECHGCCY

Attribute	Description
Name	THECHGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

THECHGAMT

Attribute	Description
Name	THECHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQAMT

Attribute	Description
Name	LIQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCAMOUNT

Attribute	Description
Name	LCAMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOCAL_CURRR

Attribute	Description
Name	LOCAL_CURRR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LC_LIAB_AMOUNT

Attribute	Description

Name	LC_LIAB_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR_DAYS

Attribute	Description
Name	TENOR_DAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSITDAYS

Attribute	Description
Name	TRANSITDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDT

Attribute	Description
Name	BASDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASDTDES

Attribute	Description
Name	BASDTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

REIMDYS

Attribute	Description
Name	REIMDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VDATECR

Attribute	Description
Name	VDATECR
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASE_DATE_CODE

Attribute	Description
Name	BASE_DATE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

CUSTOMER_ID

Attribute	Description
Name	CUSTOMER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LMTMONFLG

Attribute	Description
Name	LMTMONFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDISFLG

Attribute	Description
Name	REDISFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

AUTOLIQFLG

Attribute	Description
Name	AUTOLIQFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ADVBYLOAN

Attribute	Description
Name	ADVBYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWROLLOVR

Attribute	Description
Name	ALLWROLLOVR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKTOLOAN

Attribute	Description
Name	LINKTOLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

USE_LC_REF_MESS

Attribute	Description
Name	USE_LC_REF_MESS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_DTL_PAYMSG

Attribute	**Description**	
Name	LC_DTL_PAYMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FROMDATE

Attribute	**Description**	
Name	FROMDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TODATE

Attribute	**Description**	
Name	TODATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GRCDAYS

Attribute	**Description**	
Name	GRCDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ALLOWREPAY

Attribute	**Description**
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACPFRMDT

Attribute	Description
Name	ACPFRMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACPTODT

Attribute	Description
Name	ACPTODT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCORGRECFG

Attribute	Description
Name	DOCORGRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DOCDUPRECFG

Attribute	Description
Name	DOCDUPRECFG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVLETDT

Attribute	Description
Name	COVLETDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACKNREC

Attribute	Description
Name	ACKNREC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNDT

Attribute	Description
Name	ACKNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PASS_TO_CHG_DRDE

Attribute	Description
Name	PASS_TO_CHG_DRDE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OURCHGREF

Attribute	Description
Name	OURCHGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHG_REFUSED

Attribute	**Description**	
Name	CHG_REFUSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PASS_INT_TO_DRDE

Attribute	**Description**	
Name	PASS_INT_TO_DRDE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STATASDT

Attribute	**Description**	
Name	STATASDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOAN_CONTREF

Attribute	**Description**	
Name	LOAN_CONTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARGAMTLIQ

Attribute	Description
Name	MARGAMTLIQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGDUEAMT

Attribute	Description
Name	MARGDUEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLCCY

Attribute	Description
Name	COLLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLAMT

Attribute	Description
Name	COLLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLDESC

Attribute	Description
Name	COLLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CHKNUM

Attribute	Description
Name	CHKNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ICCPCKCCY

Attribute	Description
Name	ICCPCKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXHRATE

Attribute	Description
Name	EXHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITREQDT

Attribute	Description
Name	FORFAITREQDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORFAITDOCDT

Attribute	Description
Name	FORFAITDOCDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROVAMT

Attribute	Description
Name	PROVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTREMRKS

Attribute	Description
Name	INTREMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PARENT_CON_REF

Attribute	Description
Name	PARENT_CON_REF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PURAMT

Attribute	Description
Name	PURAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNLNKFXRATE

Attribute	Description
Name	UNLNKFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYCOLEXRT

Attribute	Description
Name	EFFLCYCOLEXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EFFLCYPURRATE

Attribute	Description
Name	EFFLCYPURRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

USRDEFSTATS

Attribute	Description
Name	USRDEFSTATS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDCOLLAT

Attribute	Description
Name	LIQDCOLLAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SETTLEAMT

Attribute	**Description**	
Name	SETTLEAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWBRK

Attribute	**Description**	
Name	ALLWBRK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKPAIDBYUS

Attribute	**Description**	
Name	BROKPAIDBYUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACPTOADVFLG

Attribute	**Description**	
Name	ACPTOADVFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTRACT_DERIVED_STATUS

Attribute	Description	
Name	CONTRACT_DERIVED_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHAR_FIELD1

Attribute	Description	
Name	CHAR_FIELD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CNFRMD

Attribute	Description	
Name	CNFRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

CONF_AMT

Attribute	Description	
Name	CONF_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNCONF_AMT

Attribute	Description
Name	UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_CONF_AMT

Attribute	Description
Name	AVL_CONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

AVL_UNCONF_AMT

Attribute	Description
Name	AVL_UNCONF_AMT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

COLLCADVCHGFROM

Attribute	Description
Name	COLLCADVCHGFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,I</td></tr></table>

TOP

TRANSFERCOLLATFROMLC

Attribute	Description
Name	TRANSFERCOLLATFROMLC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TFR_COLL_AMT

Attribute	Description
Name	TFR_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OUT_COLL_AMT

Attribute	Description
Name	OUT_COLL_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RFNDINT

Attribute	Description
Name	RFNDINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RCVRY_RT

Attribute	Description
Name	RCVRY_RT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REC_INT_RTCD

Attribute	Description
Name	REC_INT_RTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

REBATE_AMT

Attribute	Description
Name	REBATE_AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FURTHER_IDENTIFICATION

Attribute	Description
Name	FURTHER_IDENTIFICATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,ACCEPT,DEBIT,NEGOTIATE,REIMBURSE,REMITTED,SEE72</td></tr></table>

TOP

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Deferred-Chg-Comp-Master

Attribute	Description
Name	Deferred-Chg-Comp-Master
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Parties

Attribute	**Description**	
Name	Contract-Parties	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTLANG

Attribute	**Description**	
Name	PARTLANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTCTRCOD

Attribute	**Description**	
Name	PARTCTRCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTREFNO

Attribute	**Description**	
Name	PARTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PARTNAM

Attribute	Description
Name	PARTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD1

Attribute	Description
Name	PARTADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD2

Attribute	Description
Name	PARTADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD3

Attribute	Description
Name	PARTADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTADD4

Attribute	Description

Name	PARTADD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTID

Attribute	Description
Name	PARTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Addr

Attribute	Description
Name	Party-Addr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Party-Limits

Attribute	Description
Name	Party-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,F,C,P</td></tr></table>

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,BILL_OS_AMT,AMT_PURCHASED,CNF_LIAB_AVAIL_AMT,UCNF_LIAB_AVAIL_AMT

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMBNKCOP

Attribute	Description
Name	REIMBNKCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVLETDATE

Attribute	Description

Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Doc-Clause

Attribute	Description
Name	Doc-Clause
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

INCOTRM

Attribute	Description
Name	INCOTRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Shipment

Attribute	Description
Name	Shipment
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPMRKS

Attribute	Description
Name	SHIPMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARSHIPINFO

Attribute	Description
Name	PARSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SHIPDTLS

Attribute	Description
Name	SHIPDTLS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Pay-Excep

Attribute	Description
Name	Pay-Excep
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PAYMSGDT

Attribute	Description
Name	PAYMSGDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONPAYMSGDT

Attribute	Description
Name	NONPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Pay-Fate

Attribute	Description
Name	Pay-Fate

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Acc-Excep

Attribute	Description
Name	Acc-Excep
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRCREQDFLG

Attribute	Description
Name	TRCREQDFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NONACCPAYMSGDT

Attribute	Description
Name	NONACCPAYMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROTFLG

Attribute	Description
Name	PROTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRACRECPART

Attribute	Description
Name	TRACRECPART
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCMSGDT

Attribute	Description
Name	ACCMSGDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Acc-Fate

Attribute	Description
Name	Acc-Fate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MANGENFLG

Attribute	Description
Name	MANGENFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVFTREQDFLG

Attribute	Description
Name	ADVFTREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

ADVFTMED

Attribute	Description
Name	ADVFTMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRVADVFTDT

Attribute	Description
Name	PRVADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NUMADVFTSNT

Attribute	Description
Name	NUMADVFTSNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTADVFTDT

Attribute	Description
Name	NXTADVFTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVFTRECPART

Attribute	Description
Name	ADVFTRECPART
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Disc

Attribute	Description
Name	Contract-Disc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DISCCD

Attribute	Description
Name	DISCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3500

TOP

DISCRESLFLG

Attribute	Description
Name	DISCRESLFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

DISCRESDT

Attribute	Description
Name	DISCRESDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISCRECDT

Attribute	Description
Name	DISCRECDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Reserve

Attribute	Description
Name	Contract-Reserve
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRCREQDFLG

Attribute	Description

Name	TRCREQDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,R

TOP

NUMTRCTOSENT

Attribute	Description
Name	NUMTRCTOSENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACMED

Attribute	Description
Name	TRACMED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACFREQ

Attribute	Description
Name	TRACFREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRACSRTDT

Attribute	Description
Name	TRACSRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVTRACDT

Attribute	Description
Name	PREVTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NUMTRSENT

Attribute	Description
Name	NUMTRSENT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEXTTRACDT

Attribute	Description
Name	NEXTTRACDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESRELDT

Attribute	Description
Name	RESRELDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCAPPDT

Attribute	Description
Name	DISCAPPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRACER_RECEIVER_TYP

Attribute	Description
Name	TRACER_RECEIVER_TYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDRESFLG

Attribute	Description
Name	UNDRESFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Roll-Pref

Attribute	Description
Name	Roll-Pref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDT

Attribute	Description
Name	BASEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEDTDESC

Attribute	Description
Name	BASEDTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

TNRDAYS

Attribute	Description
Name	TNRDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRNSDAYS

Attribute	Description
Name	TRNSDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDAYS

Attribute	Description
Name	MATDAYS
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTLIQDMOD

Attribute	Description
Name	INTLIQDMOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,I

TOP

FRMCALCDT

Attribute	Description
Name	FRMCALCDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOCALCDT

Attribute	**Description**	
Name	TOCALCDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BASEDTCOD

Attribute	**Description**	
Name	BASEDTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

Drafts

Attribute	**Description**	
Name	Drafts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	**Description**	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	**Description**

Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Invoice-Master

Attribute	Description
Name	Invoice-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INVCCY

Attribute	Description
Name	INVCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MARGIND

Attribute	Description
Name	MARGIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,A

TOP

MARG

Attribute	Description
Name	MARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ELGAMT

Attribute	Description
Name	ELGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGAMT

Attribute	Description
Name	MARGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Invoice-Details

Attribute	Description
Name	Invoice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INVCNO

Attribute	Description
Name	INVCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INVCDT

Attribute	Description
Name	INVCDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Insurance-Master

Attribute	Description
Name	Insurance-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSCOMPCOD

Attribute	Description
Name	INSCOMPCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSPOLNO

Attribute	Description
Name	INSPOLNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSCOMPNAM

Attribute	**Description**	
Name	INSCOMPNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN1

Attribute	**Description**	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	**Description**	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	**Description**	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELENO

Attribute	Description
Name	TELENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAXNO

Attribute	Description
Name	FAXNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Iccf-Calc-Dates

Attribute	Description
Name	Iccf-Calc-Dates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

INTFRMDT

Attribute	Description
Name	INTFRMDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTTODT

Attribute	Description
Name	INTTODT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Account-Master

Attribute	Description
Name	Account-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Pack-Credit

Attribute	Description
Name	Pack-Credit
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SEQNO

Attribute	Description

Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTCOD

Attribute	Description
Name	EVNTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STLAMT

Attribute	Description
Name	STLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Pack-Credit-Dtls

Attribute	Description
Name	Pack-Credit-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLACCNO

Attribute	Description
Name	CLACCNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LNKCCY

Attribute	Description
Name	LNKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

OUTSTAMT

Attribute	Description
Name	OUTSTAMT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVNTCOD

Attribute	**Description**	
Name	EVNTCOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Deferred-Chg-Comp-Details

Attribute	**Description**	
Name	Deferred-Chg-Comp-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LCREFNO

Attribute	**Description**	
Name	LCREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

AMT_TRANSFERRED

Attribute	Description
Name	AMT_TRANSFERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP_CCY

Attribute	Description
Name	COMP_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT_PAID

Attribute	Description
Name	AMT_PAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bctbs-Int-Chg-Calc

Attribute	Description
Name	Bctbs-Int-Chg-Calc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOA

Attribute	Description
Name	CONTREFNOA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTA

Attribute	Description
Name	COMPONENTA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STDTA

Attribute	Description
Name	STDTA
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCYA

Attribute	Description
Name	COMPCCYA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INTRATEA

Attribute	Description
Name	INTRATEA
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTBASISA

Attribute	Description
Name	INTBASISA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEA

Attribute	Description
Name	WAIVEA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INTAMOUNTA

Attribute	Description
Name	INTAMOUNTA
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENTB

Attribute	Description
Name	COMPONENTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYB

Attribute	Description
Name	COMPCCYB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTRATEB

Attribute	Description	
Name	INTRATEB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISB

Attribute	Description	
Name	INTBASISB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEB

Attribute	Description	
Name	WAIVEB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INTAMOUNTB

Attribute	Description	
Name	INTAMOUNTB	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPONENTC

Attribute	Description
Name	COMPONENTC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COMPCCYC

Attribute	Description
Name	COMPCCYC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTRATEC

Attribute	Description
Name	INTRATEC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTBASISC

Attribute	Description
Name	INTBASISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 3,6,0,1,2,4,5,7,8,9,-1,-2

TOP

WAIVEC

Attribute	Description
Name	WAIVEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INTAMOUNTC

Attribute	Description
Name	INTAMOUNTC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNOD

Attribute	Description
Name	CONTREFNOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTD

Attribute	Description
Name	COMPONENTD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPD

Attribute	Description
Name	INTCHGCOMPD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STDTD

Attribute	Description
Name	STDTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYD

Attribute	Description
Name	COMPCCYD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERD

Attribute	Description
Name	CHGPERD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISD

Attribute	Description
Name	INTBASISD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WAIVEDD

Attribute	Description
Name	WAIVEDD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTD

Attribute	Description
Name	CHGAMTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSD

Attribute	Description
Name	STATUSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOE

Attribute	Description
Name	CONTREFNOE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTE

Attribute	Description
Name	COMPONENTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

INTCHGCOMPE

Attribute	Description
Name	INTCHGCOMPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTE

Attribute	Description
Name	STDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYE

Attribute	Description
Name	COMPCCYE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERE

Attribute	Description
Name	CHGPERE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASISE

Attribute	Description
Name	INTBASISE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVEE

Attribute	Description
Name	WAIVEE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

CHGAMTE

Attribute	Description
Name	CHGAMTE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUSE

Attribute	Description
Name	STATUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREFNOF

Attribute	Description
Name	CONTREFNOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COMPONENTF

Attribute	Description
Name	COMPONENTF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

INTCHGCOMPF

Attribute	Description
Name	INTCHGCOMPF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STDTF

Attribute	Description
Name	STDTF
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPCCYF

Attribute	Description
Name	COMPCCYF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGPERF

Attribute	Description
Name	CHGPERF
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTBASISF

Attribute	**Description**	
Name	INTBASISF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVEF

Attribute	**Description**	
Name	WAIVEF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CHGAMTF

Attribute	**Description**	
Name	CHGAMTF	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUSF

Attribute	**Description**	
Name	STATUSF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPDESCA

Attribute	Description
Name	COMPDESCA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCB

Attribute	Description
Name	COMPDESCB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCC

Attribute	Description
Name	COMPDESCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCD

Attribute	Description
Name	COMPDESCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

COMPDESCE

Attribute	Description
Name	COMPDESCE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COMPDESCF

Attribute	Description
Name	COMPDESCF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Contract-Multitnr

Attribute	Description
Name	Contract-Multitnr
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SERIALNUM

Attribute	Description
Name	SERIALNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASDATE

Attribute	Description
Name	BASDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASEDATE_CODE

Attribute	Description
Name	BASEDATE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

VALUDATE

Attribute	Description
Name	VALUDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TNOR

Attribute	Description
Name	TNOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRANSTDAYS

Attribute	Description
Name	TRANSTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MATDAT

Attribute	Description
Name	MATDAT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPLITPCT

Attribute	Description
Name	SPLITPCT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BILLAMNT

Attribute	Description
Name	BILLAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTAMT

Attribute	Description
Name	DISCOUNTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REBATAMT

Attribute	Description
Name	REBATAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXCRATE

Attribute	Description
Name	EXCRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNTDAMT

Attribute	Description
Name	DISCOUNTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTNAMT

Attribute	Description
Name	LIQDTNAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDTDAMT

Attribute	Description
Name	LIQDTDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMCALCDATE

Attribute	Description
Name	FRMCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOCALCDATE

Attribute	Description
Name	TOCALCDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRDFNDSTS

Attribute	Description
Name	USRDFNDSTS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STSAFDATE

Attribute	Description
Name	STSAFDATE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UNDERPROTEST

Attribute	Description
Name	UNDERPROTEST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PROTESTDATE

Attribute	Description
Name	PROTESTDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Tax

Attribute	**Description**	
Name	Tax	
Datatype		
Description	Tax Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details

Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description

Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,C,P

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTSEQNO

Attribute	Description

Name	SPTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	Description
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	Description
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NEGORATE

Attribute	**Description**	
Name	NEGORATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGO_REF_NO

Attribute	**Description**	
Name	NEGO_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Bcpref

Attribute	**Description**	
Name	Bcpref	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	Number
Description	Indicates the Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR

Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LOANVALDATE

Attribute	Description	
Name	LOANVALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXCHRATE

Attribute	Description	
Name	ORGEXCHRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Effective-Intrate-Det

Attribute	**Description**	
Name	Effective-Intrate-Det	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EFFECTDT

Attribute	**Description**	
Name	EFFECTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

IRR

Attribute	**Description**	
Name	IRR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Intrest

Attribute	**Description**
Name	Intrest
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEPOSITRTCD

Attribute	Description
Name	DEPOSITRTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Intrest-View

Attribute	Description
Name	Intrest-View

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRUALCCY

Attribute	Description
Name	ACCRUALCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PENALTYTYP

Attribute	Description
Name	PENALTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWINMASTER

Attribute	Description
Name	SHOWINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description
Name	CUSTMARGIN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	**Description**	
Name	UNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

NOINTPERIOD

Attribute	Description
Name	NOINTPERIOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PESN

Attribute	Description
Name	PESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTCALC

Attribute	Description
Name	AMTCALC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

Uicolumns

Attribute	Description
Name	Uicolumns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcfx-Details

Attribute	Description
Name	Bcfx-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FXREFNO

Attribute	Description
Name	FXREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TFAMT

Attribute	Description
Name	TFAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TFRATE

Attribute	Description
Name	TFRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Loanaccdet

Attribute	Description
Name	Loanaccdet

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTFIN

Attribute	Description
Name	AMTFIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description

Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.4.BC-CloseContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *Taxes*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Collateral-details*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Linkages*
        - *CONREFNO*

LATEVNSEQNO

Misdetails

CONREFNO

Settlements

CONREFNO

LATEVNSEQNO

Adice

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Effective-Int-Rate

CONREFNO

LATEVNSEQNO

Intrest

CONREFNO

LATEVNSEQNO

Bcfx

BILLREFNO

ESN

Loanacc

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Charges

Attribute	Description

Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Effective-Int-Rate

Attribute	Description
Name	Effective-Int-Rate
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest

Attribute	Description
Name	Intrest

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcfx

Attribute	Description
Name	Bcfx
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLREFNO

Attribute	Description
Name	BILLREFNO
Datatype	String
Description	Indicates Bill Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Loanacc

Attribute	Description
Name	Loanacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.CloseDocArrival

Close BC Document Arrival

2.65.1.BC-CloseDocArrival-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*

REIM_BANK
DOCREF
DOCDATE
COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	**Description**	
Name	MAKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVLETDATE

Attribute	**Description**	
Name	COVLETDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FRSTMAILORG

Attribute	**Description**	
Name	FRSTMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

SECMAILORG

Attribute	**Description**	
Name	SECMAILORG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCTYPE

Attribute	**Description**	
Name	DOCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHRSHIPINFO

Attribute	**Description**	
Name	OTHRSHIPINFO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

GOODSCODE

Attribute	**Description**	
Name	GOODSCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

GOODSDESC

Attribute	**Description**	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

TRNSSHIPFLAG

Attribute	**Description**	
Name	TRNSSHIPFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

2.65.2.BC-CloseDocArrival-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Contract-Details-IO
CONREFNO
Adice

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.65.3.BC-CloseDocArrival-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *CONREFNO*
    - *LATEVNSEQNO*
    - *MAKER*
    - *MAKDTTIME*
    - *CHKR*
    - *CHKDTTIME*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *BRNCD*
    - *Doc-Details*
      - *DOCODE*
      - *DOCDESC*
      - *DOCSLNO*
      - *FRSTMAILCOP*
      - *SECMAILCOP*
      - *REIM_BANK*
      - *DOCREF*
      - *DOCDATE*

COVLETREF
COVLETDATE
FRSTMAILORG
SECMAILORG
DOCTYPE
Doc-Clauses
CLAUSECODE
CLAUSEDESC
Goods-Details
BCREF
ESN
SHPMNTMARK
DESFROM
DESTO
CARNAM
SHIPMENT_DETAILS
LATSHIPDT
SHIPDT
ARRVDT
OTHRSHIPINFO
GOODSCODE
GOODSDESC
TRNSSHIPFLAG
PARTIALSHPMNT
Adice
ADV_CODE
SUPRESS
PRIORITY
PRTY
MEDIUM
PRTYID
PRTYNAME
Fft
FFT_CODE
FFTTXT
Ins
INSCD
INSTXT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description

Name	Contract-Details-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,A</td></tr></table>

TOP

BRNCD

Attribute	Description

Name	BRNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Doc-Details

Attribute	Description
Name	Doc-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCODE

Attribute	Description
Name	DOCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DOCSLNO

Attribute	Description
Name	DOCSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILCOP

Attribute	Description
Name	FRSTMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECMAILCOP

Attribute	Description
Name	SECMAILCOP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REIM_BANK

Attribute	Description
Name	REIM_BANK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCREF

Attribute	Description
Name	DOCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCDATE

Attribute	Description
Name	DOCDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COVLETREF

Attribute	Description
Name	COVLETREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVLETDATE

Attribute	Description
Name	COVLETDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FRSTMAILORG

Attribute	Description
Name	FRSTMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

SECMAILORG

Attribute	Description
Name	SECMAILORG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Doc-Clauses

Attribute	Description
Name	Doc-Clauses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECODE

Attribute	Description
Name	CLAUSECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREF

Attribute	Description
Name	BCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

DESFROM

Attribute	Description
Name	DESFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DESTO

Attribute	Description
Name	DESTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CARNAM

Attribute	Description
Name	CARNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SHIPMENT_DETAILS

Attribute	Description
Name	SHIPMENT_DETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPDT

Attribute	Description
Name	SHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ARRVDT

Attribute	Description
Name	ARRVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHRSHIPINFO

Attribute	Description
Name	OTHRSHIPINFO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

GOODSCODE

Attribute	Description
Name	GOODSCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

TRNSSHIPFLAG

Attribute	Description
Name	TRNSSHIPFLAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADV_CODE

Attribute	Description
Name	ADV_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	Indicates Supress Y for Yes;N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates Priority High : 1 Normal : 2 Low : 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	Indicates Party Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

Fft

Attribute	Description
Name	Fft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFT_CODE

Attribute	Description
Name	FFT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Ins

Attribute	Description
Name	Ins

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.4.BC-CloseDocArrival-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *Adice*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Adice

Attribute	Description
Name	Adice
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.66.CreateAmendConfirm

Creation of BC Amendment Confirmation

2.66.1.BC-CreateAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

ESN
TXNSTAT
AUTHSTAT
EVENTDESC
Amendadv
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft
- *FFTCD*
- *FFTTXT*

Amendins
- *INSCD*
- *INSTXT*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Intrest
- *CONREFNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*
  - *SPREAD*
  - *STATUS*

ACRDAMT
WAIVER
ACRREQRD
ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP

PENALTYTYP
SHOWINMASTER
MAXRT
MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT

Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Transaction Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,K,V,S,A,H</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Authorization status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

SPREAD

Attribute	**Description**	
Name	SPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STATUS

Attribute	**Description**	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description

Name	PENATYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	Description	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	Description	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	Description	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	Description	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPERIOD

Attribute	**Description**	
Name	NOINTPERIOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN

Attribute	**Description**
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTCALC

Attribute	**Description**	
Name	AMTCALC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description	Includes the Charges Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.66.2.BC-CreateAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-IO*
    - *CONREFNO*
    - *BILLAMT*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *EVENTDESC*
    - *Amendadv*
      - *PRTY*
      - *MEDIUM*
      - *ADVCD*
      - *SUPRESS*
      - *PRIORITY*
    - *Amendfft*

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*

RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5

RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*

REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
LATEVNSEQNO
Intrest-Details
INTBASIS
RATE
RATECD
ACRDAMT
WAIVER
ACRREQRD
RTYP
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
NOUNIT
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
COMPONENT
EVNT
Intrest-View
INTBASIS
ACQUIRDAMT
WAIVER
ACCREQUIRD
RTTYP
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
RATCD
DISACCRAPP
VALDT
TRDT
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER

DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Taxes
CONREFNO
LATEVNSEQNO
Tax
WAIVER
Tax-Details
Rule-Details

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRVALDT

Attribute	**Description**	
Name	DRVALDT	
Datatype	Date	
Description	Indicates Debit Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VALDT

Attribute	**Description**	
Name	VALDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCREFNO

Attribute	**Description**	
Name	BCREFNO	
Datatype	String	
Description	Indicates BC Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description	Letters Of Credit Contract reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP

Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String

Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	Description
Name	Intrest
Datatype	
Description	Indicates Interest Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,S</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,L,M</td></tr></table>

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RTTYP

Attribute	Description	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

RESETTENOR

Attribute	Description	
Name	RESETTENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BORROW_LEND_IND

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M,

TOP

RATECALCTYP

Attribute	Description	
Name	RATECALCTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	

Description	Includes Rule details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.66.3.BC-CreateAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amendmaster-Full*
    - *CONREFNO*
    - *BILLDUEAMT*
    - *BILLAMT*
    - *CUSTID*
    - *BILLCCY*
    - *CR_VALUE_DATE*
    - *DRVALDT*
    - *VALDT*
    - *MATDT*
    - *BCREFNO*
    - *CONTREFNO*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *ESN*
    - *TXNSTAT*
    - *AUTHSTAT*

EVENTDESC

Amendadv

- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *ADVCD*
- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*

PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*

ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Intrest
CONREFNO
Intrest-Details
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACRDAMT
WAIVER
ACRREQRD

ACQRCCY
RTYP
PENATYTYP
SHOWNINMASTER
MAXRT
MINRT
RESTTENOR
BORROWLENDID
RTCALCTYP
CUSTMARG
LEVELNO
BULKAMTFLG
DEPOSITRTCD
NOUNIT
NOUNITS
RATCDUSGE
DISCACCAPP
DENOMITORBASIS
BASIS366
NOINTPRE
MINSPRD
MAXSPRD
MARGIN
COMPONENT
AMT
CHANGEDURAMND
CCY
EVNT
EVNTDESC
COMPDESC
Intrest-View
INTBASIS
RATE
RATECD
SPREAD
STATUS
ACQUIRDAMT
WAIVER
ACCREQUIRD
ACCRUALCCY
RTTYP
PENALTYTYP
SHOWINMASTER
MAXRT

MINRT
RESETTENOR
BORROW_LEND_IND
RATECALCTYP
CUSTMARGIN
LEVELNO
BULKAMTFLAG
DEPOSITASRTCD
UNIT
NOUNITS
RATCD
DISACCRAPP
DENOMINATORBASIS
BASIS366
NOINTPERIOD
MINSPREAD
MAXSPREAD
MARGIN
COMPONENT
CONREFNO
VALDT
TRDT
AMT
CHNGDRNGAMD
CCY
EVENT
ESN
PESN
AMTCALC
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amendmaster-Full

Attribute	Description
Name	Amendmaster-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLDUEAMT

Attribute	Description
Name	BILLDUEAMT
Datatype	Number
Description	Indicates Bill Due Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BILLCCY

Attribute	Description
Name	BILLCCY
Datatype	String
Description	Indicates Bill Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	User id of the user who saved the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	The date and time at which the Transaction saved
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	User id of the user who authorized the contract
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	The date and time at which the Transaction Authorized

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSCD

Attribute	Description
Name	INSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description

Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Intrest-Details

Attribute	**Description**	
Name	Intrest-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	**Description**	
Name	INTBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATE

Attribute	**Description**

Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACRDAMT

Attribute	Description
Name	ACRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRREQRD

Attribute	Description
Name	ACRREQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,S

TOP

PENATYTYP

Attribute	Description
Name	PENATYTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SHOWNINMASTER

Attribute	Description
Name	SHOWNINMASTER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEVELNO

Attribute	Description
Name	LEVELNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BULKAMTFLG

Attribute	Description
Name	BULKAMTFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITRTCD

Attribute	**Description**	
Name	DEPOSITRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NOUNIT

Attribute	**Description**	
Name	NOUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M,Y

TOP

NOUNITS

Attribute	**Description**	
Name	NOUNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,I

TOP

BASIS366

Attribute	Description
Name	BASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,Y,D

TOP

NOINTPRE

Attribute	Description
Name	NOINTPRE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MARGIN

Attribute	Description
Name	MARGIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHANGEDURAMND

Attribute	Description
Name	CHANGEDURAMND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Intrest-View

Attribute	Description
Name	Intrest-View
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

SPREAD

Attribute	Description
Name	SPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRUALCCY

Attribute	**Description**	
Name	ACCRUALCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

PENALTYTYP

Attribute	**Description**	
Name	PENALTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHOWINMASTER

Attribute	**Description**	
Name	SHOWINMASTER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRT

Attribute	Description
Name	MINRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESETTENOR

Attribute	Description
Name	RESETTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,L,M,

TOP

RATECALCTYP

Attribute	Description
Name	RATECALCTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

CUSTMARGIN

Attribute	**Description**	
Name	CUSTMARGIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEVELNO

Attribute	**Description**	
Name	LEVELNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BULKAMTFLAG

Attribute	**Description**	
Name	BULKAMTFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEPOSITASRTCD

Attribute	**Description**	
Name	DEPOSITASRTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UNIT

Attribute	Description
Name	UNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NOUNITS

Attribute	Description
Name	NOUNITS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,P</td></tr></table>

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DENOMINATORBASIS

Attribute	Description
Name	DENOMINATORBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BASIS366

Attribute	**Description**	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

NOINTPERIOD

Attribute	**Description**	
Name	NOINTPERIOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MARGIN

Attribute	**Description**
Name	MARGIN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHNGDRNGAMD

Attribute	Description
Name	CHNGDRNGAMD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PESN

Attribute	**Description**	
Name	PESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTCALC

Attribute	**Description**	
Name	AMTCALC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description	Includes the Charges Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	Includes the Taxes details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description

Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.66.4.BC-CreateAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amendmaster-PK*
      - *CONREFNO*
    - *Amendmaster-IO*
      - *CONREFNO*
      - *BILLAMT*
      - *CR_VALUE_DATE*
      - *DRVALDT*
      - *VALDT*
      - *BCREFNO*
      - *CONTREFNO*
      - *ESN*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *EVENTDESC*
      - *Amendadv*
        - *PRTY*
        - *MEDIUM*
        - *ADVCD*

- *SUPRESS*
- *PRIORITY*

Amendfft

- *FFTCD*
- *FFTTXT*

Amendins

- *INSCD*
- *INSTXT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*

RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5

BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*

- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Intrest

- *CONREFNO*
- *LATEVNSEQNO*
- *Intrest-Details*
  - *INTBASIS*
  - *RATE*
  - *RATECD*
  - *ACRDAMT*
  - *WAIVER*
  - *ACRREQRD*
  - *RTYP*
  - *RESTTENOR*
  - *BORROWLENDID*
  - *RTCALCTYP*
  - *CUSTMARG*
  - *NOUNIT*
  - *RATCDUSGE*
  - *DISCACCAPP*
  - *DENOMITORBASIS*
  - *BASIS366*
  - *COMPONENT*
  - *EVNT*
- *Intrest-View*
  - *INTBASIS*
  - *ACQUIRDAMT*
  - *WAIVER*
  - *ACCREQUIRD*
  - *RTTYP*
  - *RESETTENOR*
  - *BORROW_LEND_IND*
  - *RATECALCTYP*
  - *RATCD*
  - *DISACCRAPP*
  - *VALDT*
  - *TRDT*

Charges

- *LATEVNSEQNO*

CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Taxes
CONREFNO
LATEVNSEQNO
Tax
WAIVER
Tax-Details
Rule-Details
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amendmaster-PK

Attribute	Description
Name	Amendmaster-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Amendmaster-IO

Attribute	Description
Name	Amendmaster-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BILLAMT

Attribute	Description
Name	BILLAMT
Datatype	Number
Description	Indicates Bill Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CR_VALUE_DATE

Attribute	Description
Name	CR_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRVALDT

Attribute	Description
Name	DRVALDT
Datatype	Date
Description	Indicates Debit Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates BC Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Letters Of Credit Contract reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String

Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates Event Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Amendadv

Attribute	Description
Name	Amendadv
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADVCD

Attribute	**Description**
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,N

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Amendfft

Attribute	Description
Name	Amendfft
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

FFTTXT

Attribute	Description
Name	FFTTXT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

TOP

Amendins

Attribute	Description
Name	Amendins
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSCD

Attribute	Description
Name	INSCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

INSTXT

Attribute	Description
Name	INSTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	Description	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description

Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String

Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3

Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description

Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Intrest

Attribute	**Description**	
Name	Intrest	
Datatype		
Description	Indicates Interest Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Intrest-Details

Attribute	Description
Name	Intrest-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

ACRDAMT

Attribute	**Description**	
Name	ACRDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRREQRD

Attribute	**Description**	
Name	ACRREQRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RTYP

Attribute	Description
Name	RTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,S

TOP

RESTTENOR

Attribute	Description
Name	RESTTENOR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BORROWLENDID

Attribute	Description
Name	BORROWLENDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,B,L,M

TOP

RTCALCTYP

Attribute	Description
Name	RTCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,D,I,R

TOP

CUSTMARG

Attribute	Description
Name	CUSTMARG

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOUNIT

Attribute	Description
Name	NOUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M,Y

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,P

TOP

DISCACCAPP

Attribute	Description
Name	DISCACCAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DENOMITORBASIS

Attribute	Description
Name	DENOMITORBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,I

TOP

BASIS366

Attribute	Description	
Name	BASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

COMPONENT

Attribute	Description	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Intrest-View

Attribute	Description	
Name	Intrest-View	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACQUIRDAMT

Attribute	Description
Name	ACQUIRDAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCREQUIRD

Attribute	Description
Name	ACCREQUIRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,S

TOP

RESETTENOR

Attribute	**Description**	
Name	RESETTENOR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BORROW_LEND_IND

Attribute	**Description**	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,L,M,

TOP

RATECALCTYP

Attribute	**Description**	
Name	RATECALCTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,D,I,R

TOP

RATCD

Attribute	**Description**	
Name	RATCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,P

TOP

DISACCRAPP

Attribute	Description
Name	DISACCRAPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxes

Attribute	**Description**	
Name	Taxes	
Datatype		
Description	Includes the Taxes details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.CreateBCDisc

Input of Bills and Collections Discrepancy Code

2.67.1.BC-CreateBCDisc-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-Full*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullRequest

TOP

Disc-Master-Full

Attribute	Description

Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.67.2.BC-CreateBCDisc-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Disc-Master-IO*
    - *DISCCODE*
    - *LANGUAGECODE*
    - *DISCDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about IORequest

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.67.3.BC-CreateBCDisc-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*

Disc-Master-Full
DISCCODE
LANGUAGECODE
DISCDESC
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String

Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE

Datatype	String
Description	Indicates the Language Code.
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.4.BC-CreateBCDisc-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Disc-Master-PK*
      - *DISCCODE*
      - *LANGUAGECODE*
    - *Disc-Master-IO*
      - *DISCCODE*
      - *LANGUAGECODE*
      - *DISCDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE
FIELD_VALUE
VAL_TYPE
Disc-Master-Full
DISCCODE
LANGUAGECODE
DISCDESC
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Includes the FCUBS Header Details.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This.xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Disc-Master-PK

Attribute	Description
Name	Disc-Master-PK
Datatype	
Description	Includes the Discrepancy Master primary key Details.

TOP

DISCCODE

Attribute	**Description**	
Name	DISCCODE	
Datatype	String	
Description	Indicates the Discrepancy Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Disc-Master-IO

Attribute	Description
Name	Disc-Master-IO
Datatype	
Description	Includes the Discrepancy Master IO Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISCDESC

Attribute	Description
Name	DISCDESC

Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Auth.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Disc-Master-Full

Attribute	Description
Name	Disc-Master-Full
Datatype	
Description	Includes the Discrepancy Master Full Details.

TOP

DISCCODE

Attribute	Description
Name	DISCCODE
Datatype	String
Description	Indicates the Discrepancy Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LANGUAGECODE

Attribute	Description
Name	LANGUAGECODE
Datatype	String
Description	Indicates the Language Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISCDESC

Attribute	Description
Name	DISCDESC
Datatype	String
Description	Indicates the Discrepancy description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Bills and Collections Service
[August] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.