

Gateway Documentation - Collections Service  
Oracle FLEXCUBE Universal Banking  
Release FCUBS\_12.0.87.1.0  
[August] [2014]



# Table Of Contents

---

<b>1. BACKGROUND</b>	<b>1</b>
<b>2. FCUBSCNService</b>	<b>2</b>
<b>2.1. CreateCollectionInteraction</b>	<b>2</b>
2.1.1. <i>CN-CreateCollectionInteraction-Req-Full-MSG.xsd</i>	2
2.1.2. <i>CN-CreateCollectionInteraction-Req-IO-MSG.xsd</i>	25
2.1.3. <i>CN-CreateCollectionInteraction-Res-Full-MSG.xsd</i>	38
2.1.4. <i>CN-CreateCollectionInteraction-Res-PK-MSG.xsd</i>	62
<b>2.2. DeleteCollectionInteraction</b>	<b>77</b>
2.2.1. <i>CN-DeleteCollectionInteraction-Req-Full-MSG.xsd</i>	77
2.2.2. <i>CN-DeleteCollectionInteraction-Req-IO-MSG.xsd</i>	100
2.2.3. <i>CN-DeleteCollectionInteraction-Res-PK-MSG.xsd</i>	106
2.2.4. <i>CN-DeleteCollectionInteraction-Res-Full-MSG.xsd</i>	115
<b>2.3. AuthorizeCollectionInteraction</b>	<b>139</b>
2.3.1. <i>CN-AuthorizeCollectionInteraction-Res-PK-MSG.xsd</i>	139
2.3.2. <i>CN-AuthorizeCollectionInteraction-Req-Full-MSG.xsd</i>	148
2.3.3. <i>CN-AuthorizeCollectionInteraction-Req-IO-MSG.xsd</i>	171
2.3.4. <i>CN-AuthorizeCollectionInteraction-Res-Full-MSG.xsd</i>	177
<b>2.4. QueryPlanActivity</b>	<b>201</b>
2.4.1. <i>CN-QueryPlanActivity-Req-IO-MSG.xsd</i>	201
2.4.2. <i>CN-QueryPlanActivity-Res-Full-MSG.xsd</i>	212

# 1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

**1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS

**2. Outbound application integration**– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSCNService of CN-Module

## 2.FCUBSCNService

Collections ServiceCollections Service

### 2.1.CreateCollectionInteraction

CreateCollectionInteraction

#### 2.1.1.CN-CreateCollectionInteraction-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

PROCESS\_STAGE  
TOTPTPAMT  
ACTION\_CODE  
RESLT  
ACTINDT  
DELREASON  
NEXTACTION  
RSLTDT  
NXTACTIONDT  
COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB  
Asset  
    LOANREFNO  
    ASSETQUTPRINCIPAL  
    ASSETCCY  
    ASSETBRN  
    ASSETTOTALOVD  
    ASSETSCHOVD  
    ASSETUDETSTAT  
    ASSETAMT  
    PRINC\_OVERDUE  
    MATURITY\_DATE  
    NO\_OF\_DAYS\_DELINQUENT  
    INT\_OVERDUE  
    ASSET\_INT\_RATE  
    COLLTYPE  
Ptp  
    PTPAMT  
    PTPDT  
    AMTPAID  
    PTPCHARGE  
    TAGCCY  
    PTPSTAT  
Footer  
    CONREFNO  
    MAKER  
    MAKDTTIME  
    CHKR  
    CHKDTTIME

EVNTSEQNO

CONSTAT

AUTHSTATS

Legal

ACTION\_REF\_NO

COLL\_REF\_NO

LOCATION

DT\_LAST\_HEARING

NEXTACTION

NEXT\_HEARING\_DT

LAWYER\_NAME

SEQ\_NO

PROCEDNG\_SUMM

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Creation Full Request details of Collections module

[TOP](#)

## CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CLCTNREFNO

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)**RECORD\_DATE**

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ISN**

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**AGNCYNAME**

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**CUSTOMER**

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_NAME1**

Attribute	Description	
Name	CUSTOMER_NAME1	

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTSUBSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CLCTNESN

<b>Attribute</b>	<b>Description</b>	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EXTREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## RECORGN

<b>Attribute</b>	<b>Description</b>	
Name	RECORGN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,S,U

**PROCESS\_STAGE**

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,R,E,A

**TOTPTPAMT**

Attribute	Description	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ACTION\_CODE**

Attribute	Description	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**RESLT**

Attribute	Description	
Name	RESLT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**ACTINDT**

Attribute	Description
Name	ACTINDT

Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DELREASON

<b>Attribute</b>	<b>Description</b>	
Name	DELREASON	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RSLTDT

<b>Attribute</b>	<b>Description</b>	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NXTACTIONDT

<b>Attribute</b>	<b>Description</b>	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NLS\_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL

<b>Attribute</b>	<b>Description</b>
Name	ASSETQUTPRINCIPAL

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETCCY

<b>Attribute</b>	<b>Description</b>	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ASSETBRN

<b>Attribute</b>	<b>Description</b>	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

<b>Attribute</b>	<b>Description</b>	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

<b>Attribute</b>	<b>Description</b>	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

## ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PRINC\_OVERDUE

Attribute	Description	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MATURITY\_DATE

Attribute	Description	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NO\_OF\_DAYS\_DELINQUENT

Attribute	Description	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## INT\_OVERDUE

Attribute	Description	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSET\_INT\_RATE

Attribute	Description	
Name	ASSET_INT_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## COLLTYPE

Attribute	Description	
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PTPCHARGE

Attribute	Description	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>	
Name	Footer	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHKDTIME

Attribute	Description	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,A,C

[TOP](#)

## AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

<b>Attribute</b>	<b>Description</b>	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## LOCATION

<b>Attribute</b>	<b>Description</b>	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15



[TOP](#)**DT\_LAST\_HEARING**

Attribute	Description	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**NEXTACTION**

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**NEXT\_HEARING\_DT**

Attribute	Description	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**LAWYER\_NAME**

Attribute	Description	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**SEQ\_NO**

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## 2.1.2.CN-CreateCollectionInteraction-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-IO*

*CLCTNREFNO*

*ISN*

*CLCTNESN*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*

*NEXTACTION*

*RSLTDT*

*NXTACTIONDT*

*COMNTS*

*NLS\_HR*

*OFSMINS*

*CUSTMAIL*

*MEDIA*

*INTRACTIONPLACE*

*CUSTMOB*

*Ptp*

[PTPAMT](#)  
[PTPDT](#)  
[Legal](#)  
[LOCATION](#)  
[DT\\_LAST\\_HEARING](#)  
[NEXTACTION](#)  
[NEXT\\_HEARING\\_DT](#)  
[LAWYER\\_NAME](#)  
[SEQ\\_NO](#)  
[PROCEDNG\\_SUMM](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)



## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Creation IO Request details of Collections module

[TOP](#)

## CLCTNREFNO

Attribute	Description				
Name	CLCTNREFNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

[TOP](#)

## ISN

Attribute	Description				
Name	ISN				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

[TOP](#)

## CLCTNESN

Attribute	Description				
Name	CLCTNESN				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

[TOP](#)

## ACTION\_CODE

Attribute	Description				
Name	ACTION_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## RESLT

Attribute	Description				
Name	RESLT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## ACTINDT

Attribute	Description				
Name	ACTINDT				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DELREASON

Attribute	Description				
Name	DELREASON				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## NEXTACTION

Attribute	Description
Name	NEXTACTION
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RSLTDT

<b>Attribute</b>	<b>Description</b>	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NXTACTIONDT

<b>Attribute</b>	<b>Description</b>	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## COMNTS

<b>Attribute</b>	<b>Description</b>	
Name	COMNTS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## NLS\_HR

<b>Attribute</b>	<b>Description</b>	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## OFSMINS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	OFSMINS	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CUSTMAIL

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MEDIA

<b>Attribute</b>	<b>Description</b>	
Name	MEDIA	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**Ptp**

Attribute	Description	
Name	Ptp	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**PTPAMT**

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PTPDT**

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**Legal**

Attribute	Description	
Name	Legal	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**LOCATION**

Attribute	Description	
Name	LOCATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

<b>Attribute</b>	<b>Description</b>	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

<b>Attribute</b>	<b>Description</b>	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## SEQ\_NO

<b>Attribute</b>	<b>Description</b>
Name	SEQ_NO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

### 2.1.3.CN-CreateCollectionInteraction-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

*PROCESS\_STAGE*

*TOTPTPAMT*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*



NEXTACTION  
RSLTDT  
NXTACTIONDT  
COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB  
Asset  
    LOANREFNO  
    ASSETQUTPRINCIPAL  
    ASSETCCY  
    ASSETBRN  
    ASSETTOTALOVD  
    ASSETSCHOVD  
    ASSETUDETSTAT  
    ASSETAMT  
    PRINC\_OVERDUE  
    MATURITY\_DATE  
    NO\_OF\_DAYS\_DELINQUENT  
    INT\_OVERDUE  
    ASSET\_INT\_RATE  
    COLLTYPE  
Ptp  
    PTPAMT  
    PTPDT  
    AMTPAID  
    PTPCHARGE  
    TAGCCY  
    PTPSTAT  
Footer  
    CONREFNO  
    MAKER  
    MAKDTTIME  
    CHKR  
    CHKDTTIME  
    EVNTSEQNO  
    CONSTAT  
    AUTHSTATS  
Legal  
    ACTION\_REF\_NO  
    COLL\_REF\_NO

LOCATION  
 DT\_LAST\_HEARING  
 NEXTACTION  
 NEXT\_HEARING\_DT  
 LAWYER\_NAME  
 SEQ\_NO  
 PROCEDNG\_SUMM  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Creation Full Response details of Collections module

[TOP](#)

## CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CLCTNREFNO

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## RECORD\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## AGNCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTOMER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_NAME1



Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

## RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,S,U

[TOP](#)

## PROCESS\_STAGE

<b>Attribute</b>	<b>Description</b>	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	I,R,E,A

[TOP](#)

## TOTPTPAMT

<b>Attribute</b>	<b>Description</b>	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ACTION\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RESLT

<b>Attribute</b>	<b>Description</b>	
Name	RESLT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NXTACTIONDT

Attribute	Description	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NLS\_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETCCY

Attribute	Description	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ASSETUDETSTAT**

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**ASSETAMT**

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PRINC\_OVERDUE**

Attribute	Description	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**MATURITY\_DATE**

Attribute	Description	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**NO\_OF\_DAYS\_DELINQUENT**

Attribute	Description	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**INT\_OVERDUE**

Attribute	Description	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ASSET\_INT\_RATE**

Attribute	Description	
Name	ASSET_INT_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**COLLTYPE**

Attribute	Description	
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

**Ptp**

Attribute	Description	
Name	Ptp	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**PTPAMT**

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPDT

<b>Attribute</b>	<b>Description</b>	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMTPAID

<b>Attribute</b>	<b>Description</b>	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPCHARGE

<b>Attribute</b>	<b>Description</b>	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TAGCCY

<b>Attribute</b>	<b>Description</b>	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PTPSTAT

<b>Attribute</b>	<b>Description</b>	
Name	PTPSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>	
Name	Footer	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**CHKR**

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHKDTIME**

Attribute	Description	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**EVNTSEQNO**

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CONSTAT**

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,A,C

**AUTHSTATS**

Attribute	Description
Name	AUTHSTATS

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

<b>Attribute</b>	<b>Description</b>	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## LOCATION

<b>Attribute</b>	<b>Description</b>	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

<b>Attribute</b>	<b>Description</b>	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

<b>Attribute</b>	<b>Description</b>	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## SEQ\_NO

<b>Attribute</b>	<b>Description</b>
Name	SEQ_NO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.1.4.CN-CreateCollectionInteraction-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ISN*

*Main-IO*

*CLCTNREFNO*

*ISN*

*CLCTNESN*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*

*NEXTACTION*

*RSLTDT*

*NXTACTIONDT*

*COMNTS*

*NLS\_HR*

*OFSMINS*

*CUSTMAIL*

*MEDIA*



INTRACTIONPLACE

CUSTMOB

Ptp

PTPAMT

PTPDT

Legal

LOCATION

DT\_LAST\_HEARING

NEXTACTION

NEXT\_HEARING\_DT

LAWYER\_NAME

SEQ\_NO

PROCEDNG\_SUMM

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute	Description
Name	NAME

Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Creation PK Response details of Collections module

[TOP](#)

## ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	

Description	It indicates Collection Interaction Creation IO Response details of Collections module
-------------	--

[TOP](#)

## CLCTNREFNO

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ACTION\_CODE

Attribute	Description	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RESLT

Attribute	Description	
Name	RESLT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NXTACTIONDT

<b>Attribute</b>	<b>Description</b>	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## COMNTS

<b>Attribute</b>	<b>Description</b>	
Name	COMNTS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## NLS\_HR

<b>Attribute</b>	<b>Description</b>	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## OFSMINS

<b>Attribute</b>	<b>Description</b>	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CUSTMAIL

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMAIL	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MEDIA

<b>Attribute</b>	<b>Description</b>	
Name	MEDIA	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Ptp

<b>Attribute</b>	<b>Description</b>	
Name	Ptp	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Legal

Attribute	Description	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## LOCATION

Attribute	Description	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

Attribute	Description	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**NEXTACTION**

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**NEXT\_HEARING\_DT**

Attribute	Description	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**LAWYER\_NAME**

Attribute	Description	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

**SEQ\_NO**

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PROCEDNG\_SUMM**

Attribute	Description	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.DeleteCollectionInteraction

DeleteCollectionInteraction

### 2.2.1.CN-DeleteCollectionInteraction-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

*PROCESS\_STAGE*

*TOTPTPAMT*

*ACTION\_CODE*

RESLT  
ACTINDT  
DELREASON  
NEXTACTION  
RSLTDT  
NXTACTIONDT  
COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB  
Asset  
    LOANREFNO  
    ASSETQUTPRINCIPAL  
    ASSETCCY  
    ASSETBRN  
    ASSETTOTALOVD  
    ASSETSCHOVD  
    ASSETUDETSTAT  
    ASSETAMT  
    PRINC\_OVERDUE  
    MATURITY\_DATE  
    NO\_OF\_DAYS\_DELINQUENT  
    INT\_OVERDUE  
    ASSET\_INT\_RATE  
    COLLTYPE  
Ptp  
    PTPAMT  
    PTPDT  
    AMTPAID  
    PTPCHARGE  
    TAGCCY  
    PTPSTAT  
Footer  
    CONREFNO  
    MAKER  
    MAKDTTIME  
    CHKR  
    CHKDTTIME  
    EVNTSEQNO  
    CONSTAT  
    AUTHSTATS



Legal

*ACTION\_REF\_NO*  
*COLL\_REF\_NO*  
*LOCATION*  
*DT\_LAST\_HEARING*  
*NEXTACTION*  
*NEXT\_HEARING\_DT*  
*LAWYER\_NAME*  
*SEQ\_NO*  
*PROCEDNG\_SUMM*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

**MSGID**

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Deletion Full Request details of Collections module

[TOP](#)

## CLCTAGENTID

Attribute	Description				
Name	CLCTAGENTID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

[TOP](#)

## CLCTNREFNO

Attribute	Description				
Name	CLCTNREFNO				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

[TOP](#)

## SRCCD

Attribute	Description				
Name	SRCCD				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

[TOP](#)**RECORD\_DATE**

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ISN**

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**AGNCYNAME**

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**CUSTOMER**

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER\_NAME1**

Attribute	Description	
Name	CUSTOMER_NAME1	

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTSUBSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CLCTNESN

<b>Attribute</b>	<b>Description</b>	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EXTREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## RECORGN

<b>Attribute</b>	<b>Description</b>	
Name	RECORGN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,S,U



**PROCESS\_STAGE**

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,R,E,A

**TOTPTPAMT**

Attribute	Description	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ACTION\_CODE**

Attribute	Description	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**RESLT**

Attribute	Description	
Name	RESLT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**ACTINDT**

Attribute	Description
Name	ACTINDT

Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DELREASON

<b>Attribute</b>	<b>Description</b>	
Name	DELREASON	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RSLTDT

<b>Attribute</b>	<b>Description</b>	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NXTACTIONDT

<b>Attribute</b>	<b>Description</b>	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NLS\_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL

<b>Attribute</b>	<b>Description</b>
Name	ASSETQUTPRINCIPAL

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETCCY

<b>Attribute</b>	<b>Description</b>	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ASSETBRN

<b>Attribute</b>	<b>Description</b>	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

<b>Attribute</b>	<b>Description</b>	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

<b>Attribute</b>	<b>Description</b>	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

## ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PRINC\_OVERDUE

Attribute	Description	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## MATURITY\_DATE

Attribute	Description	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NO\_OF\_DAYS\_DELINQUENT

Attribute	Description	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## INT\_OVERDUE

Attribute	Description				
Name	INT_OVERDUE				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ASSET\_INT\_RATE

Attribute	Description				
Name	ASSET_INT_RATE				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## COLLTYPE

Attribute	Description				
Name	COLLTYPE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>30</td></tr></tbody></table>	Restrictions	Description	maxLength	30
	Restrictions	Description			
maxLength	30				

[TOP](#)

## Ptp

Attribute	Description						
Name	Ptp						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## PTPAMT

Attribute	Description				
Name	PTPAMT				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)**PTPDT**

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**AMTPAID**

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**PTPCHARGE**

Attribute	Description	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**TAGCCY**

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**PTPSTAT**

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>	
Name	Footer	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHKDTIME

Attribute	Description	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,A,C

[TOP](#)

## AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

<b>Attribute</b>	<b>Description</b>	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## LOCATION

<b>Attribute</b>	<b>Description</b>	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

Attribute	Description	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

Attribute	Description	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

Attribute	Description	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## SEQ\_NO

Attribute	Description	
Name	SEQ_NO	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## 2.2.2.CN-DeleteCollectionInteraction-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Main-IO

ISN

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------

Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Deletion IO Request details of Collections module

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

### 2.2.3.CN-DeleteCollectionInteraction-Res-PK-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ISN*

*Main-IO*

*ISN*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

#### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Deletion PK Response details of Collections module

[TOP](#)

## ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Deletion IO Response details of Collections module

[TOP](#)

## ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.4.CN-DeleteCollectionInteraction-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

*PROCESS\_STAGE*

*TOTPTPAMT*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*

NEXTACTION  
RSLTDT  
NXTACTIONDT

COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB

*Asset*

LOANREFNO  
ASSETQUTPRINCIPAL  
ASSETCCY  
ASSETBRN  
ASSETTOTALOVD  
ASSETSCHOVD  
ASSETUDETSTAT  
ASSETAMT  
PRINC\_OVERDUE  
MATURITY\_DATE  
NO\_OF\_DAYS\_DELINQUENT  
INT\_OVERDUE  
ASSET\_INT\_RATE  
COLLTYPE

*Ptp*

PTPAMT  
PTPDT  
AMTPAID  
PTPCHARGE  
TAGCCY  
PTPSTAT

*Footer*

CONREFNO  
MAKER  
MAKDTTIME  
CHKR  
CHKDTTIME  
EVNTSEQNO  
CONSTAT  
AUTHSTATS

*Legal*

ACTION\_REF\_NO  
COLL\_REF\_NO

LOCATION  
 DT\_LAST\_HEARING  
 NEXTACTION  
 NEXT\_HEARING\_DT  
 LAWYER\_NAME  
 SEQ\_NO  
 PROCEDNG\_SUMM  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Deletion Full Response details of Collections module

[TOP](#)

## CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CLCTNREFNO

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## RECORD\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## AGNCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTOMER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_NAME1

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

## RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,S,U

[TOP](#)

## PROCESS\_STAGE

<b>Attribute</b>	<b>Description</b>	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	I,R,E,A

[TOP](#)

## TOTPTPAMT

<b>Attribute</b>	<b>Description</b>	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ACTION\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RESLT

<b>Attribute</b>	<b>Description</b>	
Name	RESLT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NXTACTIONDT

Attribute	Description	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0



**COMNTS**

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**NLS\_HR**

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**OFSMINS**

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CUSTMAIL**

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MEDIA**

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETCCY

Attribute	Description	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ASSETUDETSTAT**

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**ASSETAMT**

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PRINC\_OVERDUE**

Attribute	Description	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**MATURITY\_DATE**

Attribute	Description	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**NO\_OF\_DAYS\_DELINQUENT**

Attribute	Description	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**INT\_OVERDUE**

Attribute	Description	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ASSET\_INT\_RATE**

Attribute	Description	
Name	ASSET_INT_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**COLLTYPE**

Attribute	Description	
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

**Ptp**

Attribute	Description	
Name	Ptp	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**PTPAMT**

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPDT

<b>Attribute</b>	<b>Description</b>	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMTPAID

<b>Attribute</b>	<b>Description</b>	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPCHARGE

<b>Attribute</b>	<b>Description</b>	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TAGCCY

<b>Attribute</b>	<b>Description</b>	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PTPSTAT

<b>Attribute</b>	<b>Description</b>	
Name	PTPSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>	
Name	Footer	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**CHKR**

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHKDTIME**

Attribute	Description	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**EVNTSEQNO**

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CONSTAT**

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,A,C

**AUTHSTATS**

Attribute	Description
Name	AUTHSTATS



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

<b>Attribute</b>	<b>Description</b>	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## LOCATION

<b>Attribute</b>	<b>Description</b>	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

<b>Attribute</b>	<b>Description</b>	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

<b>Attribute</b>	<b>Description</b>	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## SEQ\_NO

<b>Attribute</b>	<b>Description</b>
Name	SEQ_NO

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs		unbounded
	minOccurs		0

[TOP](#)

## WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attributes	Attribute		Description
	maxOccurs		unbounded

[TOP](#)

## WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

[TOP](#)

## WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

[TOP](#)

## 2.3.AuthorizeCollectionInteraction

AuthorizeCollectionInteraction

### 2.3.1.CN-AuthorizeCollectionInteraction-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Main-PK*

*ISN*

*Main-IO*

*ISN*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID



Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Authorization PK Response details of Collections module

[TOP](#)

## ISN

Attribute	Description				
Name	ISN				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Authorization IO Response details of Collections module

[TOP](#)

## ISN

Attribute	Description				
Name	ISN				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute		Description
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute		Description
Name	WCODE	

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.3.2.CN-AuthorizeCollectionInteraction-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

*PROCESS\_STAGE*

*TOTPTPAMT*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*

NEXTACTION  
RSLTDT  
NXTACTIONDT  
COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB  
Asset  
    LOANREFNO  
    ASSETQUTPRINCIPAL  
    ASSETCCY  
    ASSETBRN  
    ASSETTOTALOVD  
    ASSETSCHOVD  
    ASSETUDETSTAT  
    ASSETAMT  
    PRINC\_OVERDUE  
    MATURITY\_DATE  
    NO\_OF\_DAYS\_DELINQUENT  
    INT\_OVERDUE  
    ASSET\_INT\_RATE  
    COLLTYPE  
Ptp  
    PTPAMT  
    PTPDT  
    AMTPAID  
    PTPCHARGE  
    TAGCCY  
    PTPSTAT  
Footer  
    CONREFNO  
    MAKER  
    MAKDTTIME  
    CHKR  
    CHKDTTIME  
    EVNTSEQNO  
    CONSTAT  
    AUTHSTATS  
Legal  
    ACTION\_REF\_NO  
    COLL\_REF\_NO

[LOCATION](#)  
[DT\\_LAST\\_HEARING](#)  
[NEXTACTION](#)  
[NEXT\\_HEARING\\_DT](#)  
[LAWYER\\_NAME](#)  
[SEQ\\_NO](#)  
[PROCEDNG\\_SUMM](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request	

**Main-Full**

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Authorization Full Request details of Collections module

**CLCTAGENTID**

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**CLCTNREFNO**

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

**SRCCD**

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**RECORD\_DATE**

Attribute	Description
Name	RECORD_DATE
Datatype	Date
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## AGNCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTOMER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_NAME1

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NAME1	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**INTSUBSEQNO**

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CLCTNESN**

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**EXTREF**

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

**RECORGN**

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,S,U

**PROCESS\_STAGE**

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	I,R,E,A

[TOP](#)

## TOTPTPAMT

<b>Attribute</b>	<b>Description</b>	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ACTION\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RESLT

<b>Attribute</b>	<b>Description</b>	
Name	RESLT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACTINDT

<b>Attribute</b>	<b>Description</b>	
Name	ACTINDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DELREASON



Attribute	Description	
Name	DELREASON	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NXTACTIONDT

Attribute	Description	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## NLS\_HR

<b>Attribute</b>	<b>Description</b>	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## OFSMINS

<b>Attribute</b>	<b>Description</b>	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CUSTMAIL

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MEDIA

<b>Attribute</b>	<b>Description</b>	
Name	MEDIA	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>
Name	INTRACTIONPLACE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL

<b>Attribute</b>	<b>Description</b>	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSETCCY

Attribute	Description	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## ASSETAMT

<b>Attribute</b>	<b>Description</b>	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PRINC\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## MATURITY\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NO\_OF\_DAYS\_DELINQUENT

<b>Attribute</b>	<b>Description</b>	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INT\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**ASSET\_INT\_RATE**

Attribute		Description
Name	ASSET_INT_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**COLLTYPE**

Attribute		Description
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

**Ptp**

Attribute		Description
Name	Ptp	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**PTPAMT**

Attribute		Description
Name	PTPAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PTPDT**

Attribute		Description
Name	PTPDT	
Datatype	Date	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMTPAID

<b>Attribute</b>	<b>Description</b>	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPCHARGE

<b>Attribute</b>	<b>Description</b>	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TAGCCY

<b>Attribute</b>	<b>Description</b>	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PTPSTAT

<b>Attribute</b>	<b>Description</b>	
Name	PTPSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>
Name	Footer

Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHKR

<b>Attribute</b>	<b>Description</b>	
Name	CHKR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## EVNTSEQNO

<b>Attribute</b>	<b>Description</b>	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONSTAT

<b>Attribute</b>	<b>Description</b>	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,A,C

[TOP](#)

## AUTHSTATS

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

Attribute	Description	
Name	Legal	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

Attribute	Description	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

Attribute	Description	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## LOCATION

Attribute	Description	
Name	LOCATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

Attribute	Description	
Name	DT_LAST_HEARING	
Datatype	Date	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

<b>Attribute</b>	<b>Description</b>	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## SEQ\_NO

<b>Attribute</b>	<b>Description</b>	
Name	SEQ_NO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCDNG\_SUMM

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

### 2.3.3.CN-AuthorizeCollectionInteraction-Req-IO-MSG.xsd

#### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

#### FCUBS\_BODY

Main-IO

ISN

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description
-----------	-------------



Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Main-IO

<b>Attribute</b>	<b>Description</b>
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Authorization IO Request details of Collections module

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## 2.3.4.CN-AuthorizeCollectionInteraction-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Main-Full*

*CLCTAGENTID*

*CLCTNREFNO*

*SRCCD*

*RECORD\_DATE*

*ISN*

*AGNCYNAME*

*CUSTOMER*

*CUSTOMER\_NAME1*

*INTSUBSEQNO*

*CLCTNESN*

*EXTREF*

*RECORGN*

*PROCESS\_STAGE*

*TOTPTPAMT*

*ACTION\_CODE*

*RESLT*

*ACTINDT*

*DELREASON*

NEXTACTION  
RSLTDT  
NXTACTIONDT

COMNTS  
NLS\_HR  
OFSMINS  
CUSTMAIL  
MEDIA  
INTRACTIONPLACE  
CUSTMOB

*Asset*

LOANREFNO  
ASSETQUTPRINCIPAL  
ASSETCCY  
ASSETBRN  
ASSETTOTALOVD  
ASSETSCHOVD  
ASSETUDETSTAT  
ASSETAMT  
PRINC\_OVERDUE  
MATURITY\_DATE  
NO\_OF\_DAYS\_DELINQUENT  
INT\_OVERDUE  
ASSET\_INT\_RATE  
COLLTYPE

*Ptp*

PTPAMT  
PTPDT  
AMTPAID  
PTPCHARGE  
TAGCCY  
PTPSTAT

*Footer*

CONREFNO  
MAKER  
MAKDTTIME  
CHKR  
CHKDTTIME  
EVNTSEQNO  
CONSTAT  
AUTHSTATS

*Legal*

ACTION\_REF\_NO  
COLL\_REF\_NO

LOCATION  
 DT\_LAST\_HEARING  
 NEXTACTION  
 NEXT\_HEARING\_DT  
 LAWYER\_NAME  
 SEQ\_NO  
 PROCEDNG\_SUMM  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

**DESTINATION**

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Authorization Full Response details of Collections module

[TOP](#)

## CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## CLCTNREFNO

Attribute	Description	
Name	CLCTNREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## RECORD\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## AGNCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	AGNCYNAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTOMER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CUSTOMER\_NAME1

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

## RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	M,S,U

[TOP](#)

## PROCESS\_STAGE

<b>Attribute</b>	<b>Description</b>	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	I,R,E,A

[TOP](#)

## TOTPTPAMT

<b>Attribute</b>	<b>Description</b>	
Name	TOTPTPAMT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ACTION\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## RESLT

<b>Attribute</b>	<b>Description</b>	
Name	RESLT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## NXTACTIONDT

Attribute	Description	
Name	NXTACTIONDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**COMNTS**

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**NLS\_HR**

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**OFSMINS**

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CUSTMAIL**

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**MEDIA**

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## INTRACTIONPLACE

<b>Attribute</b>	<b>Description</b>	
Name	INTRACTIONPLACE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CUSTMOB

<b>Attribute</b>	<b>Description</b>	
Name	CUSTMOB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Asset

<b>Attribute</b>	<b>Description</b>	
Name	Asset	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## LOANREFNO

<b>Attribute</b>	<b>Description</b>	
Name	LOANREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## ASSETQUTPRINCIPAL



Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETCCY

Attribute	Description	
Name	ASSETCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ASSETUDETSTAT**

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**ASSETAMT**

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PRINC\_OVERDUE**

Attribute	Description	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**MATURITY\_DATE**

Attribute	Description	
Name	MATURITY_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**NO\_OF\_DAYS\_DELINQUENT**

Attribute	Description	
Name	NO_OF_DAYS_DELINQUENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## INT\_OVERDUE

Attribute	Description	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSET\_INT\_RATE

Attribute	Description	
Name	ASSET_INT_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## COLLTYPE

Attribute	Description	
Name	COLLTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

## Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPDT

<b>Attribute</b>	<b>Description</b>	
Name	PTPDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMTPAID

<b>Attribute</b>	<b>Description</b>	
Name	AMTPAID	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTPCHARGE

<b>Attribute</b>	<b>Description</b>	
Name	PTPCHARGE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TAGCCY

<b>Attribute</b>	<b>Description</b>	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PTPSTAT

<b>Attribute</b>	<b>Description</b>	
Name	PTPSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	P,H,B,L,C,K

[TOP](#)

## Footer

<b>Attribute</b>	<b>Description</b>	
Name	Footer	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CONREFNO

<b>Attribute</b>	<b>Description</b>	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKDTIME

<b>Attribute</b>	<b>Description</b>	
Name	MAKDTIME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

**CHKR**

Attribute	Description	
Name	CHKR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHKDTIME**

Attribute	Description	
Name	CHKDTIME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**EVNTSEQNO**

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CONSTAT**

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,A,C

**AUTHSTATS**

Attribute	Description
Name	AUTHSTATS

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	,U,A

[TOP](#)

## Legal

<b>Attribute</b>	<b>Description</b>	
Name	Legal	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ACTION\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	ACTION_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## COLL\_REF\_NO

<b>Attribute</b>	<b>Description</b>	
Name	COLL_REF_NO	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## LOCATION

<b>Attribute</b>	<b>Description</b>	
Name	LOCATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## DT\_LAST\_HEARING

<b>Attribute</b>	<b>Description</b>	
Name	DT_LAST_HEARING	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NEXTACTION

<b>Attribute</b>	<b>Description</b>	
Name	NEXTACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## NEXT\_HEARING\_DT

<b>Attribute</b>	<b>Description</b>	
Name	NEXT_HEARING_DT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## LAWYER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	LAWYER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## SEQ\_NO

<b>Attribute</b>	<b>Description</b>
Name	SEQ_NO



Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PROCEDNG\_SUMM

<b>Attribute</b>	<b>Description</b>	
Name	PROCEDNG_SUMM	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.QueryPlanActivity

Query Plan Activity

### 2.4.1.CN-QueryPlanActivity-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cnvws-Dashboard-Qry-IO*

*COLLPROD*

*ASSTPROD*

*STATE*

*COLLQUEUE*

*GRPIDS*

*COLLAGENT*

*QCOLLCTNREF*

*ASSET\_PREFERENCE*

*CIFID*

*QPRINC\_OVERDUE*

*QINT\_OVERDUE*

*QOVERDUE\_DAYS*

*QTOT\_OVERDUE*

*CUSTOMER\_NAME*

*UIDENTIFY*

QNEXT\_ACTIVITY

CURRENCY

Cnvws-Dashboard-Details

SELECT

Cnvws-Coldet-Qry

SELECT

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)



## Cnws-Dashboard-Qry-IO

Attribute	Description
Name	Cnws-Dashboard-Qry-IO
Datatype	
Description	

[TOP](#)

## COLLPROD

Attribute	Description				
Name	COLLPROD				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
	Restrictions	Description			
maxLength	4				

[TOP](#)

## ASSTPROD

Attribute	Description				
Name	ASSTPROD				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
	Restrictions	Description			
maxLength	4				

[TOP](#)

## STATE

Attribute	Description				
Name	STATE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## COLLQUEUE

Attribute	Description
Name	COLLQUEUE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## GRPIDS

<b>Attribute</b>	<b>Description</b>	
Name	GRPIDS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## COLLAGENT

<b>Attribute</b>	<b>Description</b>	
Name	COLLAGENT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## QCOLLCTNREF

<b>Attribute</b>	<b>Description</b>	
Name	QCOLLCTNREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ASSET\_PREFERENCE

<b>Attribute</b>	<b>Description</b>	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CIFID

<b>Attribute</b>	<b>Description</b>	
Name	CIFID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## QPRINC\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	QPRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## QINT\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	QINT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## QOVERDUE\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	QOVERDUE_DAYS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## QTOT\_OVERDUE

<b>Attribute</b>	<b>Description</b>
Name	QTOT_OVERDUE

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CUSTOMER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

[TOP](#)

## UIDENTIFY

<b>Attribute</b>	<b>Description</b>	
Name	UIDENTIFY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## QNEXT\_ACTIVITY

<b>Attribute</b>	<b>Description</b>	
Name	QNEXT_ACTIVITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cnws-Dashboard-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cnws-Dashboard-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SELECT

<b>Attribute</b>	<b>Description</b>	
Name	SELECT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## Cnws-Coldet-Qry

<b>Attribute</b>	<b>Description</b>	
Name	Cnws-Coldet-Qry	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SELECT

<b>Attribute</b>	<b>Description</b>	
Name	SELECT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## 2.4.2.CN-QueryPlanActivity-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cnvws-Dashboard-Qry-IO*

*COLLPROD*

*ASSTPROD*

*STATE*

*COLLQUEUE*

*GRPIDS*

*COLLAGENT*

*QCOLLCTNREF*

*ASSET\_PREFERENCE*

*CIFID*

*QPRINC\_OVERDUE*

*QINT\_OVERDUE*

*QOVERDUE\_DAYS*

*QTOT\_OVERDUE*

*CUSTOMER\_NAME*

*UIDENTIFY*

*QNEXT\_ACTIVITY*

*CURRENCY*

*Cnvws-Dashboard-Details*  
 SELECT  
*Cnvws-Coldet-Qry*  
 SELECT  
*Cnvws-Dashboard-Qry-Full*  
 BRANCH  
 COLLPROD  
 ASSTPROD  
 STATE  
 COLLQUEUE  
 GRPIDS  
 COLLAGENT  
 QCOLLCTNREF  
 ASSET\_PREFERENCE  
 CIFID  
 QPRINC\_OVERDUE  
 QINT\_OVERDUE  
 QOVERDUE\_DAYS  
 QTOT\_OVERDUE  
 CUSTOMER\_NAME  
 UIDENTIFY  
 QNEXT\_ACTIVITY  
 QNEXT\_ACTIVITY\_DATE  
*Cnvws-Dashboard-Details*  
 ASSET\_PREFERENCE  
 LCR  
 QUEUE  
 GRPIDS  
 CLCTAGENTID  
 STATE  
 SELECT  
 COLLCTNSTATUS  
 PRINC\_OVERDUE  
 INT\_OVERDUE  
 OVERDUE\_DAYS  
 TOT\_OVERDUE  
 CUSTNAME  
 UIDENTIFY  
 QNEXT\_ACTIVITY  
 CURRENCY  
 QNEXT\_ACTIVITY\_DATE  
*Cnvws-Coldet-Qry-Main*  
 ASSET\_PREFERENCE  
 CURRCOLREF\_1

*Cnvws-Coldet-Qry-Evnt*

*EVENTCD  
EVENT\_DATE  
ESN  
MAKER\_ID  
CHECKER\_ID  
EVTDES*

*Cnvws-Coldet-Qry-Ptp*

*COLLREF  
INTSEQNO\_1  
ASSET\_PREFERENCE  
PTP\_AMOUNT  
PTPCCY  
PTP\_DATE  
AMOUNTPAID  
PTP\_STATUS  
PTP\_CHARGE*

*Cnvws-Coldet-Qry*

*COLLREF  
EXTREF  
ISN  
RECORD\_DATE  
RECORGN  
PROCESS\_STAGE  
PTPASS  
SOURCE  
SELECT*

*Cnvws-Astdet-Qry*

*ASSET\_PREFERENCE  
DUEDETDT\_1  
COUNTER  
ASSTPROD  
ASSTAMNT  
ASSTBOOKDT  
ASSTVALUEDT  
NAME  
ASSTCCY  
ASSRMATDT*

*Cnvws-Astdet-Qry-Duedet*

*SOURCE  
ASSETREF  
COLLCTNREF  
COMP  
TOT\_AMT\_DUE*



[EARDUEDT](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cnvws-Dashboard-Qry-IO**

Attribute	Description
Name	Cnvws-Dashboard-Qry-IO
Datatype	
Description	

[TOP](#)**COLLPROD**

Attribute	Description	
Name	COLLPROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**ASSTPROD**

Attribute	Description	
Name	ASSTPROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)**STATE**

Attribute	Description	
Name	STATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**COLLQUEUE**

Attribute	Description	
Name	COLLQUEUE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**GRPIDS**

Attribute	Description	
Name	GRPIDS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**COLLAGENT**

Attribute	Description	
Name	COLLAGENT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

**QCOLLCTNREF**

Attribute	Description	
Name	QCOLLCTNREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**ASSET\_PREFERENCE**

Attribute	Description	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## QPRINC\_OVERDUE

Attribute	Description	
Name	QPRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## QINT\_OVERDUE

Attribute	Description	
Name	QINT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## QOVERDUE\_DAYS

Attribute	Description	
Name	QOVERDUE_DAYS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## QTOT\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	QTOT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## CUSTOMER\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

[TOP](#)

## UIDENTIFY

<b>Attribute</b>	<b>Description</b>	
Name	UIDENTIFY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## QNEXT\_ACTIVITY

<b>Attribute</b>	<b>Description</b>	
Name	QNEXT_ACTIVITY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Cnws-Dashboard-Details

Attribute	Description	
Name	Cnws-Dashboard-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SELECT

Attribute	Description	
Name	SELECT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## Cnws-Coldet-Qry

Attribute	Description	
Name	Cnws-Coldet-Qry	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SELECT

Attribute	Description	
Name	SELECT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## Cnvws-Dashboard-Qry-Full

<b>Attribute</b>	<b>Description</b>
Name	Cnvws-Dashboard-Qry-Full
Datatype	
Description	

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## COLLPROD

<b>Attribute</b>	<b>Description</b>	
Name	COLLPROD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## ASSTPROD

<b>Attribute</b>	<b>Description</b>	
Name	ASSTPROD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## STATE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	STATE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## COLLQUEUE

<b>Attribute</b>	<b>Description</b>	
Name	COLLQUEUE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## GRPIDS

<b>Attribute</b>	<b>Description</b>	
Name	GRPIDS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## COLLAGENT

<b>Attribute</b>	<b>Description</b>	
Name	COLLAGENT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## QCOLLCTNREF

<b>Attribute</b>	<b>Description</b>	
Name	QCOLLCTNREF	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## ASSET\_PREFERENCE

<b>Attribute</b>	<b>Description</b>	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CIFID

<b>Attribute</b>	<b>Description</b>	
Name	CIFID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

[TOP](#)

## QPRINC\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	QPRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## QINT\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	QINT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## QOVERDUE\_DAYS

Attribute	Description	
Name	QOVERDUE_DAYS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## QTOT\_OVERDUE

Attribute	Description	
Name	QTOT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## CUSTOMER\_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

## UIDENTIFY

Attribute	Description	
Name	UIDENTIFY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

## QNEXT\_ACTIVITY

Attribute	Description	
Name	QNEXT_ACTIVITY	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

[TOP](#)

## QNEXT\_ACTIVITY\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	QNEXT_ACTIVITY_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Cnws-Dashboard-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cnws-Dashboard-Details	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ASSET\_PREFERENCE

<b>Attribute</b>	<b>Description</b>	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## LCR

<b>Attribute</b>	<b>Description</b>	
Name	LCR	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## QUEUE

Attribute	Description				
Name	QUEUE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## GRPIDS

Attribute	Description				
Name	GRPIDS				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## CLCTAGENTID

Attribute	Description				
Name	CLCTAGENTID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

[TOP](#)

## STATE

Attribute	Description				
Name	STATE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

[TOP](#)

## SELECT

Attribute	Description
-----------	-------------



Name	SELECT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

[TOP](#)

## COLLECTNSTATUS

<b>Attribute</b>	<b>Description</b>	
Name	COLLECTNSTATUS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## PRINC\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	PRINC_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INT\_OVERDUE

<b>Attribute</b>	<b>Description</b>	
Name	INT_OVERDUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## OVERDUE\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	OVERDUE_DAYS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

**TOT\_OVERDUE**

Attribute	Description	
Name	TOT_OVERDUE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**CUSTNAME**

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

**UIDENTIFY**

Attribute	Description	
Name	UIDENTIFY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**QNEXT\_ACTIVITY**

Attribute	Description	
Name	QNEXT_ACTIVITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

**CURRENCY**

Attribute	Description
Name	CURRENCY

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## QNEXT\_ACTIVITY\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	QNEXT_ACTIVITY_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Cnvws-Coldet-Qry-Main

<b>Attribute</b>	<b>Description</b>	
Name	Cnvws-Coldet-Qry-Main	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSET\_PREFERENCE

<b>Attribute</b>	<b>Description</b>	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CURRCOLREF\_1

<b>Attribute</b>	<b>Description</b>	
Name	CURRCOLREF_1	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

**Cnvws-Coldet-Qry-Evnt**

Attribute	Description	
Name	Cnvws-Coldet-Qry-Evnt	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**EVENTCD**

Attribute	Description	
Name	EVENTCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

**EVENT\_DATE**

Attribute	Description	
Name	EVENT_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**ESN**

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**MAKER\_ID**

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKER\_ID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## EVTDES

<b>Attribute</b>	<b>Description</b>	
Name	EVTDES	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## Cnvws-Coldet-Qry-Ptp

<b>Attribute</b>	<b>Description</b>	
Name	Cnvws-Coldet-Qry-Ptp	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## COLLREF

<b>Attribute</b>	<b>Description</b>	
Name	COLLREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

**INTSEQNO\_1**

Attribute	Description	
Name	INTSEQNO_1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**ASSET\_PREFERENCE**

Attribute	Description	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

**PTP\_AMOUNT**

Attribute	Description	
Name	PTP_AMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**PTPCCY**

Attribute	Description	
Name	PTPCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PTP\_DATE**

Attribute	Description
Name	PTP_DATE

Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMOUNTPAID

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTPAID	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PTP\_STATUS

<b>Attribute</b>	<b>Description</b>	
Name	PTP_STATUS	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## PTP\_CHARGE

<b>Attribute</b>	<b>Description</b>	
Name	PTP_CHARGE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## Cnvws-Coldet-Qry

<b>Attribute</b>	<b>Description</b>	
Name	Cnvws-Coldet-Qry	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## COLLREF

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	COLLREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## EXTREF

<b>Attribute</b>	<b>Description</b>	
Name	EXTREF	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	30

[TOP](#)

## ISN

<b>Attribute</b>	<b>Description</b>	
Name	ISN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RECORD\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RECORGN

<b>Attribute</b>	<b>Description</b>	
Name	RECORGN	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## PROCESS\_STAGE

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## PTPASS

Attribute	Description	
Name	PTPASS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SELECT

Attribute	Description	
Name	SELECT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

[TOP](#)

## Cnvws-Astdet-Qry

Attribute	Description	
Name	Cnwvs-Astdet-Qry	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ASSET\_PREFERENCE

Attribute	Description	
Name	ASSET_PREFERENCE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## DUEDETD\_1

Attribute	Description	
Name	DUEDETD_1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## COUNTER

Attribute	Description	
Name	COUNTER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

[TOP](#)

## ASSTPROD

Attribute	Description	
Name	ASSTPROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	4

[TOP](#)

## ASSTAMNT

<b>Attribute</b>	<b>Description</b>	
Name	ASSTAMNT	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSTBOOKDT

<b>Attribute</b>	<b>Description</b>	
Name	ASSTBOOKDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ASSTVALUEDT

<b>Attribute</b>	<b>Description</b>	
Name	ASSTVALUEDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## ASSTCCY

<b>Attribute</b>	<b>Description</b>	
Name	ASSTCCY	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## ASSRMATDT

Attribute	Description	
Name	ASSRMATDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## Cnvws-Astdet-Qry-Duedet

Attribute	Description	
Name	Cnvws-Astdet-Qry-Duedet	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## ASSETREF

Attribute	Description	
Name	ASSETREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## COLLCTNREF

Attribute	Description	
Name	COLLCTNREF	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## COMP

<b>Attribute</b>	<b>Description</b>	
Name	COMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## TOT\_AMT\_DUE

<b>Attribute</b>	<b>Description</b>	
Name	TOT_AMT_DUE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EARDUEDT

<b>Attribute</b>	<b>Description</b>	
Name	EARDUEDT	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



**Collections Service**  
**[August] [2014]**

**Oracle Financial Services software Limited**  
**Oracle Park**  
**Off Western Express Highway**  
**Goregaon (East)**  
**Mumbai, Maharashtra 400 063**  
**India**

**Worldwide Inquiries:**  
**Phone: +91 22 6718 3000**  
**Fax: +91 22 6718 3001**  
**[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)**

**Copyright © [2007], [2014], Oracle and/or its affiliates. All rights reserved.**

**Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.**

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

**This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.**

**This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.**

**The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.**

**This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any**



kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.